

## EUROLITE Set LED IP PAR 7x8W QCL Spot + 2x Diffuser Cover (15x60° and 40°): 20000670

Weather-proof spotlight with 7 QCL LEDs and RGBW color mixing incl. 2x frost filters

GTIN: 4026397362312



**List price: 296.31 €**

incl. 19% VAT.

### Features:

#### EUROLITE LED IP PAR 7x8W QCL Spot

Weather-proof (IP65) spotlight with 7 x 8 W LED and 4in1 QCL RGBW color mixing

- 7 powerful LEDs 8 W high-power 4in1 QCL RGBW (homogenous color mix)
- Color blend stepless; color change adjustable; color fade adjustable; Dimmer electronic
- Strobe effect
- Direct color selection for 25 preset colors
- The device is cooled by passive convection cooling
- Control via DMX; stand-alone; IR remote control
- Preprogrammed in LED PC-Control 512; EASY SHOW 1; LED EASY OPERATOR 4x4; LED EASY OPERATOR 4x6; LED EASY OPERATOR DELUXE; Light Captain; EASY SHOW 2; EASY SHOW 3; Colorchief
- Flicker-free
- With a beam angle of 15°
- With double bracket
- LCD display
- Mains input and output for power linking up to 8 units
- Suitable for outdoor use IP65
- With pressure compensation membrane
- For application areas such as: Installation; stage; rental; architecture
- Silent operation
- Application possibility: Standing; suspended; on stand

#### Package contents

- 1 x device, 1 x power cord, 1 x remote control, 1 x battery, 1 x user manual

### Logistic

EAN / GTIN: 4026397362312

Weight: 5,20 kg

Length: 0.41 m

Width: 0.31 m

Height: 0.28 m

## EUROLITE Diffuser Cover 15x60° for IP PAR-7<p class='attributgroup'>Package contents

- 1 x beamshaper

## EUROLITE Diffuser Cover 40° for IP PAR-7

- With a beam angle of 40°

### Package contents

- 1 x frost filter

## Technical specifications:

Weight:	4,27 kg
---------	---------

## EUROLITE LED IP PAR 7x8W QCL Spot

Power supply:	100-240 V AC, 50/60 Hz
Power consumption:	55 W
IP classification:	IP65
Power connection:	Mains input via IP T-Con (M) mounting version power supply cord with safety plug
Power output:	IP T-Con (F) mounting version
Lamp type:	LED lamp
LED type:	7 x 8 W high-power 4in1 QCL RGBW (homogenous color mix)
Flash rate:	0 - 20 Hz
DMX channels:	3; 4; 5; 6; 10
DMX input:	1 x 3-pin XLR (M) mounting version IP
DMX output:	1 x 3-pin XLR (F) mounting version IP
Cooling:	Passive convection cooling
Control:	DMX; stand-alone; IR remote control
Preprogrammed in:	LED PC-Control 512; EASY SHOW 1; LED EASY OPERATOR 4x4; LED EASY OPERATOR 4x6; LED EASY OPERATOR DELUXE; Light Captain; EASY SHOW 2; EASY SHOW 3; Colorchief
Projection:	Flicker-free
Beam angle:	15°
Beam angle (1/2 peak):	15°
Housing color:	Black
Attachment system:	Double bracket
Display type:	LCD display
Material:	Aluminum casting
Dimensions:	Width: 25,5 cm Depth: 15,3 cm Height: 28,1 cm

Weight:	4,07 kg
Noise classification:	Class 0 (no noise at all)
Photobiological safety:	Risk Group 0
Mounting bracket	
Diameter mounting holes:	3 x Ø11mm
Material:	Metal, 2,5 mm
Power cord	
Cable construction:	3 x 1,0 mm² H05RN-F
Cable length:	Approx. 1,2 m
Remote control	
Battery:	1 x button cell 3.0 V CR2025 lithium manganese built-in
Legal specifications	
Special product:	Not designed for household room illumination
Intended use:	Show effect lighting

#### **EUROLITE Diffuser Cover 15x60° for IP PAR-7**

Dimensions:	Height: 0,65 cm Diameter: Ø 18,50 cm
Weight:	0,10 kg

#### **EUROLITE Diffuser Cover 40° for IP PAR-7**

Beam angle:	40°
Beam angle (1/2 peak):	40°
Dimensions:	Depth: 0,6 cm Diameter: Ø 18,50 cm
Weight:	0,10 kg
Ring	
Material:	Plastic
Color:	Black
Ring diameter:	Inside: 157 mm