

## EUROLITE Set LED IP PAR 12x8W QCL Spot + 2x Diffuser Cover (15x60° and 40°) 20000671

Weather-proof spotlight with 12 QCL LEDs and RGBW color mixing incl. 2x frost filters

GTIN: 4026397362329



15x60°



40°



### Features:

- 12 LEDs 8 W 4in1 QCL RGBW (homogenous color mix)
- Color blend stepless; color change adjustable; color fade adjustable; Dimmer electronic
- Strobe effect
- Direct color selection for 25 preset colors
- The device is cooled by passive convection cooling
- Control via DMX; IR remote control; stand-alone
- Fixtures available for LED PC-Control 512; EASY SHOW 1; LED EASY OPERATOR 4x4; LED EASY OPERATOR 4x6; LED EASY OPERATOR DELUXE; Light Captain; EASY SHOW 2; EASY SHOW 3; Colorchief
- Flicker-free
- With a beam angle of 15°
- With double bracket
- LCD display
- Mains input and output for power linking up to 8 units
- Suitable for outdoor use IP65
- With pressure compensation membrane
- For application areas such as: Architecture; stage; clubs/dancing school; wedding/gala/events; theater; rental; video and photography
- Silent operation
- Application possibility: Standing; suspended; on stand

### Logistic

EAN / GTIN: 4026397362329

Weight: 6,60 kg

Length: 0.41 m

Width: 0.31 m

Height: 0.28 m

### Technical specifications:

Weight: 5.43 kg

---

### **EUROLITE LED IP PAR 12x8W QCL Spot**

Power supply:	100-240 V AC, 50/60 Hz
Power consumption:	75 W
IP classification:	IP65
Protection class:	Protection class I
Power connection:	Mains input via IP T-Con (M) mounting version power supply cord with safety plug
Power output:	IP T-Con (F) mounting version
Fuse:	T 5 A fuse fix on board
Lamp type:	LED lamp
LED type:	12 x 8 W 4in1 QCL RGBW (homogenous color mix)
Flash rate:	0.5 - 24 Hz
DMX channels:	3; 4; 5; 6; 10
DMX input:	3-pin XLR (M) mounting version IP
DMX output:	3-pin XLR (F) mounting version IP
Cooling:	Passive convection cooling
Control:	DMX; IR remote control; stand-alone
Fixtures available for:	LED PC-Control 512; EASY SHOW 1; LED EASY OPERATOR 4x4; LED EASY OPERATOR 4x6; LED EASY OPERATOR DELUXE; Light Captain; EASY SHOW 2; EASY SHOW 3; Colorchief
Projection:	Flicker-free
PWM frequency:	5900 Hz
Beam angle:	15°
Beam angle (1/2 peak):	15°
Beam angle (1/10 peak):	30°
Housing color:	Black
Attachment system:	Double bracket
Display type:	LCD display
Material:	Aluminum casting
Dimensions:	Width: 28.5 cm Depth: 15.3 cm Height: 31.35 cm
Weight:	5.20 kg
Noise classification:	Class 0 (no noise at all); Class 0 (no noise at all)
Photobiological safety:	Risk Group 0
Diameter mounting holes:	3 x Ø11mm
Material:	Metal, 2.5 mm
Cable construction:	3 x 1.0 mm <sup>2</sup> H05RN-F
Cable length:	Approx. 1.2 m
Battery:	1 x button cell 3.0 V CR2025 lithium manganese
Special product:	Not designed for household room illumination

Intended use: Show effect lighting

---

**EUROLITE Diffuser Cover 15x60° for IP PAR-12**

Dimensions: Height: 0.7 cm  
Diameter: Ø 22.20 cm

---

Weight: 0.11 kg

---

**EUROLITE Diffuser Cover 40° for IP PAR-12**

Dimensions: Height: 0.65 cm  
Diameter: Ø 22.20 cm

---

Weight: 0.12 kg

---

**Scope of delivery:**

---

**1 x EUROLITE LED IP PAR 12x8W QCL Spot**

1 x spotlight  
1 x power cord  
1 x remote control  
1 x battery  
1 x user manual

**1 x EUROLITE Diffuser Cover 15x60° for IP PAR-12**

1 x beamshaper

**1 x EUROLITE Diffuser Cover 40° for IP PAR-12**

1 x frost filter