

## EUROLITE Set 4x LED IP Tourlight 120 QCL + Case

4x weather-proof LED spot with 120 W RGBW LED including PRO flightcase

Art. No.: 2000674

GTIN: 4026397360417



**The article is no longer in our assortment.**

### Features:

#### EUROLITE LED IP Tourlight 120 QCL

Weather-proof LED spotlight (IP65) with 120 W RGBW LED

- High-performance LED spot for outdoor applications
- Equipped with a 120-watt RGBW COB LED
- Chip-on-board technology makes for homogeneous color mixing
- Beam angle: 11° (1/2 peak), 26° (1/10 peak)
- For architectural and stage lighting
- Weather-proof metal housing (IP65)
- Stepless RGBW color blend, color change, color fade, dimmer and strobe effect
- 63 integrated color macros
- User-defined color settings can be set and saved individually
- Different dimmer curves and dimmer speeds (step response) adjustable
- DMX-controlled operation or stand-alone operation with master/slave function
- Addressing and setting via control board with four touch operating buttons and LCD
- Swivel mounting bracket
- Additional bracket for floor use
- Hanging installation via quick-lock Omega holder (included in delivery)
- IP T-Con terminals for power linking up to 8 units
- 1 powerful LED 120 W COB (chip-on-board) 4in1 QCL RGBW (homogenous color mix)
- The device is cooled by temperature-controlled fan
- Control via Master/slave function; stand-alone
- Preprogrammed in Light J; LED PC-Control 512; EASY SHOW 1; LED EASY OPERATOR 4x4; LED EASY OPERATOR 4x6; LED EASY OPERATOR DELUXE; Light Captain
- Flicker-free
- With a beam angle of 11°
- Suitable for outdoor use IP65

### Logistic

EAN / GTIN: 4026397360417

### Package contents

- 1 x spotlight, 1 x user manual, 1 x power cord, 1 x omega bracket, 1 x cover

### ROADINGER Flightcase 4x LED IP Tourlight 120

Trunk case, PRO version

- For optimal security
- With accessory compartment
- High-quality workmanship with birch multiplex 7 mm, dark brown, laminated
- Interior with foam padding
- Aluminum profile frames 30mm with rounded edges
- 2 hinged, chromium plated case handles
- 2 chrome tip-over locks
- 2 high-quality butterfly locks
- Branded hardware
- For further information about this product, please refer to the Data Sheet under "Downloads"

### Technical specifications:

---

Weight: 36,25 kg

---

### EUROLITE LED IP Tourlight 120 QCL

|                         |   |
|-------------------------|---|
| Power supply:           | 100-240 V AC, 50/60 Hz  |
| Power consumption:      | 125 W   |
| IP classification:      | IP65  |
| Power connection:       | Mains input via IP T-Con (M) mounting version power supply cord with safety plug (provided)                                     |
| Power output:           | 1 x IP T-Con (F) mounting version   |
| LED:                    | 1 x 120 W COB (chip-on-board) 4in1 QCL RGBW (homogenous color mix)  |
| Flash rate:             | 1 - 20 Hz   |
| DMX channels:           | 1; 4; 8; 9  |
| DMX input:              | 1 x 3-pin XLR (M) mounting version IP   |
| DMX output:             | 1 x 3-pin XLR (F) mounting version IP   |
| Cooling:                | Temperature-controlled fan  |
| Control:                | Master/slave function; stand-alone  |
| Preprogrammed in:       | Light J; LED PC-Control 512; EASY SHOW 1; LED EASY OPERATOR 4x4; LED EASY OPERATOR 4x6; LED EASY OPERATOR DELUXE; Light Captain |
| Projection:             | Flicker-free  |
| Beam angle:             | 11°   |
| Beam angle (1/2 peak):  | 11°   |
| Beam angle (1/10 peak): | 26°   |
| Housing color:          | Black   |
| Dimensions:             | Width: 27 cm<br>Depth: 27 cm<br>Height: 30,5 cm   |

---

|                      |  |
|----------------------|--|
| Weight:              | 5,90 kg                                      |
| Legal specifications |  |
| Special product:     | Not designed for household room illumination |
| Intended use:        | Show effect lighting                         |

#### **ROADINGER Flightcase 4x LED IP Tourlight 120**

|                          |   |
|--------------------------|---|
| Maximum load:            | 50 kg   |
| Aluminum profile frames: | 30 mm   |
| Case handle:             | 2 pc/pcs                                      |
| Stop hinge:              | 2 pc/pcs                                      |
| Lock:                    | Butterfly lock: 2 pc/pcs                      |
| Use of brands:           | Branded hardware                              |
| Material:                | Birch multiplex, 7 mm                         |
| Color:                   | Dark brown, laminated                         |
| Device compartment:      | 28 cm x 19 cm x 30,5 cm                       |
| Middle compartment:      | 10,5 cm x 41 cm x 30,5 cm                     |
| Inside dimensions:       | 66,5 cm x 41 cm x 30,5 cm                     |
| Dimensions:              | Width: 74 cm<br>Depth: 40 cm<br>Height: 45 cm |
| Weight:                  | 12,65 kg                                      |