

## EUROLITE Set 4x LED Super Strobe ABL + Case

4x 3in1 LED effect light with RGB color mixing including PRO flightcase

Art. No.: 20000679

GTIN: 4026397360943



**List price: 1724.31 €**

incl. 19% VAT.

### Features:

#### EUROLITE LED Super Strobe ABL

LED lighting effect with threefold effects

- Flat metal housing with integrated wall holders
- 216 powerful LEDs 0,5 W SMD 5730 cold white (CW)
- 144 powerful LEDs SMD 5050 3in1 TCL RGB (homogenous color mix)<BR> LEDs controlled separately
- Dimmer electronic; color blend stepless
- Strobe effect; wash effect; Blinder effect
- 17 integrated show programs
- Control via master/slave function; DMX; stand-alone; sound to light
- Preprogrammed in LED PC-Control 512; EASY SHOW 1; Light Captain
- Flicker-free
- With mounting bracket
- 4 digit 7-segment LED display
- Mains input and output for power linking up to 8 units
- For application areas such as: Clubs/dancing school; stage; restaurants, bars and hotels; mobile djs / entertainer
- Very quiet working noise
- Application possibility: Suspended; on stand

#### Package contents

- 1 x light effect, 1 x mounting bracket, 1 x power cord, 2 x knurled screw, 2 x washer, 1 x user manual

### Logistic

EAN / GTIN: 4026397360943

Weight: 27,40 kg

Length: 0.00 m

Width: 0.00 m

Height: 0.00 m

#### ROADINGER Flightcase 4x LED Super Strobe

Trunk case, HIGHLINE version

- For optimal security
- With accessory compartment
- High-quality workmanship with birch multiplex 7 mm, black, laminated
- Interior with felt cover
- Aluminum profile frames 30mm with rounded edges
- 3 hinged, chromium plated case handles
- 3 chrome tip-over locks
- 2 high-quality butterfly locks
- Rubber feet
- Branded hardware
- For further information about this product, please refer to the Data Sheet under "Downloads"

## Technical specifications:

|         |          |
|---------|----------|
| Weight: | 30,89 kg |
|---------|----------|

### EUROLITE LED Super Strobe ABL

|                          |   |
|--------------------------|---|
| Power supply:            | 100-240 V AC, 50/60 Hz  |
| Power consumption:       | 95 W  |
| IP classification:       | IP20  |
| Protection class:        | Protection class I  |
| Power connection:        | Mains input via P-Con (blue), mounting version<br>power supply cord with safety plug (provided) |
| Power output:            | P-Con (gray), mounting version  |
| Fuse:                    | 5 x 20 mm, F 2 A fuse replaceable   |
| LED type:                | 216 x 0,5 W SMD 5730 cold white (CW)<br>144 x SMD 5050 3in1 TCL RGB (homogenous<br>color mix)   |
| DMX channels:            | 7; 13; 22; 148  |
| DMX input:               | 1 x 3-pin XLR (M) mounting version  |
| DMX output:              | 1 x 3-pin XLR (F) mounting version  |
| Control:                 | Master/slave function; DMX; stand-alone; sound<br>to light                                      |
| Preprogrammed in:        | LED PC-Control 512; EASY SHOW 1; Light<br>Captain   |
| Projection:              | Flicker-free  |
| Beam angle (1/2 peak):   | 120°  |
| Attachment system:       | Mounting bracket  |
| Display type:            | 4 digit 7-segment LED display   |
| Diameter mounting holes: | 2 x Ø5mm; 6 x Ø9mm  |
| Dimensions:              | Width: 45,5 cm<br>Depth: 8,5 cm<br>Height: 25,5 cm  |
| Weight:                  | 4,26 kg   |
| Noise classification:    | Class 1 (very slight noise, suitable for noise-<br>sensitive environments)                      |

Mounting bracket

|                          |  |
|--------------------------|--|
| Diameter mounting holes: | 3 x Ø11mm; 2 x Ø8mm                          |
| Material:                | Metal, 2 mm                                  |
| Power cord               |  |
| Cable construction:      | 3 x 1,0 mm² H05RN-F                          |
| Cable length:            | Approx. 1,5 m                                |
| Legal specifications     |  |
| Special product:         | Not designed for household room illumination |
| Intended use:            | Show effect lighting                         |

#### **ROADINGER Flightcase 4x LED Super Strobe**

|                          |   |
|--------------------------|---|
| Maximum load:            | 50 kg   |
| Aluminum profile frames: | 30 mm   |
| Case handle:             | 3 pc/pcs  |
| Stop hinge:              | 3 pc/pcs  |
| Lock:                    | Butterfly lock: 2 pc/pcs                          |
| Transport aid:           | Rubber feet                                       |
| Use of brands:           | Branded hardware                                  |
| Material:                | Birch multiplex, 7 mm                             |
| Color:                   | Black, laminated; dark brown, laminated           |
| Inside dimensions:       | 60 cm x 40,5 cm x 31 cm                           |
| Device compartment:      | 9 cm x 47 cm x 31 cm                              |
| Accessory compartment:   | 12 cm x 40 cm x 31 cm                             |
| Dimensions:              | Width: 64,5 cm<br>Depth: 45 cm<br>Height: 34,5 cm |
| Weight:                  | 13,85 kg  |