

EUROLITE Set 4x LED Super Strobe ABL + Case

4x 3in1 LED effect light with RGB color mixing including PRO flightcase

Art. No.: 2000679

GTIN: 4026397360943



List price: 1724.31 €

incl. 19% VAT.

Features:

EUROLITE LED Super Strobe ABL

LED lighting effect with threefold effects

- Flat metal housing with integrated wall holders
- 216 powerful LEDs 0,5 W SMD 5730 cold white (CW)
- 144 powerful LEDs SMD 5050 3in1 TCL RGB (homogenous color mix) LEDs controlled separately
- Strobe effect; Wash effect; Blinder effect
- 17 integrated show programs
- Control via Master/slave function; DMX; stand-alone; Sound to light
- Flicker-free
- With Mounting bracket
- 4 digit 7-segment LED display
- Dimmer electronic; color blend stepless
- Mains input and output for power linking up to 8 units
- Preprogrammed in LED PC-Control 512; EASY SHOW 1; Light Captain
- For application areas such as: Clubs/dancing school; Stage; restaurants, bars and hotels; mobile djs / entertainer
- Very quiet working noise
- Application possibility: Suspended; on stand

Package contents

- 1 x light effect, 1 x mounting bracket, 1 x power cord, 2 x knurled screw, 2 x washer, 1 x user manual

Logistic

EAN / GTIN: 4026397360943

Weight: 27,40 kg

Length: 0.00 m

Width: 0.00 m

Height: 0.00 m

ROADINGER Flightcase 4x LED Super Strobe

Trunk case, PRO version

- For optimal security
- With accessory compartment
- High-quality workmanship with birch multiplex 7 mm, black, laminated
- Interior with felt cover
- Aluminum profile frames 30mm with rounded edges
- 3 hinged, chromium plated case handles
- 3 chrome tip-over locks
- 2 high-quality butterfly locks
- Rubber feet
- Branded hardware
- For further information about this product, please refer to the Data Sheet under "Downloads"

Technical specifications:

Weight: 30,89 kg

EUROLITE LED Super Strobe ABL

| | |
|------------------------|--|
| Power supply: | 100-240 V AC, 50/60 Hz |
| Power consumption: | 95 W |
| Protection class: | Protection class I |
| Power connection: | Mains input via P-Con (blue), mounting version power supply cord with safety plug (provided) |
| Power output: | P-Con (gray), mounting version |
| Fuse: | 5 x 20 mm, F 2 A Fuse replaceable |
| LED: | 216 x 0,5 W SMD 5730 cold white (CW) 144 x SMD 5050 3in1 TCL RGB (homogenous color mix) |
| DMX channels: | 7; 13; 22; 148 |
| DMX input: | 1 x 3-pin XLR (M) mounting version |
| DMX output: | 1 x 3-pin XLR (F) mounting version |
| Control: | Master/slave function; DMX; stand-alone; Sound to light |
| Preprogrammed in: | LED PC-Control 512; EASY SHOW 1; Light Captain |
| Projection: | Flicker-free |
| Beam angle (1/2 peak): | 120° |
| Attachment system: | Mounting bracket |
| Display type: | 4 digit 7-segment LED display |
| Dimensions: | Width: 45,5 cm Depth: 8,5 cm Height: 25,5 cm |
| Weight: | 4,26 kg |
| Noise classification: | Class 1 (very slight noise, suitable for noise-sensitive environments) |
| Power cord | |
| Cable construction: | 3 x 1,0 mm ² H05RN-F |
| Cable length: | Approx. 1,5 m |

Mounting bracket

| | |
|--------------------------|--|
| Diameter mounting holes: | 3 x Ø11mm; 2 x Ø8mm |
| Material: | Metal, 2 mm |
| Legal specifications | |
| Special product: | Not designed for household room illumination |
| Intended use: | Show effect lighting |

ROADINGER Flightcase 4x LED Super Strobe

| | |
|--------------------------|---|
| Maximum load: | 50 kg |
| Aluminum profile frames: | 30 mm |
| Case handle: | 3 pc/pcs |
| Stop hinge: | 3 pc/pcs |
| Lock: | Butterfly lock: 2 pc/pcs |
| Transport aid: | Rubber feet |
| Use of brands: | Branded hardware |
| Material: | Birch multiplex, 7 mm |
| Color: | Black, laminated; dark brown, laminated |
| Inside dimensions: | 60 cm x 40,5 cm x 31 cm |
| Device compartment: | 9 cm x 47 cm x 31 cm |
| Accessory compartment: | 12 cm x 40 cm x 31 cm |
| Dimensions: | Width: 64,5 cm Depth: 45 cm Height: 34,5 cm |
| Weight: | 13,85 kg |
