

### **EUROLITE Set 4x LED THA-150F + Case**

4x fresnel spot with 170 W warm white/amber LED including PRO flightcase

Art. No.: 20000681 GTIN: 4026397360974







List price: 4342.31 €

incl. 19% VAT.

### Features:

## **EUROLITE LED THA-150F Theater Spot**

Fresnel spotlight, dim to warm, 170 W warm white/amber LED, CRI >90, quiet, DMX

- New LED technology that simulates the color temperature curve of a halogen lamp when dimming
- Rugged metal housing
- 1 powerful LED 170 W COB (chip-on-board) Dim to warm (homogenous color mix)
- Exact 16 bit resolution at Dimmer
- Zoom motor driven
- Color blend stepless; Dimmer electronic; Dimmer speed (step response) adjustable; dimmer curves adjustable
- Strobe effect
- The device is cooled by temperature-controlled fan
- Control via RDM; DMX
- Preprogrammed in Light'J; Light Captain
- Flicker-free
- With a beam angle of 8° 55°
- Very high color rendering index (CRI)
- With mounting bracket
- LCD display
- Rubber feet
- Mains input and output for power linking up to 8 units
- For application areas such as: Trade fair and shop fitting; installation; stage; theater
- Application possibility: Suspended; on stand

# Package contents

- 1 x spotlight, 1 x power cord, 1 x barndoor, 1 x filter frame, 1 x user manual

### Logistic

EAN / GTIN: 4026397360974

Weight: 78,00 kg Length: 1.20 m Width: 0.80 m Heigth: 0.85 m Bulky product

#### ROADINGER Flightcase 4x LED THA-150F Theater Spot

Trunk case with castors, PRO version

- With accessory compartment
- With 4 device compartments
- High-quality workmanship with birch multiplex 7 mm, dark brown, laminated
- Interior with foam padding
- Aluminum profile frames 25mm with rounded edges
- 4 hinged, chromium plated case handles
- 3 chrome tip-over locks
- 2 high-quality butterfly locks
- 4 x castors with 2 locking brakes
- 4 x built-in stacking trays in the cover
- Branded hardware

## **Technical specifications:**

Weight: 66,50 kg

#### **EUROLITE LED THA-150F Theater Spot**

| Power supply:                | 100-240 V AC, 50/60 Hz   |
|------------------------------|--|
| Power consumption:           | 150 W  |
| IP classification:           | IP20   |
| Protection class:            | Protection class I   |
| Power connection:            | Mains input via P-Con (blue), mounting version power supply cord with safety plug included |
| Power output:                | P-Con (gray), mounting version   |
| LED type:                    | 1 x 170 W COB (chip-on-board) Dim to warm (homogenous color mix)                           |
| Equipment:                   | Zoom motor driven  |
| DMX channels:                | 2; 6; 7  |
| DMX input:                   | 1 x 3-pin XLR (M) mounting version<br>1 x 5-pin XLR (M) mounting version                   |
| DMX output:                  | 1 x 3-pin XLR (F) mounting version<br>1 x 5-pin XLR (F) mounting version                   |
| Cooling:                     | Temperature-controlled fan   |
| Control:                     | RDM; DMX   |
| Preprogrammed in:            | Light´J; Light Captain   |
| Projection:                  | Flicker-free   |
| Beam angle:                  | 8° - 55°   |
| Beam angle (1/2 peak):       | 8 - 39°  |
| Beam angle (1/10 peak):      | 12 - 55°   |
| Color rendering index (CRI): | 96 Ra  |
| Luminous flux:               | 5093 lm  |
| Housing color:               | Black  |
| Attachment system:           | Mounting bracket   |
|                              |  |

| Display type:                    | LCD display  |
|----------------------------------|--|
| Transport aid:                   | Rubber feet  |
| Material:                        | Aluminum casting; metal                                |
| Slot for spot length:            | 20 cm x 20 cm  |
| Dimensions:                      | Length: 45,7 cm<br>Width: 33,6 cm<br>Height: 39,8 cm   |
| Weight:                          | 9,40 kg  |
| Noise classification:            | Class 2 (slight noise)                                 |
| Energy efficiency class (A - G): | G  |
| EPREL-Nr:                        | 1243870  |
| Mounting bracket                 |  |
| Diameter mounting holes:         | 5 x Ø10mm  |
| Material:                        | Aluminum casting, 6,5 mm                               |
| Power cord                       |  |
| Cable construction:              | 3 x 1,5 mm² H05VV-F                                    |
| Cable length:                    | Approx. 1,3 m  |
| Barndoor                         |  |
| Material:                        | Aluminum, 1,5 mm; metal, 1 mm                          |
| Ring diameter:                   | Outside: 198 mm<br>Inside: 220 mm                      |
| Dimensions:                      | Width: 50,5 cm Depth: 4,2 cm Height: 50,5 cm           |
| Filter frame                     |  |
| Material:                        | Aluminum, 1 mm   |
| Dimensions:                      | Width: 22,5 cm<br>Height: 22,5 cm<br>Diameter: Ø 18 cm |

## **ROADINGER Flightcase 4x LED THA-150F Theater Spot**

| Maximum load:            | 100 kg   |
|--------------------------|--|
| Aluminum profile frames: | 25 mm  |
| Case handle:             | 4 pc/pcs   |
| Stop hinge:              | 3 pc/pcs   |
| Lock:                    | Butterfly lock: 2 pc/pcs   |
| Transport aid:           | <ul><li>4 x castors with 2 locking brakes</li><li>4 x built-in stacking trays in the cover</li></ul> |
| Use of brands:           | Branded hardware   |
| Material:                | Birch multiplex, 7 mm  |
| Color:                   | Dark brown, laminated  |
| Accessory compartment:   | 9 cm x 79 cm x 23,5 cm   |
| Device compartment:      | 48 cm x 22,5 cm x 23,5 cm  |
| Inside dimensions:       | 105 cm x 79 cm x 23,5 cm   |
| Dimensions:              | Width: 112 cm  |

Depth: 50 cm Height: 84 cm

Weight: 28,90 kg