



Features:

EUROLITE PAR-30 Spot black

PAR-30 housing with E27 socket (with plug + cable)

- 4 clip-to-hold clamps with spring locks for comfortable opening of the color filter frame
- Strong clamps with extension springs for safe hold and for quick opening of the rear housing cover
- Blackened tube for precise light output
- Suitable for different spot angles
- Small lighting-systems can also be realized with a small budget
- Control via plug and play
- With mounting bracket
- For PAR 30
- For application areas such as: Clubs/dancing school; decoration; Trade fair and shop fitting; party room; restaurants, bars and hotels; advertisement/Shop window
- Silent operation

OMNILUX PAR-30 230V COB 12W E-27 LED 1800k-3000k dim2warm

PAR-30 LED lamp with modern dim-to-warm feature

- Dimming behavior comparable with incandescent and halogen lamps (dim-to-warm)
- Changes the light color from 3000 K (warm white) to 1800 K (extra warm white) when dimming
- Creates particularly cosy atmospheres
- Easy lamp replacement
- Energy-saving
- Dimmable
- Easy installation

Logistic

EAN / GTIN: 4026397366600

Weight: 7,00 kg

Length: 0.61 m

Width: 0.31 m

Height: 0.42 m

- Variable color temperature 1800 K - 3000 K
- Very high color rendering index (CRI)

EUROLITE EDX-4 DMX RDM LED Dimmer Pack

4-channel dimmer for LED lights with 230 V operation

- Trailing edge dimmer with 4 channels
- Max. channel load 200 watts
- Independent DMX addressing per channel possible
- Dimmer or switch operation
- 4 channel faders for control on the device
- Note: Only suitable for LED - not for conventional light bulbs
- 16 integrated show programs
- Control via RDM; stand-alone; sound to light via microphone; DMX; QuickDMX via USB (optional); W-DMX by wireless solution via USB (optional); CRMX by LumenRadio via USB (optional)
- With rigging points
- LCD display
- For application areas such as: Trade fair and shop fitting; theater; rental; video and photography; restaurants, bars and hotels
- Silent operation
- Application possibility: Wall mounting

Technical specifications:

| | |
|----------------------------------|---------|
| Weight: | 5.20 kg |
| Energy efficiency class (A - G): | F |

EUROLITE PAR-30 Spot black

| | |
|-----------------------|----------------------------------------------------|
| Power supply: | 230 V AC, 50 Hz |
| Power consumption: | Max. 100 W |
| IP classification: | IP20 |
| Protection class: | Protection class I |
| Suitable lamp: | Max. 230 V/100 W E27 |
| Power connection: | Fixed power supply cord with safety plug |
| Cable construction: | 3 x 0.75 mm ² H05SS-F |
| Cable length: | Approx. 0.4 m |
| Base: | E27 |
| Lamp type: | Selectable |
| Color generation: | Via color filter frame |
| Control: | Plug and play |
| Construction: | PAR-30 |
| Housing color: | Black matte |
| Attachment system: | Mounting bracket |
| Material: | Aluminum |
| Slot for spot length: | 12.8 cm x 12.8 cm |
| Dimensions: | Length: 23.5 cm Width: 14.5 cm Height: 21 cm |

| | |
|--------------------------|---------------------------------------------------------|
| Weight: | 0.53 kg |
| Noise classification: | Class 0 (no noise at all) |
| Diameter mounting holes: | 2 x Ø10mm |
| Material: | Aluminum, 3 mm |
| Color: | Black, matte |
| Shape: | Octagonal |
| Material: | Aluminum, 0.5 mm |
| Color: | Black, matte |
| Dimensions: | Length: 12.6 cm Width: 12.6 cm Diameter: Ø 9.4 cm |
| Weight: | 0.022 kg |

OMNILUX PAR-30 230V COB 12W E-27 LED 1800k-3000k dim2warm

| | |
|----------------------------------|--------------------------|
| Operating voltage: | 230 |
| Nominal wattage: | 12 W |
| Base: | E27 |
| Lamp type: | LED lamp; reflector lamp |
| Lamp specification: | Dimmable |
| Beam angle: | 24° |
| Setup: | Easy installation |
| Color of light: | White |
| Color temperature: | 1800K - 3000K adjustable |
| Color rendering index (CRI): | 96 Ra |
| Construction: | PAR-30 |
| Operating temperature max.: | 40° C |
| Operating temperature min.: | 20° C |
| Lamp life: | 15000 h |
| Luminous flux: | 960 lm |
| Wavelength: | 640 nm |
| Weight: | 0.14 kg |
| Photobiological safety: | Risk Group 1 |
| Energy efficiency class (A - G): | F |
| EPREL-Nr: | 963473 |

EUROLITE EDX-4 DMX RDM LED Dimmer Pack

| | |
|-------------------|-----------------------------------------------------------------------------------------------------------|
| Power supply: | 230 V AC, 50 Hz |
| Output power: | Max. 200 W Max. 800 W |
| Power connection: | Mains input via P-Con (blue), mounting version power supply cord with safety plug |
| Power output: | 4 x safety contact (F), hinged lid mounting version fused 1 x P-Con (gray), mounting version Bypass |

| | |
|--------------------------------|-------------------------------------------------------------------------------------------------------------------------------------------------------------------------|
| Device fuse: | 5 x 20 mm, F 6 A fuse replaceable |
| Power output fuse per channel: | 5 x 20 mm, T 1 A fuse replaceable |
| DMX channels: | 1; 4; 6 |
| DMX input: | 3-pin XLR (M) |
| DMX output: | 3-pin XLR (F) |
| Control: | RDM; stand-alone; sound to light via microphone; DMX; QuickDMX via USB (optional); W-DMX by wireless solution via USB (optional); CRMX by LumenRadio via USB (optional) |
| Control channels: | 4 |
| Flying points: | 2 x M10 thread |
| Display type: | LCD display |
| Status LED: | Channel level meter |
| Color: | Black |
| Dimensions: | Width: 21 cm Depth: 29 cm Height: 9 cm |
| Weight: | 2.53 kg |
| Noise classification: | Class 0 (no noise at all) |

Scope of delivery:

4 x EUROLITE PAR-30 Spot black

1 x spotlight
1 x filter frame
1 x user manual

1 x EUROLITE EDX-4 DMX RDM LED Dimmer Pack

1 x device
1 x user manual
1 x power cord