



List price: 422.45 €

incl. 19% VAT.

Features:

EUROLITE PAR-30 Spot black

PAR-30 housing with E27 socket (with plug + cable)

- 4 clip-to-hold clamps with spring locks for comfortable opening of the color filter frame
- Strong clamps with extension springs for safe hold and for quick opening of the rear housing cover
- Blackened tube for precise light output
- Suitable for different spot angles
- Small lighting-systems can also be realized with a small budget
- Control via plug and play
- With Mounting bracket
- For PAR 30
- For application areas such as: Advertisement/Shop window; Decoration; Clubs/dancing school

Package contents

- 1 x spotlight, 1 x mounting bracket, 1 x filter frame, 1 x user manual

Logistic

EAN / GTIN: 4026397366600

Weight: 7,00 kg

Length: 0.61 m

Width: 0.31 m

Height: 0.42 m

OMNILUX PAR-30 230V COB 12W E-27 LED 1800k-3000k dim2warm

PAR-30 LED lamp with modern dim-to-warm feature

- Dimming behavior comparable with incandescent and halogen lamps (dim-to-warm)
- Changes the light color from 3000 K (warm white) to 1800 K (extra warm white) when dimming
- Creates particularly cosy atmospheres
- Easy lamp replacement
- Energy-saving
- Dimmable
- Variable color temperature 1800 K - 3000 K

- Easy installation
- Very high color rendering index (CRI)

EUROLITE EDX-4 DMX RDM LED Dimmer Pack

4-channel dimmer for LED lights with 230 V operation

- Trailing edge dimmer with 4 channels
 - Max. channel load 200 watts
 - Independent DMX addressing per channel possible
 - Dimmer or switch operation
 - 4 channel faders for control on the device
 - Note: Only suitable for LED - not for conventional light bulbs
 - 16 integrated show programs
 - Control via RDM; stand-alone; Sound to light via Microphone; DMX; QuickDMX via USB (optional); W-DMX by wireless solution via USB (optional); CRMX by LumenRadio via USB (optional)
 - With rigging points
 - LCD display
 - For application areas such as: Trade fair and shop fitting; theater; Rental; video and photography; restaurants, bars and hotels
 - Silent operation
 - Application possibility: Wall mounting
- Package contents**
- 1 x device, 1 x user manual, 1 x power cord

Technical specifications:

Weight:	5,30 kg
Energy efficiency class (A - G):	F

EUROLITE PAR-30 Spot black

Power supply:	230 V AC, 50 Hz
Power consumption:	Max. 100 W
IP classification:	IP20
Protection class:	Protection class I
Suitable lamp:	Max. 230 V/100 W E27
Power connection:	Fixed power supply cord with safety plug
Cable construction:	3 x 0,75 mm ² H05SS-F
Cable length:	Approx. 0,4 m
Base:	E27
Lamp type:	Selectable
Color generation:	Via color filter frame
Control:	Plug and play
Construction:	PAR-30
Housing color:	Black
Attachment system:	Mounting bracket
Material:	Aluminum
Slot for spot length:	12,8 cm x 12,8 cm
Dimensions:	Length: 23,5 cm

Width: 14,5 cm
Height: 21 cm

Weight:	530 g
Mounting bracket	
Diameter mounting holes:	2 x Ø10mm
Material:	Aluminum, 3 mm
Color:	Black
Filter frame	
Shape:	Octagonal
Material:	Aluminum, 0,5 mm
Color:	Black
Dimensions:	Length: 12,6 cm Width: 12,6 cm Diameter: Ø 9,4 cm
Weight:	22 g

OMNILUX PAR-30 230V COB 12W E-27 LED 1800k-3000k dim2warm

Voltage (lamps):	230 V
Nominal wattage:	12 W
Base:	E27
Lamp type:	LED lamp
Lamp specification:	Dimmable
Beam angle:	24°
Color of light:	White
Color temperature:	1800K - 3000K adjustable
Setup:	Easy installation
Color rendering index (CRI):	96 Ra
Construction:	PAR-30
Operating temperature max.:	40° C
Operating temperature min.:	20° C
Lamp life:	15000 h
Luminous flux:	960 lm
Wavelength:	640 nm
Weight:	140 g
Photobiological safety:	Risk Group 1
Energy efficiency class (A - G):	F

EUROLITE EDX-4 DMX RDM LED Dimmer Pack

Power supply:	230 V AC, 50 Hz
Output power:	Max. 200 W per channel Max. 800 W
Power connection:	Mains input via P-Con (blue), mounting version power supply cord with safety plug

Power output:	4 x Safety contact (F), hinged lid mounting version 1 x P-Con (gray), mounting version Bypass
DMX channels:	1; 4; 6
DMX input:	3-pin XLR (M)
DMX output:	3-pin XLR (F)
Control:	RDM; stand-alone; Sound to light via Microphone; DMX; QuickDMX via USB (optional); W-DMX by wireless solution via USB (optional); CRMX by LumenRadio via USB (optional)
Control channels:	4
Flying points:	2 x M10 thread
Display type:	LCD display
Status LED:	Chanal level meter
Color:	Black
Dimensions:	Width: 21 cm Depth: 29 cm Height: 9 cm
Weight:	2,63 kg
Noise classification:	Class 0 (no noise at all)