

eurolite®

Set 4x PAR-30 Spot sw dim2warm + EDX-4 DMX RDM LED Dimmer pack

Art. No.: 20000696

GTIN: 4026397366600



List price: 422.45 €
incl. 19% VAT.

eurolite®

Set 4x PAR-30 Spot sw dim2warm + EDX-4 DMX RDM LED Dimmer pack

Art. No.: 20000696

GTIN: 4026397366600

Features:

EUROLITE PAR-30 Spot black

PAR-30 housing with E27 socket (with plug + cable)

- 4 clip-to-hold clamps with spring locks for comfortable opening of the color filter frame
- Strong clamps with extension springs for safe hold and for quick opening of the rear housing cover
- Blackened tube for precise light output
- Suitable for different spot angles
- Small lighting-systems can also be realized with a small budget
- Control via plug and play
- With Mounting bracket
- For PAR 30
- For application areas such as: Advertisement/Shop window; Decoration; Clubs/dancing school

Package contents

- 1 x spotlight, 1 x mounting bracket, 1 x filter frame, 1 x user manual

OMNILUX PAR-30 230V COB 12W E-27 LED 1800k-3000k dim2warm

- PAR-30 LED lamp with modern dim-to-warm feature
- Dimming behavior comparable with incandescent and halogen lamps (dim-to-warm)
 - Changes the light color from 3000 K (warm white) to 1800 K (extra warm white) when dimming
 - Creates particularly cosy atmospheres
 - Easy lamp replacement
 - Energy-saving
 - Dimmable
 - Variable color temperature 1800 K - 3000 K
 - Easy installation
 - Very high color rendering index (CRI)

EUROLITE EDX-4 DMX RDM LED Dimmer Pack

- 4-channel dimmer for LED lights with 230 V operation
- Trailing edge dimmer with 4 channels
 - Max. channel load 200 watts
 - Independent DMX addressing per channel possible
 - Dimmer or switch operation
 - 4 channel faders for control on the device
 - Note: Only suitable for LED - not for conventional light bulbs
 - 16 integrated show programs
 - Control via RDM; stand-alone; Sound to light via Microphone; DMX; QuickDMX via USB (optional); W-DMX by wireless solution via USB (optional); CRMX by LumenRadio via USB (optional)
 - With rigging points
 - LCD display
 - Silent operation