EUROLITE Set 2x TMH XB-280 + Case

Art. No.: 20000702

GTIN: 4026397492484

2x bright, narrow beam with OSD 10 280 W discharge lamp incl. PRO flightcase with castors

Features:

- Positioning within
- <p>EUROLITE TMH XB-280 Moving Head Beam
- <h2 class="featureSatz">Bright, narrow beam with OSD 10 280W discharge lamp, color wheel, gobos and prisms</h2>Equipped with an OSD 10 Reflector 280W discharge lamp
- Positioning within 540° PAN, 270° TILT
- Exact positioning (16 bit resolution)
- Color wheel; focus motor-driven; gobo wheel with static gobos; frost filter; prism 8-fold rotating; prism 24-fold rotating
- Dimmer electronic
- Strobe effect
- Color wheel with 14 dichroic filters plus open
half colors selectable, Rainbow effect with adjustable speed in both directions
- Gobo wheel with static gobos, 13 gobos und open
shake effect
- The device is cooled by cooling fan
- Control via DMX; stand-alone; master/slave function; sound to light via microphone; QuickDMX via USB (optional); W-DMX by wireless solution via USB (optional); CRMX by LumenRadio via USB (optional)
- Fixtures available for LED PC-Control 512; Light Captain
- With a beam angle of 2°
- Multicolor LCD display
- For application areas such as: Clubs/dancing school; stage; rental
- Application possibility: Standing; suspended
- <p>ROADINGER Flightcase 2x TMH-XB-280
- <h2 class="featureSatz">Trunk case with castors</h2>For optimal security
- With 2 device compartments
- With 1 accessory compartment

Logistic

EAN / GTIN: 4026397492484

Eurolite®, Futurelight®, PSSO®, Roadinger®, Alutruss®, Europalms® and Dimavery® are trademarks of Steinigke Showtechnic GmbH, Andreas-Bauer-Straße 5, DE-97297 Waldbüttelbrunn
All rights reserved. Subject to change without notice. Errors and omissions excepted.Illustration only. Actual item may differ from photo.

- High-quality workmanship with plywood multi-layer glued 7 mm, black, laminated
- Interior with foam padding
cover with foam padding
- Aluminum profile frames 30mm with rounded edges
- 2 hinged, chromium plated case handles
- 2 chrome tip-over locks
- 2 high-quality butterfly locks with shut-off function
- 4 x castors with 2 locking brakes
- For further information about this product, please refer to the Data Sheet under "Downloads"

Technical specifications:

Weight:	46.30 kg

EUROLITE TMH XB-280 Moving Head Beam

Power supply:	100-240 V AC, 50/60 Hz
Power consumption:	385 W
IP classification:	IP20
Power connection:	Mains input via P-Con (blue), mounting version power supply cord with safety plug (provided)
Fuse:	T 5 A fuse replaceable
Lamp type:	Discharge lamp
Max. TILT movement:	270° exact positioning (16 bit resolution)
Max. PAN movement:	540° exact positioning (16 bit resolution)
Flash rate:	1 - 18 Hz
Equipment:	Color wheel; focus motor-driven; gobo wheel with static gobos; frost filter; prism 8-fold rotating; prism 24-fold rotating
Color generation:	Color wheel with 14 dichroic filters plus open Half colors selectable, Rainbow effect with adjustable speed in both directions
Gobos:	Gobo wheel with static gobos, 13 gobos und open Shake effect
DMX channels:	16; 19
DMX input:	3-pin XLR (M) mounting version
DMX output:	3-pin XLR (F) mounting version
Cooling:	Cooling fan
Control:	DMX; stand-alone; master/slave function; sound to light via microphone; QuickDMX via USB (optional); W-DMX by wireless solution via USB (optional); CRMX by LumenRadio via USB (optional)
Fixtures available for:	LED PC-Control 512; Light Captain
Beam angle:	2°
Beam angle (1/2 peak):	2°
Housing color:	Black
Display type:	Multicolor LCD display
Dimensions:	Width: 30.0 cm

Eurolite®, Futurelight®, PSSO®, Roadinger®, Alutruss®, Europalms® and Dimavery® are trademarks of Steinigke Showtechnic GmbH, Andreas-Bauer-Straße 5, DE-97297 Waldbüttelbrunn
All rights reserved. Subject to change without notice. Errors and omissions excepted.Illustration only. Actual item may differ from photo.

	Depth: 20.5 cm Height: 50.5 cm
Weight:	14.80 kg
Noise classification:	Class 4 (loud noises)

ROADINGER Flightcase 2x TMH-XB-280

Maximum load:	50 kg
Aluminum profile frames:	30 mm
Case handle:	2 pc/pcs
Stop hinge:	2 pc/pcs
Lock:	Butterfly lock: 2 pc/pcs with shut-off function
Transport aid:	4 x castors with 2 locking brakes
Material:	Plywood multi-layer glued, 7 mm
Color:	Black, laminated
Device compartment:	22 cm x 32 cm x 50 cm
Accessory compartment:	7 cm x 32 cm x 22 cm
Inside dimensions:	53 cm x 32 cm x 50 cm
Dimensions:	Width: 58 cm Depth: 37 cm Height: 67 cm
Weight:	16.70 kg

Scope of delivery:

1 x moving light
1 x user manual
1 x power cord
2 x omega bracket

Eurolite®, Futurelight®, PSSO®, Roadinger®, Alutruss®, Europalms® and Dimavery® are trademarks of Steinigke Showtechnic GmbH, Andreas-Bauer-Straße 5, DE-97297 Waldbüttelbrunn
All rights reserved. Subject to change without notice. Errors and omissions excepted.Illustration only. Actual item may differ from photo.