

## EUROLITE Set LED KLS-3002 + STV-40S-WOT Steel stand

Bar with 4 powerful RGBAW/UV spots, QuickDMX, remote control and bag incl. steel stand

Art. No.: 20000719

GTIN: 4026397304305



**List price: 808.01 €**

incl. 19% VAT.

### Features:

#### EUROLITE LED KLS-3002 Next Compact Light Set

Bar with 4 powerful RGBAW/UV spots, QuickDMX support, IR remote control and carrying bag

- Crossbar with integrated DMX control unit and TV spigot for tripod installation
- 7 powerful LEDs 10 W high-power 6in1 HCL RGBWA/UV (homogenous color mix) spots controlled separately
- With a beam angle of 19°
- 20 integrated show programs
- Direct color selection for 21 preset colors
- Dimmer electronic; color blend stepless; color selection; program selection
- UV effect
- Control via stand-alone; DMX; IR remote control; Sound to light via Microphone; Wireless footswitch (optional); QuickDMX via USB (optional); W-DMX by wireless solution via USB (optional); CRMX by LumenRadio via USB (optional)
- Preprogrammed in EASY SHOW 1; Light J; LED PC-Control 512; LED EASY OPERATOR DELUXE; Light Captain; EASY SHOW 2; EASY SHOW 3
- For application areas such as: Mobile use; Stage; mobile djs / entertainer; Rental
- Mounting points and power outlets for additional fixtures
- Mains input and output for power linking up to 8 units
- Silent operation
- Application possibility: Suspended; on stand

#### Package contents

- 1 x device, 1 x user manual, 1 x declaration of conformity, 1 x power cord, 1 x remote control, 1 x bag, 2 x omega bracket, 4 x knurled screw, 4 x washer, 1 x battery, 1 x terminating plug (power)

### Logistic

EAN / GTIN: 4026397304305

Weight: 22,00 kg

Length: 1.35 m

Width: 0.21 m

Height: 0.58 m

Bulky product

## EUROLITE STV-40S-WOT Steel Stand

Steel lighting stand without crossbar, max. load 18 kg, max. height 340 cm

- Stable lighting stand for mobile use
- The telescopic tube is additionally fixed with a safety pin
- TV spigot
- Complies with DIN 15560-27 and DIN EN ISO 12100-2
- Adjustable height

### Package contents

- 1 x stand, 1 x user manual

## Technical specifications:

---

Weight: 19,34 kg

---

## EUROLITE LED KLS-3002 Next Compact Light Set

Power supply:	100-240 V AC, 50/60 Hz
Power consumption:	225 W
IP classification:	IP20
Power connection:	Mains input via P-Con (blue), mounting version power supply cord with safety plug (provided)
Cable length:	3 m
Power output:	2 x IEC connector (F) mounting version fused 1 x P-Con (gray), mounting version Bypass
Device fuse:	5 x 20 mm, T 2,5 A Fuse replaceable
Power output fuse per channel:	5 x 20 mm, T 5 A Fuse replaceable
Lamp type:	LED lamp
LED:	7 x 10 W high-power 6in1 HCL RGBWA/UV (homogenous color mix)
DMX channels:	2; 4; 6; 10; 24; 28
DMX input:	1 x 3-pin XLR (M) mounting version
DMX output:	1 x 3-pin XLR (F) mounting version
Cooling:	Passive convection cooling
Control:	Stand-alone; DMX; IR remote control; Sound to light via Microphone; Wireless footswitch (optional); QuickDMX via USB (optional); W-DMX by wireless solution via USB (optional); CRMX by LumenRadio via USB (optional)
Preprogrammed in:	EASY SHOW 1; Light J; LED PC-Control 512; LED EASY OPERATOR DELUXE; Light Captain; EASY SHOW 2; EASY SHOW 3
Beam angle:	19°
Beam angle (1/2 peak):	19°
Beam angle (1/10 peak):	35°
Housing color:	Black
Attachment system:	TV spigot Ø 28mm Omega bracket

Dimensions:	Width: 1,28 m Depth: 8 cm Height: 29 cm
Weight:	11,14 kg
Noise classification:	Class 0 (no noise at all)
Remote control	
Battery:	1 x Button cell 3.0 V CR2025 lithium manganese built-in
Legal specifications	
Special product:	Not designed for household room illumination
Intended use:	Show effect lighting

#### **EUROLITE STV-40S-WOT Steel Stand**

Maximum carrying capacity:	18 kg
Standard:	DIN 15560-27, DIN EN ISO 12100-2
Height:	Maximum: 340 cm above 2 sections Minimum: 150 cm
Attachment system:	TV spigot Ø 28mm
Type (general stands):	Light stand/manual
Color:	Black
Transport dimensions:	1,59 m x 18 cm x 15 cm
Base area:	Ø 1,2 m
Weight:	8,20 kg