

EUROLITE Set 4x AKKU Bar-6 QCL + Flightcase with charging function Art. No.: 200000722

4x Battery-powered LED bar with 4in1 LEDs and remote control incl. PRO flightcase with charging function function function from the control incl. PRO flightcase with charging function functin function function function function function function function







List price: 1783.81 €

incl. 19% VAT.

Features:

EUROLITE AKKU Bar-6 QCL

Battery-powered LED bar with 4in1 LEDs and IR remote control

- Additional frost filter provides a wide, soft and homogeneous light
- Cordless, flexible and versatile
- Integrated automatic charging of the battery and status indicator
- 6 powerful LEDs 8 W SMD 9080 4in1 QCL RGBW (homogenous color mix)
 LEDs controlled separately
- Color blend stepless; color change adjustable; color fade adjustable; Dimmer electronic;
 Dimmer speed (step response) adjustable
- Strobe effect
- Integrated show programs
- Direct color selection for 35 preset colors
- The device is cooled by passive convection cooling
- Control via stand-alone; DMX; master/slave function; sound to light via microphone; IR remote control; W-DMX by wireless solution via USB (optional); CRMX by LumenRadio via USB (optional); QuickDMX via USB (optional)
- Preprogrammed in LED PC-Control 512; EASY SHOW 1; LED EASY OPERATOR 4x4; LED EASY OPERATOR 4x6; LED EASY OPERATOR DELUXE; Light 'J; Light Captain; EASY SHOW 2; EASY SHOW 3; Colorchief
- Flicker-free
- With a beam angle of 8°
- With double bracket
- Mains input and output for power linking up to 8 units
- For application areas such as: Wedding/gala/events; mobile use; mobile djs / entertainer; small rental
- Silent operation

Logistic

EAN / GTIN: 4026397168273

- Application possibility: Standing; suspended; on stand
 - Package contents
- 1 x bar, 1 x user manual, 1 x power cord, 1 x frost filter, 1 x remote control, 1 x battery

ROADINGER Flightcase 4x AKKU BAR-6 QCL with charging function

Trunk case with castors

- With accessory compartment
- With 4 device compartments
- Interior with foam padding
- Aluminum profile frames 25mm with rounded edges
- 4 hinged, chromium plated case handles
- 2 chrome tip-over locks
- 2 high-quality butterfly locks with shut-off function
- 4 x castors with 2 locking brakes
- 4 x built-in stacking trays in the cover

Package contents

- 1 x case, 1 x user manual, 1 x power cord

Technical specifications:

Weight: 34,35 kg

EUROLITE AKKU Bar-6 QCL

Power supply:	100-240 V AC, 50/60 Hz
IP classification:	IP20
Protection class:	Protection class I
Power connection:	Battery/battery pack
	Mains input via P-Con (blue), mounting version power supply cord with safety plug (provided)
Power output:	1 x P-Con (gray), mounting version
Battery pack type:	1 x lithium ion 11,1 V, 10400 mAh, 115,44 Wh
Lamp type:	LED lamp
LED type:	6 x 8 W SMD 9080 4in1 QCL RGBW (homogenous color mix)
DMX channels:	4; 6; 8; 11; 12; 13; 17; 24; 29
DMX input:	1 x 3-pin XLR (M) mounting version
DMX output:	1 x 3-pin XLR (F) mounting version
Cooling:	Passive convection cooling
Control:	Stand-alone; DMX; master/slave function; sound to light via microphone; IR remote control; W-DMX by wireless solution via USB (optional); CRMX by LumenRadio via USB (optional); QuickDMX via USB (optional)
Preprogrammed in:	LED PC-Control 512; EASY SHOW 1; LED EASY OPERATOR 4x4; LED EASY OPERATOR 4x6; LED EASY OPERATOR DELUXE; Light J; Light Captain; EASY SHOW 2; EASY SHOW 3; Colorchief
Projection:	Flicker-free
Beam angle:	8°

Beam angle (1/2 peak):	8°
Beam angle (1/10 peak):	17°
Housing color:	Black
Attachment system:	Double bracket
Dimensions:	Length: 50,2 cm
	Depth: 6 cm
	Height: 20,1 cm
Weight:	3,80 kg
Noise classification:	Class 0 (no noise at all)
Remote control	
Battery:	1 x button cell 3.0 V CR2032 lithium manganese built-in
Legal specifications	
Special product:	Not designed for household room illumination
Intended use:	Show effect lighting

ROADINGER Flightcase 4x AKKU BAR-6 QCL with charging function

Power supply:	100-240 V AC, 50/60 Hz
Power consumption:	Max. 1150 W
Power connection:	Mains input via P-Con (blue), mounting version power supply cord with safety plug (provided)
Cable length:	1,20 m
Device fuse:	5 x 20 mm, F 5 A fuse replaceable
Aluminum profile frames:	25 mm
Case handle:	4 pc/pcs
Stop hinge:	2 pc/pcs
Lock:	Butterfly lock: 2 pc/pcs with shut-off function
Transport aid:	4 x castors with 2 locking brakes4 x built-in stacking trays in the cover
Material:	Birch multiplex
Color:	Black, laminated
Device compartment:	17 cm x 50,5 cm x 18 cm
Accessory compartment:	9 cm x 50,5 cm x 18 cm
Dimensions:	Width: 98 cm
	Depth: 56 cm
	Height: 35 cm
Weight:	19,15 kg