

FUTURELIGHT Set 2x EYE-7 HCL Zoom + Case

2x PRO washlight with 6in1 COB LEDs and motorized zoom including PRO flightcase

Art. No.: 2000723

GTIN: 4026397471861



The article is no longer in our assortment.

Features:

FUTURELIGHT EYE-7 HCL Zoom LED Moving Head Wash

PRO washlight with 6in1 COB LEDs and motorized zoom

- Equipped with 7 x 17 W 6in1 LED in R/G/B/Amber/Lime/Cyan
- Variable PWM frequency (pulse-width modulation)
- Optional W-DMX receiver for wireless DMX Control
- Compact design
- 2 different LED segments, which can be controlled individually via DMX
- Exact positioning via 16-bit PAN/TILT movement resolution
- 16-bit resolution for high-resolution dimming
- Motorized zoom with 2-36° beam angle
- Color presets
- Variable color temperature
- Built-in programs
- Stepless color blend
- Strobe effect with adjustable speed
- Random strobe effect
- Automatic position correction
- PAN angle switchable between 540° and 630°
- ESDC function (Easy Service Data Check) with battery-buffered control board for operation time readouts etc. (the Li-Ion battery 3.7V, AAA, 10440 is not included)
- Control panel with LC display for easy configuration
- Stand-alone, master/slave and DMX mode
- The scenes can be modified via the Control Board or via an external controller and loaded into the memory
- Number of scenes can be changed individually
- Software upload by optional accessories via DMX link

Logistic

EAN / GTIN: 4026397471861

Weight: 28,00 kg

Length: 1.20 m

Width: 0.60 m

Height: 0.60 m

Bulky product

- 7 powerful LEDs 17 W high-power 6in1 HCL RGBALC (homogenous color mix)
 - PAN angle switchable between 540° and 630°
 - Auto position correction (feedback)
 - Exact positioning (16 bit resolution)
 - Zoom motor-driven
 - Strobe effect
 - The device is cooled by temperature-controlled fan
 - Control via stand-alone; DMX; RDM; W-DMX by wireless solution upgradeable; Master/slave function; Sound to light via Microphone
 - Preprogrammed in LED PC-Control 512; Light Captain; Light J
 - Flicker-free
 - With a beam angle of 2° - 36°
 - Built with NEUTRIK connector
- Package contents**
- 1 x moving light, 1 x power cord, 1 x user manual, 1 x declaration of conformity, 1 x mounting bracket, 1 x xLR cable

ROADINGER Flightcase 2x EYE-7 RGBW Zoom

Trunk case, PRO version

- With 2 Device compartments
- With accessory compartment
- High-quality workmanship with birch multiplex 7 mm, dark brown, laminated
- Interior with foam padding
- Aluminum profile frames 30mm with rounded edges
- 2 hinged, chromium plated case handles
- 2 chrome tip-over locks
- 1 high-quality butterfly lock
- Made in Germany
- For further information about this product, please refer to the Data Sheet under "Downloads"

Technical specifications:

Weight: 25,20 kg

FUTURELIGHT EYE-7 HCL Zoom LED Moving Head Wash

Power supply:	100-240 V AC, 50/60 Hz
Power consumption:	130 W
IP classification:	IP20
Power connection:	Mains input via PowerCON (blue), mounting version power supply cord with safety plug
Power output:	1 x PowerCON (gray), mounting version
Fuse:	5 x 20 mm, T 3,15 A Fuse replaceable
Lamp type:	LED lamp
LED:	7 x 17 W high-power 6in1 HCL RGBALC (homogenous color mix)
Max. TILT movement:	270° Exact positioning (16 bit resolution) Auto position correction (feedback)
Max. PAN movement:	540°, 630° Exact positioning (16 bit resolution) Auto position correction (feedback)
Flash rate:	1 - 18 Hz
Equipment:	Zoom motor-driven

DMX channels:	16; 19; 20; 33
DMX input:	1 x 3-pin XLR (M) mounting version
DMX output:	1 x 3-pin XLR (F) mounting version
Cooling:	Temperature-controlled fan
Control:	Stand-alone; DMX; RDM; W-DMX by wireless solution upgradeable; Master/slave function; Sound to light via Microphone
Preprogrammed in:	LED PC-Control 512; Light Captain; Light J
Projection:	Flicker-free
Beam angle:	2° - 36°
Beam angle (1/2 peak):	2 - 15°
Beam angle (1/10 peak):	7 - 36°
Illuminance in Lux (lx):	Narrow red (R) 1m: 7036 lx, 3m: 1003 lx, 6m: 248 lx Narrow green (G) 1m: 14473 lx, 3m: 2193 lx, 6m: 548 lx Narrow blue (B) 1m: 2461 lx, 3m: 478 lx, 6m: 122 lx Narrow amber (A) 1m: 27460 lx, 3m: 4256 lx, 6m: 1066 lx Narrow Lime 1m: 44659 lx, 3m: 6773 lx, 6m: 1705 lx Narrow cyan 1m: 6274 lx, 3m: 1011 lx, 6m: 251 lx Narrow all 3m: 14976 lx, 6m: 3744 lx Wide red (R) 1m: 787 lx, 3m: 95 lx, 6m: 25 lx Wide green (G) 1m: 1716 lx, 3m: 215 lx, 6m: 58 lx Wide blue (B) 1m: 392 lx, 3m: 51 lx, 6m: 14 lx Wide amber (A) 1m: 3202 lx, 3m: 388 lx, 6m: 104 lx Wide Lime 1m: 4793 lx, 3m: 594 lx, 6m: 160 lx Wide cyan 1m: 839 lx, 3m: 103 lx, 6m: 28 lx Wide all 1m: 11196 lx, 3m: 1365 lx, 6m: 362 lx
Housing color:	Black
Use of brands:	Built with NEUTRIK connector
Dimensions:	Width: 24,9 cm Depth: 17,9 cm Height: 34,7 cm
Weight:	7,30 kg
Noise classification:	Class 3 (clearly perceptible sounds)
Legal specifications	
Special product:	Not designed for household room illumination
Intended use:	Show effect lighting

ROADINGER Flightcase 2x EYE-7 RGBW Zoom

Maximum load:	50 kg
Aluminum profile frames:	30 mm
Case handle:	2 pc/pcs
Stop hinge:	2 pc/pcs
Lock:	Butterfly lock: 1 pc/pcs

Material:	Birch multiplex, 7 mm
Color:	Dark brown, laminated
Accessory compartment:	45,5 cm x
Device compartment:	18 cm x 25 cm x 22 cm
Inside dimensions:	45,5 cm x
Dimensions:	Width: 49,5 cm Depth: 44 cm Height: 47 cm
Weight:	10,60 kg