

EUROLITE Set LED KLS-180 white + BS-2 EU Loudspeaker Stand white

Art. No.: 20000726

White bar with 4 RGBW spots and 4 white strobe LEDs with QuickDMX connector incl. speaker stand

GTIN: 4026397455564



List price: 391.51 €

incl. 19% VAT.

Features:

EUROLITE LED KLS-180 Compact Light Set wh

Bar with 4 RGBW spots and 4 white strobe LEDs, with QuickDMX connector (XLR)

- Crossbar with integrated DMX control unit and stand sleeve
- Compact lightweight
- Movable and tiltable spotlights
- Dimmer electronic; color blend stepless; color change adjustable; colors preset
- Strobe effect
- The device is cooled by passive convection cooling
- Control via IR remote control; stand-alone; DMX; sound to light via microphone; master/slave function; QuickDMX via USB (optional); W-DMX by wireless solution via USB (optional); CRMX by LumenRadio via USB (optional)
- Preprogrammed in EASY SHOW 1; LED PC-Control 512; Light Captain; EASY SHOW 2; EASY SHOW 3; Light'J; Colorchief
- Flicker-free
- With a beam angle of 9°
- With mounting bracket
- Mains input and output for power linking up to 8 units
- For application areas such as: Party room; mobile use; mobile djs / entertainer; small rental
- Silent operation
- Application possibility: Suspended; on stand

spotlight

- 4 powerful LEDs 8 W SMD 9080 4in1 QCL RGBW (homogenous color mix)
4 spots controlled separately

bar

- 4 powerful LEDs 1 W SMD 8072 cold white (CW)
LEDs controlled separately

Package contents

Logistic

EAN / GTIN: 4026397455564

Weight: 10,75 kg

Length: 1.20 m

Width: 0.60 m

Height: 0.20 m

Bulky product

- 1 x device, 1 x bag, 1 x remote control, 1 x battery, 1 x power cord, 1 x user manual

OMNITRONIC BS-2 EU Loudspeaker Stand white

High steel speaker stand, height adjustable 117-205 cm, maximum load 50 kg

- Height adjustable, with locking pin
- Tube diameter: Ø 35 mm
- Adjustable height
- Scratchproof and shockproof
- Made in Europe

Technical specifications:

Weight:	9,60 kg
---------	---------

EUROLITE LED KLS-180 Compact Light Set wh

Power supply:	100-240 V AC, 50/60 Hz
Power consumption:	80 W
IP classification:	IP20
Power connection:	Mains input via IEC connector (M) mounting version power supply cord with safety plug (provided)
Power output:	IEC connector (F) mounting version
Fuse:	T 1 A
Lamp type:	LED lamp
DMX channels:	3; 4; 8; 21
DMX input:	1 x 3-pin XLR (M) mounting version
DMX output:	1 x 3-pin XLR (F) mounting version
Cooling:	Passive convection cooling
Control:	IR remote control; stand-alone; DMX; sound to light via microphone; master/slave function; QuickDMX via USB (optional); W-DMX by wireless solution via USB (optional); CRMX by LumenRadio via USB (optional)
Preprogrammed in:	EASY SHOW 1; LED PC-Control 512; Light Captain; EASY SHOW 2; EASY SHOW 3; Light J; Colorchief
Projection:	Flicker-free
Beam angle:	9°
Beam angle (1/2 peak):	9°
Housing color:	White
Attachment system:	Mounting bracket
Dimensions:	Width: 60,5 cm Depth: 14 cm Height: 23 cm
Weight:	5,10 kg
Noise classification:	Class 0 (no noise at all)

Photobiological safety:	Risk Group 0
Remote control	
Battery:	1 x button cell 3.0 V CR2025 lithium manganese built-in
Spotlight	
LED type:	4 x 8 W SMD 9080 4in1 QCL RGBW (homogenous color mix)
Bar	
LED type:	4 x 1 W SMD 8072 cold white (CW)
Flash rate:	1 - 20 Hz
Legal specifications	
Special product:	Not designed for household room illumination
Intended use:	Show effect lighting

OMNITRONIC BS-2 EU Loudspeaker Stand white

Maximum carrying capacity:	50 kg
Height:	Maximum: 205 cm Minimum: 117 cm
Attachment system:	Ø 35mm
Type (general stands):	Speaker stand/manual
Material:	Steel
Color:	White, painted; , scratchproof and shockproof
Transport dimensions:	110 cm x 17 cm x 14 cm
Weight:	4,50 kg