

## OMNITRONIC Set MOLLY-12A Subwoofer active + 2x MOLLY-6 Top 8 Ohm, black 20000727

Active 12" subwoofer with DSP and Bluetooth inkl. 2x 6.5" satellite speakers

GTIN: 4026397680485



**List price: 831.81 €**

incl. 19% VAT.

### Features:

#### OMNITRONIC MOLLY-12A Subwoofer active black

Active 12" subwoofer with DSP and Bluetooth

- 12" bassreflex subwoofer with DSP and 700 watts RMS power
- Flexibly extendable with MOLLY-6 satellites for 2.1 and 4.1 configurations
- DSP-controlled class D amplifier (500 W + 2 x 100 W)
- Separate volume control for subwoofer and satellites
- Stereo/mono selection
- Digital signal processor
- The device is cooled by temperature-controlled fan
- Control via Bluetooth
- For application areas such as: Mobile djs / entertainer; Trade fair and shop fitting; Installation; home entertainment; restaurants, bars and hotels; product presentations and lectures
- 2 Rugged carrying handles
- Black metal grille with acoustic foam
- DSP presets: FLAT; DJ; LIVE; VOICE

#### Package contents

- 1 x user manual, 1 x power cord, 1 x declaration of conformity, 1 x bass, 2 x speaker cable

### Logistic

EAN / GTIN: 4026397680485

Weight: 34,00 kg

Length: 1.20 m

Width: 0.80 m

Height: 0.50 m

Bulky product

#### OMNITRONIC MOLLY-6 Top black 2x

6.5" satellite speakers with bracket

- 8-ohm speaker pair with 6.5" woofer and 1" tweeter
- For use with MOLLY-12A subwoofers for 2.1 and 4.1 configurations
- Optional stand adaptor required for stand mounting
- Extension U-bracket and cable available for connecting 2 satellite speakers

- With Mounting bracket
- With rigging points
- Black metal grille with acoustic foam
- 2 pieces per set
- For application areas such as: Mobile djs / entertainer; Trade fair and shop fitting; Installation; home entertainment; restaurants, bars and hotels; product presentations and lectures

#### Package contents

- 2 x top, 2 x mounting bracket, 4 x knurled screw, 2 x screw plug-in terminal

## Technical specifications:

|         |          |
|---------|----------|
| Weight: | 31,00 kg |
|---------|----------|

### OMNITRONIC MOLLY-12A Subwoofer active black

|                        |                                                                                                                                                                                                                                                                                 |
|------------------------|---------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------|
| Power supply:          | 230 V AC, 50 Hz                                                                                                                                                                                                                                                                 |
| Power consumption:     | 1000 W                                                                                                                                                                                                                                                                          |
| Protection class:      | Protection class I                                                                                                                                                                                                                                                              |
| Output power:          | 1 x 500 W RMS<br>2 x 100 W RMS (8 ohms)<br>2 x 200 W RMS (4 ohms)                                                                                                                                                                                                               |
| Power connection:      | Mains input via IEC connector (M) mounting version power supply cord with safety plug (provided)                                                                                                                                                                                |
| Frequency range:       | 40 - 160 Hz                                                                                                                                                                                                                                                                     |
| Sensitivity:           | 103 dB                                                                                                                                                                                                                                                                          |
| Max. SPL:              | 128 dB                                                                                                                                                                                                                                                                          |
| DSP:                   | Digital signal processor                                                                                                                                                                                                                                                        |
| DSP presets:           | FLAT; DJ; LIVE; VOICE                                                                                                                                                                                                                                                           |
| Cooling:               | Temperature-controlled fan                                                                                                                                                                                                                                                      |
| Control:               | Bluetooth                                                                                                                                                                                                                                                                       |
| Bluetooth device name: | Omnitronic                                                                                                                                                                                                                                                                      |
| Attachment system:     | Flange: M20 thread                                                                                                                                                                                                                                                              |
| Circuitry:             | Class D                                                                                                                                                                                                                                                                         |
| Control elements:      | Phase reversal switch, level control per channel, power switch, connect                                                                                                                                                                                                         |
| Controls:              | Softstart; short-circuit; limiter; Overvoltage; overheat                                                                                                                                                                                                                        |
| Status LED:            | Signal, power, limit, fault, DSP presets                                                                                                                                                                                                                                        |
| Connections:           | Input: line via 2 x 3-pin XLR/6.35mm jack (F) combination socket (mounting version)<br><br>Input: line via 1 x 3.5 mm jack (stereo) mounting version<br><br>Input: line via 1 x stereo RCA<br>Output: line via 2 x 3-pin XLR<br>Output: Top via 2 x speaker built-in socket (F) |
| Input channels:        | 1 x stereo via Combination socket or RCA or Bluetooth, channel control via Rotary dial                                                                                                                                                                                          |
| Speaker:               | 1 x woofer 12"                                                                                                                                                                                                                                                                  |

|                       |                                               |
|-----------------------|-----------------------------------------------|
|                       | Voice coil lows 3"                            |
| Type of speaker:      | Subwoofer                                     |
| Type of construction: | Vented                                        |
| Carrying handle:      | 2 pc/pcs                                      |
| Material:             | Birch multiplex                               |
| Color:                | Black, textured coating, painted              |
| Dimensions:           | Width: 47 cm<br>Depth: 57 cm<br>Height: 40 cm |
| Weight:               | 22,10 kg                                      |

#### OMNITRONIC MOLLY-6 Top black 2x

|                    |                                                                                   |
|--------------------|-----------------------------------------------------------------------------------|
| Power:             | Program: 260W<br>Rated: 130W RMS                                                  |
| Frequency range:   | 150 - 20000 Hz                                                                    |
| Sensitivity:       | 95 dB (1W/1m)                                                                     |
| Max. SPL:          | 119 dB                                                                            |
| Impedance:         | 8 ohms                                                                            |
| Attachment system: | 2x Mounting bracket                                                               |
| Flying points:     | 2 x M8 thread                                                                     |
| Connections:       | 1 x speaker built-in socket (F)<br>1 x screw plug-in terminal                     |
| Speaker:           | 1 x woofer 6,5"<br>Basket material: Steel<br>Voice coil lows 1"<br>1 x Tweeter 1" |
| Type of speaker:   | On-ceiling/on-wall speaker; Coaxial speaker                                       |
| Material:          | MDF (Medium-density fiberboard)                                                   |
| Color:             | Black, textured coating, painted                                                  |
| Dimensions:        | Width: 18,3 cm<br>Depth: 21,4 cm<br>Height: 23 cm                                 |
| Weight:            | 8,90 kg                                                                           |