

EUROLITE Set LED KLS-902 + STV-60-WOT EU Steel Stand black

Bar with 4 powerful RGB/WW spots, QuickDMX, remote control and bag incl. lighting stand

Art. No.: 2000734

GTIN: 4026397681239



Features:

- Crossbar with integrated DMX control unit and TV spigot for tripod installation
- Mounting points and power outlets for additional fixtures
- 5 LEDs 7 W SMD 9080 4in1 QCL RGB/WW (homogenous color mix) spots controlled separately
- Color blend stepless; Dimmer electronic; program selection
- 20 integrated show programs
- The device is cooled by passive convection cooling
- Control via DMX; stand-alone; sound to light via microphone; IR remote control; wireless footswitch (optional); QuickDMX via USB (optional); W-DMX by wireless solution via USB (optional); CRMX by LumenRadio via USB (optional)
- Fixtures available for EASY SHOW 1; LED EASY OPERATOR DELUXE; Light Captain; EASY SHOW 2; Light J; EASY SHOW 3; Colorchief
- With a beam angle of 16°
- TV spigot
- With omega bracket
- Mains input and output for power linking up to 8 units
- For application areas such as: Mobile use; stage; mobile djs / entertainer; small rental; rental
- Very quiet working noise
- Application possibility: Suspended; on stand
- <p>EUROLITE STV-60-WOT EU Steel Stand black
- <h2 class="featureSatz">Lighting stand, made in EU, maximum load 30 kg, height 150-315 cm</h2>Stable lighting stand for mobile use
- Adjustable height
- TV spigot
- Available in various colors
- Made in Europe

Logistic

EAN / GTIN: 4026397681239

Weight: 17,00 kg

Length: 1.35 m

Width: 0.21 m

Height: 0.58 m

Bulky product

Technical specifications:

Weight: 15.45 kg

EUROLITE LED KLS-902 Next Compact Light Set

Power supply:	100-240 V AC, 50/60 Hz
Power consumption:	125 W
IP classification:	IP20
Power connection:	Mains input via P-Con (blue), mounting version power supply cord with safety plug (provided)
Cable length:	3 m
Power output:	2 x IEC connector (F) mounting version 1 x P-Con (gray), mounting version
Device fuse:	5 x 20 mm, T 2 A fuse replaceable
Power output fuse per channel:	5 x 20 mm, T 5 A fuse replaceable
Battery:	1 x button cell 3.0 V CR2025 lithium manganese built-in
Lamp type:	LED lamp
LED type:	5 x 7 W SMD 9080 4in1 QCL RGB/WW (homogenous color mix)
DMX channels:	3; 4; 6; 8; 16; 20; 18
DMX input:	3-pin XLR (M) mounting version
DMX output:	3-pin XLR (F) mounting version
Cooling:	Passive convection cooling
Control:	DMX; stand-alone; sound to light via microphone; IR remote control; wireless footswitch (optional); QuickDMX via USB (optional); W-DMX by wireless solution via USB (optional); CRMX by LumenRadio via USB (optional)
Fixtures available for:	EASY SHOW 1; LED EASY OPERATOR DELUXE; Light Captain; EASY SHOW 2; Light J; EASY SHOW 3; Colorchief
Beam angle (1/2 peak):	16°
Beam angle (1/10 peak):	32°
Housing color:	Black
Attachment system:	TV spigot Ø 28mm Omega bracket
Dimensions:	Width: 108 cm Depth: 6 cm Height: 28 cm
Weight:	9.80 kg
Noise classification:	Class 1 (very slight noise, suitable for noise- sensitive environments)
Special product:	Not designed for household room illumination
Intended use:	Show effect lighting

EUROLITE STV-60-WOT EU Steel Stand black

Maximum carrying capacity:	30 kg
Height:	Maximum: 320 cm Minimum: 150 cm
Attachment system:	TV spigot Ø 28mm
Type (general stands):	Light stand/manual
Material:	Steel/magnesium
Color:	Black
Transport dimensions:	126 cm x 12 cm x 15 cm
Weight:	5.65 kg

Scope of delivery:**1 x EUROLITE LED KLS-902 Next Compact Light Set**

- 1 x light effect
- 1 x user manual
- 1 x power cord
- 1 x remote control
- 1 x battery
- 2 x omega bracket
- 1 x declaration of conformity
- 4 x knurled screw
- 1 x bag

1 x EUROLITE STV-60-WOT EU Steel Stand black

- 1 x stand
- 1 x user manual