

## EUROLITE Set 2x LED TMH-S200 + Case

2x LED moving head spot including PRO flightcase

Art. No.: 20000737

GTIN: 4026397681512



### Features:

- Positioning within
- <p>EUROLITE LED TMH-S200 Moving Head Spot
- <h2 class="featureSatz">LED moving head spot with color wheel, static & rot. gobo wheel, prism, frost, focus and zoom</h2>1 LED 200 W COB (chip-on-board) cold white (CW)
- Positioning within 540° PAN, 270° TILT
- Auto position correction (feedback)
- Exact positioning (16 bit resolution)
- Prism 3-fold rotating; frost filter; gobo wheel with rotating gobos; gobo wheel with static gobos; zoom motor driven; focus motor-driven; color wheel
- Dimmer electronic; Dimmer speed (step response) adjustable
- Color wheel with 9 dichroic filters plus open<BR>half colors selectable, Rainbow effect with adjustable speed in both directions
- Gobo wheel with static gobos, 9 gobos and open<BR>shake effect
- Gobo wheel with rotating gobos, 7 gobos and open<BR>shake effect
- Slot-in gobo system for easy gobo replacement
- Gobos changeable
- Integrated show programs
- The device is cooled by cooling fan
- Control via stand-alone; DMX; master/slave function; sound to light via microphone; QuickDMX via USB (optional); W-DMX by wireless solution via USB (optional); CRMX by LumenRadio via USB (optional)
- Flicker-free
- Multicolor LCD display
- Mains input and output for power linking up to 8 units
- For application areas such as: Clubs/dancing school; wedding/gala/events; stage; rental
- Application possibility: Standing; suspended

### Logistic

EAN / GTIN: 4026397681512

Weight: 60,00 kg

Length: 1.20 m

Width: 0.80 m

Height: 0.72 m

Bulky product

- <p>ROADINGER Flightcase 2x TMH-S200 with wheels
- <h2 class="featureSatz">Trunk case with castors</h2>For optimal security
- With 2 device compartments
- High-quality workmanship with plywood multi-layer glued 7 mm, black, laminated
- Interior with foam padding<BR>cover with foam padding
- Aluminum profile frames 30mm with rounded edges
- 2 hinged, chromium plated case handles
- 2 chrome tip-over locks
- 2 high-quality butterfly locks
- 4 x castors with 2 locking brakes

## Technical specifications:

---

Weight: 48.10 kg

---

### EUROLITE LED TMH-S200 Moving Head Spot

Power supply:	100-240 V AC, 50/60 Hz
Power consumption:	250 W
Power connection:	Mains input via P-Con (blue), mounting version power supply cord with safety plug (provided)
Power output:	P-Con (gray), mounting version
Device fuse:	5 x 20 mm, T 3.15 A fuse replaceable
Lamp type:	LED lamp
LED type:	1 x 200 W COB (chip-on-board) cold white (CW)
Max. TILT movement:	270° exact positioning (16 bit resolution) auto position correction (feedback)
Max. PAN movement:	540° exact positioning (16 bit resolution) auto position correction (feedback)
Flash rate:	1 - 18 Hz
Equipment:	Prism 3-fold rotating; frost filter; gobo wheel with rotating gobos; gobo wheel with static gobos; zoom motor driven; focus motor-driven; color wheel
Color generation:	Color wheel with 9 dichroic filters plus open Half colors selectable, Rainbow effect with adjustable speed in both directions
Gobos:	Gobo wheel with static gobos, 9 gobos and open Shake effect Gobo wheel with rotating gobos, 7 gobos and open Outside diameter 19.5mm Image diameter 15mm Shake effect Slot-in gobo system for easy gobo replacement Gobos changeable
DMX channels:	17
DMX input:	3-pin XLR (M) mounting version
DMX output:	3-pin XLR (F) mounting version
Cooling:	Cooling fan

Control:	Stand-alone; DMX; master/slave function; sound to light via microphone; QuickDMX via USB (optional); W-DMX by wireless solution via USB (optional); CRMX by LumenRadio via USB (optional)
Fixtures available for:	Light Captain
Projection:	Flicker-free
Beam angle (1/2 peak):	8 - 22°
Beam angle (1/10 peak):	8 - 22°
Illuminance in Lux (lx):	Narrow cold white (CW) 3m: 22622 lx, 6m: 6278 lx Wide cold white (CW) 1m: 31619 lx, 3m: 4309 lx, 6m: 1112 lx
Housing color:	Black
Display type:	Multicolor LCD display
Dimensions:	Width: 30.5 cm Depth: 33.0 cm Height: 51.5 cm
Weight:	14.70 kg
Noise classification:	Class 3 (clearly perceptible sounds)
Special product:	Not designed for household room illumination
Intended use:	Show effect lighting

#### **ROADINGER Flightcase 2x TMH-S200 with wheels**

Maximum load:	50 kg
Aluminum profile frames:	30 mm
Case handle:	2 pc/pcs
Stop hinge:	2 pc/pcs
Lock:	Butterfly lock: 2 pc/pcs
Transport aid:	4 x castors with 2 locking brakes
Material:	Plywood multi-layer glued, 7 mm
Color:	Black, laminated
Device compartment:	25.5 cm x 32 cm x 50 cm
Inside dimensions:	63 cm x 32 cm x 50 cm
Accessory compartment:	6.5 cm x 32 cm x 19 cm
Dimensions:	Width: 67.5 cm Depth: 37 cm Height: 70.5 cm
Weight:	18.70 kg

#### **Scope of delivery:**

1 x moving light  
1 x user manual  
1 x power cord  
2 x omega bracket