

EUROLITE Set 4x LED TMH-S90 + Case

4x Led moving head spot including flightcase with wheels

Art. No.: 2000742

GTIN: 4026397681796



Features:

- Positioning within
- <p>EUROLITE LED TMH-S90 Moving Head Spot
- <h2 class="featureSatz">LED moving head spot with color wheel, static and rotating gobo wheel, prism and focus</h2>Rotating 3-facet prism with variable speed
- 1 LED 90 W COB (chip-on-board) cold white (CW)
- Positioning within 540° PAN, 200° TILT
- Auto position correction (feedback)
- Exact positioning (16 bit resolution)
- Prism 3-fold; gobo wheel with rotating gobos; gobo wheel with static gobos; focus motor-driven; color wheel
- Dimmer electronic
- Color wheel with 7 dichroic filters plus open
half colors selectable, Rainbow effect with adjustable speed in both directions
- Gobo wheel with static gobos, 7 gobos and open
shake effect
- Gobo wheel with rotating gobos, 5 gobos, 1 multi color gobo and open
shake effect
- Gobos changeable
- Slot-in gobo system for easy gobo replacement
- Integrated show programs
- The device is cooled by cooling fan
- Control via DMX; sound to light via microphone; stand-alone; master/slave function; QuickDMX via USB (optional); CRMX by LumenRadio via USB (optional); W-DMX by wireless solution via USB (optional)
- Fixtures available for EASY SHOW 1; Light Captain; EASY SHOW 3
- Flicker-free
- With a beam angle of 12°

Logistic

EAN / GTIN: 4026397681796

Weight: 50,00 kg

Length: 1.20 m

Width: 0.80 m

Height: 0.37 m

Bulky product

- For application areas such as: Clubs/dancing school; wedding/gala/events; stage; mobile djs / entertainer; restaurants, bars and hotels
- Application possibility: Standing; suspended
- <p>ROADINGER Flightcase 4x TMH-S90/H90/B90
- <h2 class="featureSatz">Trunk case with castors</h2>For optimal security
- With 4 device compartments
- High-quality workmanship with plywood multi-layer glued 7 mm, black, laminated
- Interior with foam padding
cover with foam padding
- Interior with foam padding
cover with foam padding
- Aluminum profile frames 30mm with rounded edges
- 4 hinged, chromium plated case handles
- 2 chrome tip-over locks
- 2 high-quality butterfly locks
- Castors

Technical specifications:

Weight: 43.80 kg

EUROLITE LED TMH-S90 Moving Head Spot

| | |
|---------------------|--|
| Power supply: | 100-240 V AC, 50/60 Hz |
| Power consumption: | 140 W |
| IP classification: | IP20 |
| Protection class: | Protection class I |
| Power connection: | Mains input via P-Con (blue), mounting version power supply cord with safety plug |
| Power output: | P-Con (gray), mounting version |
| Fuse: | 5 x 20 mm, T 2 A |
| Lamp type: | LED lamp |
| LED type: | 1 x 90 W COB (chip-on-board) cold white (CW) |
| Max. TILT movement: | 200° exact positioning (16 bit resolution) auto position correction (feedback) |
| Max. PAN movement: | 540° exact positioning (16 bit resolution) auto position correction (feedback) |
| Flash rate: | 1.5 - 15 Hz |
| Equipment: | Prism 3-fold; gobo wheel with rotating gobos; gobo wheel with static gobos; focus motor-driven; color wheel |
| Color generation: | Color wheel with 7 dichroic filters plus open Half colors selectable, Rainbow effect with adjustable speed in both directions |
| Gobos: | Gobo wheel with static gobos, 7 gobos and open Shake effect Gobo wheel with rotating gobos, 5 gobos, 1 multi color gobo and open Outside diameter 21.8mm Image diameter 16mm Shake effect Gobos changeable Slot-in gobo system for easy gobo replacement |

| | |
|--------------------------|---|
| DMX channels: | 15 |
| DMX input: | 3-pin XLR (M) mounting version |
| DMX output: | 3-pin XLR (F) mounting version |
| Cooling: | Cooling fan |
| Control: | DMX; sound to light via microphone; stand-alone; master/slave function; QuickDMX via USB (optional); CRMX by LumenRadio via USB (optional); W-DMX by wireless solution via USB (optional) |
| Fixtures available for: | EASY SHOW 1; Light Captain; EASY SHOW 3 |
| Projection: | Flicker-free |
| PWM frequency: | 15600 Hz |
| Beam angle: | 12° |
| Beam angle (1/2 peak): | 12° |
| Illuminance in Lux (lx): | Cold white (CW) 1m: 52772 lx, 3m: 6198 lx, 6m: 1543 lx |
| Housing color: | Black |
| Dimensions: | Width: 25.0 cm Depth: 20.5 cm Height: 35.0 cm |
| Weight: | 6.20 kg |
| Noise classification: | Class 3 (clearly perceptible sounds) |
| Photobiological safety: | Risk Group 0 |
| Special product: | Not designed for household room illumination |
| Intended use: | Show effect lighting |

ROADINGER Flightcase 4x TMH-S90/H90/B90

| | |
|--------------------------|---|
| Maximum load: | 100 kg |
| Aluminum profile frames: | 30 mm |
| Case handle: | 4 pc/pcs |
| Stop hinge: | 2 pc/pcs |
| Lock: | Butterfly lock: 2 pc/pcs |
| Transport aid: | Castors |
| Material: | Plywood multi-layer glued, 7 mm |
| Color: | Black, laminated |
| Device compartment: | 26 cm x 20 cm x 37 cm |
| Accessory compartment: | 26 cm x 9 cm x 37 cm |
| Dimensions: | Width: 58 cm Depth: 57 cm Height: 54 cm |
| Weight: | 19.00 kg |

Scope of delivery:

- 1 x moving light
- 1 x user manual
- 1 x power cord
- 1 x omega bracket
- 1 x safety eyelet