

## OMNITRONIC PAS MK3 Party Set

Subwoofer, 2x 2-Way Top, 2x Speaker Stand, Amplifier, PRO flightcase and 3x speaker cable

Art. No.: 2000744

GTIN: 4026397682366



**List price: 2557.31 €**

incl. 19% VAT.

### Features:

#### OMNITRONIC PAS-151 MK3 Subwoofer

15" bassreflex subwoofer with 3700 W RMS

- Rugged Pro PA subwoofer
- Wheels optional
- Black metal grille with acoustic foam
- 2 mould carrying handles
- Application possibility: Standing
- For application areas such as: Clubs/dancing school; Installation; mobile use; mobile djs / entertainer; restaurants, bars and hotels; Rental

#### Package contents

- 1 x user manual, 1 x bass

#### OMNITRONIC PAS-210 MK3 2-Way Top

Passive speaker with 10" woofer, 1" driver and 250 W RMS

- 2-way bass-reflex system with 25 cm woofer (8 cm voice coil)
- 2.5 cm compression driver with ferrite magnet (3.8 cm voice coil with polymer diaphragm)
- Optimized for combination with PAS subwoofers
- With rigging points
- Application possibility: Standing; suspended; monitoring; on stand
- Black metal grille with acoustic foam
- 2 mould carrying handles
- Dual flange
- For application areas such as: Clubs/dancing school; Installation; mobile use; mobile djs / entertainer; restaurants, bars and hotels; Rental

### Logistic

EAN / GTIN: 4026397682366

Weight: 100,00 kg

Length: 1.20 m

Width: 0.80 m

Height: 1.50 m

Bulky product

**Package contents**

- 1 x user manual, 1 x compact cabinet speaker

**OMNITRONIC Speaker Stand MOVE MK2 set**

2 speaker stands, extendible up to 183 cm, maximum load 30 kg + carrying bag

- Height adjustable, with locking pin
- Tube diameter: Ø 35 mm
- Adjustable height

**Package contents**

- 1 x bag

**OMNITRONIC A-3603 Class-D 2.1 Amplifier**

3-channel PA amplifier with crossover network - 4 ohms: 1 x 2000 W, 2 x 800 W

- 3-channel PA amplifier with class D circuitry and switch mode power supply
- Adjustable crossover frequency for satellites and subwoofer
- 2.1 operation or 3-channel operation selectable
- 3 level controls
- LED VU meter and LEDs for activated protective circuit (protect) and overload (clip) per channel
- Electronically balanced inputs via XLR mounting jacks, with XLR feed-through outputs
- Speaker outputs via lockable Speaker plugs
- Rugged steel chassis with aluminum front panel
- (19") 48.3 cm rack installation 2 U
- For application areas such as: Clubs/dancing school; Installation; mobile use; mobile djs / entertainer; restaurants, bars and hotels; Rental; sports centres/gyms

**Package contents**

- 1 x amplifier, 1 x user manual, 1 x power cord, 4 x foot, 4 x screw

**ROADINGER Rack Profi 2U 45cm**

Rack case, PRO version

- High-quality workmanship with birch multiplex 9 mm, dark brown, laminated
- Aluminum profile frames 20mm with rounded edges
- 4 hinged, chromium plated case handles
- 4 high-quality spring locks
- 4 rubber feet
- Branded hardware
- With profile rails suitable for 19" units
- 2 U
- Made in Europe
- For further information about this product, please refer to the Data Sheet under "Downloads"

**PSSO Speaker cable Speakon 2x2.5 5m bk**

High-quality speaker cable

- Built with NEUTRIK connector
- Made in Germany

**Package contents**

- 1 x speaker cable

**Technical specifications:**

---

Weight: 80,57 kg

---

**OMNITRONIC PAS-151 MK3 Subwoofer**

Power: Program: 1400W

|                        |  |
|------------------------|--|
|                        | Rated: 700W RMS  |
| Frequency range:       | 40 - 200 Hz  |
| Sensitivity:           | 97 dB (1W/1m)  |
| Max. SPL:              | 127 dB   |
| Impedance:             | 8 ohms   |
| Attachment system:     | Flange: M20 thread   |
| Connections:           | Input: speaker via 2 x speaker built-in socket (F)                                   |
| Speaker:               | 1 x woofer 15" with ferrit magnet<br>Basket material: aluminum<br>Voice coil lows 4" |
| Type of speaker:       | Subwoofer  |
| Type of construction:  | Vented   |
| Mould carrying handle: | 2 pc/pcs   |
| Transport aid:         | Wheels optional  |
| Material:              | Birch multiplex  |
| Color:                 | Black, textured coating, painted   |
| Dimensions:            | Width: 46 cm<br>Depth: 56 cm<br>Height: 52 cm  |
| Weight:                | 31,25 kg   |

#### OMNITRONIC PAS-210 MK3 2-Way Top

|                        |   |
|------------------------|---|
| Power:                 | Program: 500W<br>Rated: 250W RMS  |
| Frequency range:       | 65 - 20000 Hz   |
| Sensitivity:           | 96 dB (1W/1m)   |
| Max. SPL:              | 123 dB  |
| Dispersion angle:      | 90° x 60°   |
| Impedance:             | 8 ohms  |
| Attachment system:     | Dual flange: Ø 35mm (0°/5°)   |
| Flying points:         | 5 x M8 thread; 4 x M10 thread   |
| Connections:           | Input: speaker via 2 x speaker built-in socket (F)  |
| Crossover frequency:   | 3200 Hz   |
| Speaker:               | 1 x woofer 10"<br>Basket material: aluminum<br>Voice coil lows 2,5"<br>1 x compression tweeter highs 1" with ferrit magnet<br>Voice coil compression tweeter highs 1,5"<br>Horn vent 1" |
| Type of speaker:       | Compact cabinet speaker   |
| Mould carrying handle: | 2 pc/pcs  |
| Material:              | Birch multiplex   |
| Color:                 | Black, textured coating, painted  |
| Dimensions:            | Width: 32 cm<br>Depth: 52,5 cm  |

|         |               |
|---------|---------------|
|         | Height: 30 cm |
| Weight: | 12,95 kg      |

#### OMNITRONIC Speaker Stand MOVE MK2 set

|                            |                                    |
|----------------------------|------------------------------------|
| Maximum carrying capacity: | 30 kg                              |
| Tube diameter sector:      | 35                                 |
| Height:                    | Maximum: 183 cm<br>Minimum: 100 cm |
| Attachment system:         | Ø 35mm                             |
| Type (general stands):     | Speaker stand/manual               |
| Material:                  | Steel; Steel                       |
| Color:                     | Black                              |
| Weight:                    | 5,10 kg                            |

#### OMNITRONIC A-3603 Class-D 2.1 Amplifier

|                    |  |
|--------------------|--|
| Power supply:      | 100-240 V AC, 50/60 Hz   |
| Power consumption: | 685 W 1/8 power  |
| Output power:      | 2 x 800 W RMS (4 ohms)<br>2 x 400 W RMS (8 ohms)<br>1 x 2000 W RMS (4 ohms)<br>1 x 1000 W RMS (8 ohms)               |
| Power connection:  | Mains input via P-Con (blue), mounting version power supply cord with safety plug (provided)                         |
| Frequency range:   | 20 - 20000 Hz  |
| S/N ratio:         | >100 dB  |
| THD:               | <0,003 % at 1 kHz  |
| Impedance:         | Input: 20 kOhm , bal.<br>Input: 10 kOhm , unbal.   |
| Gain:              | Chanal 1 26 dB<br>Chanal 2 26 dB<br>Chanal 3 32 dB   |
| Circuitry:         | Class D  |
| Slew rate:         | >10 V/µs   |
| Damping factor:    | >500   |
| Control elements:  | Power switch, level control per channel, mode switch (2/3 channels), crossover frequency                             |
| Status LED:        | Protect, clip, level meter, bridged  |
| Connections:       | Input: line via 3 x 3-pin XLR<br>Link: line via 3 x 3-pin XLR<br>Output: speaker via 3 x speaker built-in socket (F) |
| Housing design:    | (19") 48.3 cm rack installation 2 U  |
| Dimensions:        | Width: 48,3 cm<br>Depth: 41 cm<br>Height: 8,9 cm   |
| Weight:            | 9,10 kg  |

**ROADINGER Rack Profi 2U 45cm**

|                          |   |
|--------------------------|---|
| Maximum load:            | 50 kg   |
| Aluminum profile frames: | 20 mm   |
| Case handle:             | 4 pc/pcs  |
| Lock:                    | Spring lock: 4 pc/pcs                             |
| Transport aid:           | 4 x rubber feet                                   |
| Use of brands:           | Branded hardware                                  |
| Material:                | Birch multiplex, 9 mm                             |
| Color:                   | Dark brown, laminated                             |
| Front panel width:       | 19"   |
| Mounting height:         | Approx. 9 cm (2 U)                                |
| Mounting depth:          | 450 mm  |
| Housing design:          | 2 U   |
| Dimensions:              | Width: 55,5 cm<br>Depth: 59,5 cm<br>Height: 17 cm |
| Weight:                  | 7,55 kg   |

**PSSO Speaker cable Speakon 2x2.5 5m bk**

|                     |                                       |
|---------------------|---------------------------------------|
| Cable construction: | 2 x 2,5 mm <sup>2</sup> speaker cable |
| Cable length:       | 5 m                                   |
| Plug A:             | 1 x 2-pin SpeakON (M)                 |
| Plug B:             | 1 x 2-pin SpeakON (M)                 |
| Use of brands:      | Built with NEUTRIK connector          |
| Color:              | Black                                 |
| Weight:             | 560 g                                 |