

EUROLITE Set AKKU THA-20PC TRC + Stand + Bag

Battery powered LED theater spot incl. speaker stand and matching transport bag

Art. No.: 20000796

GTIN: 4026397687392



List price: 315.35 €

incl. 19% VAT.

Features:

EUROLITE AKKU THA-20PC TRC Theater Spot bk

Battery powered LED theater spotlight with manual brightness regulation

- Two additional frost filters provide a soft, homogeneous light
 - New LED technology that simulates the color temperature curve of a halogen lamp when dimming
 - Rugged metal housing
 - Cordless, flexible and versatile
 - Battery operation up to 2h
 - Integrated automatic charging of the battery and status indicator
 - 1 powerful LED 17 W COB (chip-on-board) Dim to warm (homogenous color mix)
 - Dimmer electronic
 - The device is cooled by passive convection cooling
 - Control via stand-alone
 - Flicker-free
 - With a beam angle of 17°
 - Very high color rendering index (CRI)
 - With mounting bracket
 - Rubber feet
 - Silent operation
 - For application areas such as: Trade fair and shop fitting; wedding/gala/events; video and photography; restaurants, bars and hotels
 - Application possibility: Suspended; on stand
- Package contents**
- 1 x spotlight, 1 x user manual, 1 x external mains adapter, 1 x filter frame, 1 x barndoor, 2 x frost filter

Logistic

EAN / GTIN: 4026397687392

Weight: 6,00 kg

Length: 1.20 m

Width: 0.60 m

Height: 0.60 m

OMNITRONIC Speaker Stand BOB System

Speaker stand for BOB speakers, extendable up to 170 cm

- Tube diameter: Ø 30 mm
- Adjustable height
- Scratchproof and shockproof

Package contents

- 1 x stand, 1 x user manual

OMNITRONIC BOB Transport Bag for Tripod/Distance Tube

Accessory for the BOB series

- Suitable for stands and distance tubes
- Made of easy-care artificial black textile
- High-quality workmanship with textile , black

Package contents

- 1 x bag

Technical specifications:

Weight:	4,75 kg
---------	---------

EUROLITE AKKU THA-20PC TRC Theater Spot bk

Power supply:	100-240 V AC, 50/60 Hz
IP classification:	IP20
Power connection:	Mains input via coaxial power connector (M) mounting version power supply cord with AC adapter (provided)
Battery pack type:	1 x lithium ion 11,1 V, 2600 mAh, 28,86 Wh
Battery pack:	Battery operation up to 2h Recharging time 3h
LED type:	1 x 17 W COB (chip-on-board) Dim to warm (homogenous color mix)
Cooling:	Passive convection cooling
Control:	Stand-alone
Projection:	Flicker-free
Beam angle:	17°
Beam angle (1/2 peak):	17° Frost filter 19° Frost filter 26°
Color temperature:	3000K
Color rendering index (CRI):	92 Ra
Housing color:	Black
Attachment system:	Mounting bracket
Transport aid:	Rubber feet
Dimensions:	Length: 21 cm Width: 14,5 cm Height: 21 cm

Weight:	2,38 kg
Noise classification:	Class 0 (no noise at all)
Legal specifications	
Special product:	Not designed for household room illumination
Intended use:	Show effect lighting

OMNITRONIC Speaker Stand BOB System

Maximum carrying capacity:	14 kg
Height:	Maximum: 195 cm Minimum: 107 cm Adjustable in 6 steps with locking pin
Attachment system:	M10 thread
Type (general stands):	Speaker stand/manual
Material:	Steel
Color:	Black, painted; , scratchproof and shockproof
Main pipe diameter:	Ø 3 cm
Extension tube diameter:	Ø 2,5 cm
Weight:	2,15 kg

Locking screw M10 for STW

Weight:	0,03 kg
---------	---------

OMNITRONIC BOB Transport Bag for Tripod/Distance Tube

Material:	Textile
Color:	Black
Dimensions:	Length: 106 cm Width: 9 cm Depth: 7 cm
Weight:	0,19 kg