

EUROLITE Set LED THA-40PC TRC + Stand

Fanless PC spot with 57 W white light LED including speaker stand

Art. No.: 20000799

GTIN: 4026397687422



List price: 296.31 €

incl. 19% VAT.

Features:

EUROLITE LED THA-40PC TRC Theater-Spot bk

Fanless PC spot with 57 W white light LED, color rendering index (CRI) >90

- Rugged metal housing
- 1 powerful LED 57 W COB (chip-on-board) warm white (WW)
- Dimmer electronic
- The device is cooled by passive convection cooling
- Control via stand-alone; Rotary dial for brightness; Dimmer
- Flicker-free
- With a beam angle of 12° - 47°
- Very high color rendering index (CRI)
- With Mounting bracket
- Silent operation
- For application areas such as: Trade fair and shop fitting; Wedding/gala/events; restaurants, bars and hotels; video and photography
- Rubber feet

Package contents

- 1 x spotlight, 1 x barn door, 1 x filter frame, 1 x user manual

Logistic

EAN / GTIN: 4026397687422

Weight: 7,00 kg

Length: 1.20 m

Width: 0.60 m

Height: 0.60 m

Bulky product

OMNITRONIC Speaker Stand BOB System

Speaker stand for BOB speakers, extendable up to 170 cm

- Tube diameter: Ø 30 mm
- Adjustable height
- Scratchproof and shockproof

Package contents

- 1 x stand, 1 x user manual

Technical specifications:

Weight: 5,98 kg

EUROLITE LED THA-40PC TRC Theater-Spot bk

| | |
|------------------------------|---|
| Power supply: | 100-240 V AC, 50/60 Hz |
| Power consumption: | 40 W |
| IP classification: | IP20 |
| Protection class: | Protection class I |
| Power connection: | Fixed power supply cord with safety plug |
| Fuse: | 5 x 20 mm, T 1 A Fuse replaceable |
| LED: | 1 x 57 W COB (chip-on-board) warm white (WW) |
| Color temperature: | 3100K |
| Cooling: | Passive convection cooling |
| Control: | Stand-alone; Rotary dial for brightness; Dimmer |
| Projection: | Flicker-free |
| Beam angle: | 12° - 47° |
| Beam angle (1/2 peak): | 12 - 36° |
| Beam angle (1/10 peak): | 18 - 47° |
| Color rendering index (CRI): | 92 Ra |
| Illuminance in Lux (lx): | Narrow 3m: 2008 lx, 6m: 514 lx Wide 3m: 482 lx, 6m: 141 lx |
| Housing color: | Black |
| Attachment system: | Mounting bracket |
| Transport aid: | Rubber feet |
| Material: | Aluminum casting |
| Slot for spot length: | 13,1 cm x 13,1 cm |
| Dimensions: | Length: 26 cm Width: 20 cm Depth: 25 cm |
| Weight: | 3,82 kg |
| Noise classification: | Class 0 (no noise at all) |
| Power cord | |
| Cable construction: | 3 x 0,75 mm ² H05VV-F |
| Cable length: | Approx. 1 m |
| Mounting bracket | |
| Diameter mounting holes: | 1 x Ø10mm; 2 x Ø6mm |
| Material: | Metal, 3 mm |
| Barndoor | |
| Material: | Aluminum, 1,5 mm; metal |

| | |
|--------------------------|--|
| Ring diameter: | Outside: 12,9 mm Inside: 10,9 mm |
| <hr/> | |
| Filter frame | |
| Diameter mounting holes: | 1 x Ø4mm |
| Shape: | Octagonal |
| Material: | Aluminum, 0,8 mm |
| Dimensions: | Width: 13 cm Height: 13 cm Diameter: Ø 10,5 cm |
| <hr/> | |
| Legal specifications | |
| Special product: | Not designed for household room illumination |
| Intended use: | Show effect lighting |

OMNITRONIC Speaker Stand BOB System

| | |
|----------------------------|--|
| Maximum carrying capacity: | 14 kg |
| Height: | Maximum: 195 cm Minimum: 107 cm Adjustable in 6 steps with locking pin |
| Attachment system: | M10 thread |
| Type (general stands): | Speaker stand/manual |
| Material: | Steel |
| Color: | Black, painted; , scratchproof and shockproof |
| Main pipe diameter: | Ø 3 cm |
| Extension tube diameter: | Ø 2,5 cm |
| Weight: | 2,15 kg |