

EUROLITE Set 4x LED CBB-2 COB RGB Bar + Case

4x LED light effect bar with RGB color mixing including PRO flightcase

Art. No.: 2000809

GTIN: 4026397687965



Features:

- 2 LEDs 30 W COB (chip-on-board) 3in1 TCL RGB (homogenous color mix)
- Color blend stepless; color change adjustable; color fade adjustable; Dimmer electronic
- Strobe effect
- Integrated show programs
- Direct color selection for 18 preset colors
- The device is cooled by cooling fan
- Control via IR remote control; sound to light via microphone; stand-alone; master/slave function; DMX; QuickDMX via USB (optional); W-DMX by wireless solution via USB (optional)
- Fixtures available for LED PC-Control 512; EASY SHOW 1; LED EASY OPERATOR 4x4; LED EASY OPERATOR 4x6; LED EASY OPERATOR DELUXE; Light Captain; EASY SHOW 2; EASY SHOW 3; Colorchief
- Flicker-free
- With a beam angle of 38°
- With mounting bracket
- 4 digit 7-segment LED display
- Mains input and output for power linking up to 8 units
- For application areas such as: Clubs/dancing school; stage; decoration; wedding/gala/events; mobile djs / entertainer; restaurants, bars and hotels
- Application possibility: Standing; suspended; on stand
- <p>ROADINGER Flightcase 4 x LED CBB-2 COB Bar
- <h2 class="featureSatz">Trunk case, PRO version</h2>For optimal security
- With accessory compartment
- High-quality workmanship with birch multiplex 7 mm, dark brown, laminated
- Interior with foam padding
- Aluminum profile frames 20mm with rounded edges
- 2 hinged, chromium plated case handles

Logistic

EAN / GTIN: 4026397687965

Weight: 20,00 kg

Length: 1.20 m

Width: 0.41 m

Height: 0.30 m

Bulky product

- 2 chrome tip-over locks
- 2 high-quality butterfly locks
- Branded hardware

Technical specifications:

Weight: 17.41 kg

EUROLITE LED CBB-2 COB RGB Bar

| | |
|--------------------------|---|
| Power supply: | 100-240 V AC, 50/60 Hz |
| Power consumption: | 50 W |
| IP classification: | IP20 |
| Lamp type: | LED lamp |
| LED type: | 2 x 30 W COB (chip-on-board) 3in1 TCL RGB (homogenous color mix) |
| Flash rate: | 0.5 - 24 Hz |
| DMX channels: | 3; 4; 5; 6; 11 |
| DMX input: | 1 x 3-pin XLR (M) mounting version |
| DMX output: | 1 x 3-pin XLR (F) mounting version |
| Cooling: | Cooling fan |
| Control: | IR remote control; sound to light via microphone; stand-alone; master/slave function; DMX; QuickDMX via USB (optional); W-DMX by wireless solution via USB (optional) |
| Fixtures available for: | LED PC-Control 512; EASY SHOW 1; LED EASY OPERATOR 4x4; LED EASY OPERATOR 4x6; LED EASY OPERATOR DELUXE; Light Captain; EASY SHOW 2; EASY SHOW 3; Colorchief |
| Projection: | Flicker-free |
| PWM frequency: | 2900 Hz |
| Beam angle: | 38° |
| Beam angle (1/2 peak): | 38° |
| Beam angle (1/10 peak): | 70° |
| Housing color: | Black |
| Attachment system: | Mounting bracket |
| Display type: | 4 digit 7-segment LED display |
| Material: | Metal |
| Dimensions: | Width: 15.5 cm Depth: 24 cm Height: 17.5 cm |
| Weight: | 2.39 kg |
| Noise classification: | Class 2 (slight noise) |
| Photobiological safety: | Risk Group 0 |
| Diameter mounting holes: | 3 x Ø11mm; 4 x Ø7mm |
| Material: | Metal, 2 mm |

| | |
|------------------|--|
| Battery: | 1 x button cell CR2025 |
| Special product: | Not designed for household room illumination |
| Intended use: | Show effect lighting |

ROADINGER Flightcase 4 x LED CBB-2 COB Bar

| | |
|--------------------------|---|
| Maximum load: | 50 kg |
| Aluminum profile frames: | 20 mm |
| Case handle: | 2 pc/pcs |
| Stop hinge: | 2 pc/pcs |
| Lock: | Butterfly lock: 2 pc/pcs |
| Use of brands: | Branded hardware |
| Material: | Birch multiplex, 7 mm, laminated; birch multiplex |
| Color: | Dark brown, laminated |
| Device compartment: | 25 cm x 12 cm x 25 cm |
| Accessory compartment: | 10 cm x 27 cm x 25 cm |
| Inside dimensions: | 63.5 cm x 27 cm x 25 cm |
| Dimensions: | Width: 68 cm Depth: 31 cm Height: 29 cm |
| Weight: | 7.85 kg |

Scope of delivery:

- 1 x spotlight
- 1 x power cord
- 1 x remote control
- 1 x battery
- 1 x user manual