



### Features:

#### EUROLITE LED KLS Laser Bar Next FX Light Set

Bar with powerful spots, UV strobe LEDs, laser (RG, 2M), QuickDMX port and carrying bag

- 2 laser diodes project hundreds of red and green laser beams
  - 2 rotating derbies for mirror ball effects
  - Compact lightweight
  - Crossbar with integrated DMX control unit and TV spigot for tripod installation
  - When fog is used, this effect becomes especially attractive
  - Dimmer electronic; color blend stepless; program selection
  - 26 integrated show programs
  - The device is cooled by cooling fan
  - Control via DMX; stand-alone; sound to light via microphone; IR remote control; QuickDMX via USB (optional); wireless footswitch (optional)
  - Fixtures available for Light Captain; EASY SHOW 2; EASY SHOW 3; Colorchief
  - TV spigot
  - With mounting bracket
  - 3 digit 7-segment LED display
  - Mains input and output for power linking up to 8 units
  - For application areas such as: Clubs/dancing school; wedding/gala/events; mobile djs / entertainer; party room; restaurants, bars and hotels
  - Application possibility: On stand
- laser**
- Laser
  - Laser class 2M <BR> does not require additional protective measures or appointment of a laser safety officer

**spotlight**

### Logistic

EAN / GTIN: 4026397689082

Weight: 20,00 kg

Length: 1.35 m

Width: 0.35 m

Height: 0.51 m

Bulky product

- 3 LEDs 4 W SMD 9080 4in1 QCL RGB/WW (homogenous color mix)<BR>4 spots controlled separately
- With a beam angle of 7°  
**light effect**
- 4 LEDs 3 W SMD 8072 R/G/B/WW<BR> lighting effects controlled separately
- Multi beam effect; fan effect; flower effect  
**bar**
- 4 LEDs 1.5 W SMD 8072 ultra violet (UV)<BR> LEDs controlled separately
- UV effect; strobe effect

### EUROLITE STV-60-WOT EU Steel Stand black

Lighting stand, made in EU, maximum load 30 kg, height 150-315 cm

- Stable lighting stand for mobile use
- Adjustable height
- TV spigot
- Available in various colors
- Made in Europe

### Technical specifications:

---

Weight: 16.15 kg

---

### EUROLITE LED KLS Laser Bar Next FX Light Set

Power supply:	100-240 V AC, 50/60 Hz
Power consumption:	90 W
IP classification:	IP20
Protection class:	Protection class I
Power connection:	Mains input via P-Con (blue), mounting version power supply cord with safety plug (provided)
Cable length:	3 m
Power output:	1 x P-Con (gray), mounting version
Fuse:	T 1 A fuse replaceable
Lamp type:	LED lamp
DMX channels:	6; 8; 11; 21; 25; 29
DMX input:	1 x 3-pin XLR (M) mounting version
DMX output:	1 x 3-pin XLR (F) mounting version
Cooling:	Cooling fan
Control:	DMX; stand-alone; sound to light via microphone; IR remote control; QuickDMX via USB (optional); wireless footswitch (optional)
Fixtures available for:	Light Captain; EASY SHOW 2; EASY SHOW 3; Colorchief
Housing color:	Black
Attachment system:	TV spigot Ø 28mm 2x mounting bracket
Display type:	3 digit 7-segment LED display
Dimensions:	Width: 111 cm Depth: 15 cm

	Height: 41 cm
Weight:	10.50 kg
Noise classification:	Class 2 (slight noise)
Battery:	Button cell 3.0 V CR2025 lithium manganese built-in
Laser class:	2M
Laser color:	R/G
Laser module:	Red (R) 100 mW 650nm Green (G) 30 mW 532nm
LED type:	4 x 3 W SMD 8072 R/G/B/WW
LED type:	3 x 4 W SMD 9080 4in1 QCL RGB/WW (homogenous color mix)
Beam angle:	7°
Beam angle (1/2 peak):	Spot 7°
Beam angle (1/10 peak):	Spot 20°
LED type:	4 x 1.5 W SMD 8072 ultra violet (UV)
Flash rate:	0 - 30 Hz

#### **EUROLITE STV-60-WOT EU Steel Stand black**

Maximum carrying capacity:	30 kg
Height:	Maximum: 320 cm Minimum: 150 cm
Attachment system:	TV spigot Ø 28mm
Type (general stands):	Light stand/manual
Material:	Steel/magnesium
Color:	Black
Transport dimensions:	126 cm x 12 cm x 15 cm
Weight:	5.65 kg

#### **Scope of delivery:**

##### **1 x EUROLITE LED KLS Laser Bar Next FX Light Set**

- 1 x device
- 1 x user manual
- 1 x power cord
- 1 x bag
- 1 x declaration of conformity
- 1 x remote control
- 2 x mounting bracket
- 2 x knurled screw
- 2 x washer
- 1 x terminating plug (power)

##### **1 x EUROLITE STV-60-WOT EU Steel Stand black**

- 1 x stand
- 1 x user manual