



The article is no longer in our assortment.

Features:

EUROLITE LED B-40 HCL Beam Effect

LED beam effect with RGBAW+UV color mixing

- Precision lenses fill the room with countless rotating beams
- 5 powerful LEDs 12 W high-power 6in1 HCL RGBWA/UV
- Color blend stepless; color change adjustable; color fade adjustable; Dimmer electronic; Rotation speed stepless
- Multi beam effect; Strobe effect; UV effect
- 4 integrated show programs
- Direct color selection for 25 preset colors
- The device is cooled by low-noise cooling fan
- Control via DMX; Sound to light via Microphone; Master/slave function; stand-alone
- With Mounting bracket
- 4 digit 7-segment LED display
- Preprogrammed in Light'J; LED PC-Control 512; EASY SHOW 1; Light Captain; EASY SHOW 2; EASY SHOW 3
- Very quiet working noise
- Mains input and output for power linking up to 8 units

Package contents

- 1 x light effect, 1 x user manual, 1 x power cord, 1 x omega bracket, 2 x screw, 2 x washer

Logistic

EAN / GTIN: 4026397690590

Weight: 12,00 kg

Length: 0.82 m

Width: 0.41 m

Height: 0.52 m

ROADINGER Flightcase 1x B-40 HCL/Laser

Trunk case, PRO version

- High-quality workmanship with birch multiplex 6,5 mm, dark brown
- Interior with foam padding

- Aluminum profile frames 20mm with rounded edges
- Hinged, chromium plated case handle
- 2 chrome tip-over locks
- 2 high-quality spring locks
- Branded hardware
- European engineering
- For further information about this product, please refer to the Data Sheet under "Downloads"

Technical specifications:

Weight: 11,05 kg

EUROLITE LED B-40 HCL Beam Effect

Power supply:	100-240 V AC, 50/60 Hz
Power consumption:	50 W
IP classification:	IP20
Protection class:	Protection class I
Power connection:	Mains input via IEC connector (M) mounting version power supply cord with safety plug (provided)
Power output:	IEC connector (F) mounting version
Lamp type:	LED lamp
LED:	5 x 12 W high-power 6in1 HCL RGBWA/UV
Flash rate:	0 - 20 Hz
DMX channels:	5; 11
DMX input:	3-pin XLR (M) mounting version
DMX output:	3-pin XLR (F) mounting version
Cooling:	Low-noise cooling fan
Control:	DMX; Sound to light via Microphone; Master/slave function; stand-alone
Preprogrammed in:	Light J; LED PC-Control 512; EASY SHOW 1; Light Captain; EASY SHOW 2; EASY SHOW 3
Housing color:	Black
Attachment system:	Mounting bracket
Display type:	4 digit 7-segment LED display
Dimensions:	Width: 32 cm Depth: 32 cm Height: 38 cm
Weight:	4,15 kg
Noise classification:	Class 1 (very slight noise, suitable for noise-sensitive environments)
Legal specifications	
Special product:	Not designed for household room illumination
Intended use:	Show effect lighting

ROADINGER Flightcase 1x B-40 HCL/Laser

Maximum load:	25 kg
Aluminum profile frames:	20 mm
Case handle:	1 pc/pcs
Stop hinge:	2 pc/pcs
Lock:	Spring lock: 2 pc/pcs
Use of brands:	Branded hardware
Material:	Birch multiplex, 6,5 mm, laminated
Color:	Dark brown
Device compartment:	32,5 cm x 32,5 cm x 39 cm
Dimensions:	Length: 40 cm Width: 40 cm Height: 48 cm
Weight:	6,90 kg