

## EUROLITE Set 4x LED IP PAR 3x8W QCL Spot + Case

Art. No.: 20000846

GTIN: 4026397690620



### Features:

#### EUROLITE LED IP PAR 3x8W QCL Spot

Weather-proof (IP65) spotlight with 3 x 8 W LED and 4in1 QCL RGBW color mixing

- 3 LEDs 8 W high-power 4in1 QCL RGBW (homogenous color mix)
- Strobe effect
- Direct color selection for 25 preset colors
- The device is cooled by passive convection cooling
- Control via stand-alone; IR remote control; DMX
- Fixtures available for EASY SHOW 1; LED EASY OPERATOR 4x4; LED EASY OPERATOR 4x6; LED EASY OPERATOR DELUXE; Light´J; Light Captain; EASY SHOW 2; EASY SHOW 3; Colorchief
- Flicker-free
- With a beam angle of 15°
- With double bracket
- LCD display
- Suitable for outdoor use IP65
- With pressure compensation membrane
- For application areas such as: Architecture; stage; clubs/dancing school; wedding/gala/events; theater; rental; video and photography
- Silent operation
- Application possibility: Standing; suspended; on stand

### Logistic

EAN / GTIN: 4026397690620

Weight: 24,00 kg

Length: 1.20 m

Width: 0.60 m

Height: 0.60 m

Bulky product

#### ROADINGER Flightcase PRO 4x LED IP PAR 3x8W QCL/3x9W SCL

Trunk case, PRO version

- High-quality workmanship with birch multiplex 6.5 mm, dark brown, laminated

- Interior with foam padding
- Aluminum profile frames 25mm with rounded edges
- 2 hinged, chromium plated case handles
- 2 chrome tip-over locks
- 1 high-quality butterfly lock
- Branded hardware
- Made in Europe

Technical specifications:

|         |          |
|---------|----------|
| Weight: | 21.10 kg |
|---------|----------|

EUROLITE LED IP PAR 3x8W QCL Spot

|                         |                                                                                                                                                   |
|-------------------------|---------------------------------------------------------------------------------------------------------------------------------------------------|
| Power supply:           | 100-240 V AC, 50/60 Hz                                                                                                                            |
| Power consumption:      | 30 W                                                                                                                                              |
| IP classification:      | IP65                                                                                                                                              |
| Power connection:       | Mains input via IP T-Con (M) mounting version power supply cord with safety plug (provided)                                                       |
| Power output:           | IP T-Con (F) mounting version                                                                                                                     |
| Fuse:                   | 5 x 20 mm, T 1 A fuse serviceable                                                                                                                 |
| Lamp type:              | LED lamp                                                                                                                                          |
| LED type:               | 3 x 8 W high-power 4in1 QCL RGBW (homogenous color mix)                                                                                           |
| Flash rate:             | 0.5 - 23 Hz                                                                                                                                       |
| DMX channels:           | 3; 4; 5; 6; 10                                                                                                                                    |
| DMX input:              | 3-pin XLR (M) mounting version IP                                                                                                                 |
| DMX output:             | 3-pin XLR (F) mounting version IP                                                                                                                 |
| Cooling:                | Passive convection cooling                                                                                                                        |
| Control:                | Stand-alone; IR remote control; DMX                                                                                                               |
| Fixtures available for: | EASY SHOW 1; LED EASY OPERATOR 4x4; LED EASY OPERATOR 4x6; LED EASY OPERATOR DELUXE; Light J; Light Captain; EASY SHOW 2; EASY SHOW 3; Colorchief |
| Projection:             | Flicker-free                                                                                                                                      |
| PWM frequency:          | 5900 Hz                                                                                                                                           |
| Beam angle:             | 15°                                                                                                                                               |
| Beam angle (1/2 peak):  | 15°                                                                                                                                               |
| Beam angle (1/10 peak): | 30°                                                                                                                                               |
| Housing color:          | Black                                                                                                                                             |
| Attachment system:      | Double bracket                                                                                                                                    |
| Display type:           | LCD display                                                                                                                                       |
| Material:               | Aluminum casting                                                                                                                                  |
| Dimensions:             | Width: 21.5 cm<br>Depth: 17.1 cm<br>Height: 24.4 cm                                                                                               |
| Weight:                 | 3.00 kg                                                                                                                                           |

|                          |                                                         |
|--------------------------|---------------------------------------------------------|
| Noise classification:    | Class 0 (no noise at all)                               |
| Photobiological safety:  | Risk Group 0                                            |
| Diameter mounting holes: | 1 x Ø11mm                                               |
| Material:                | Metal, 2 mm                                             |
| Cable construction:      | 3 x 1.0 mm² H05RN-F                                     |
| Cable length:            | Approx. 1.2 m                                           |
| Battery:                 | 1 x button cell 3.0 V CR2025 lithium manganese built-in |
| Special product:         | Not designed for household room illumination            |
| Intended use:            | Show effect lighting                                    |

#### **ROADINGER Flightcase PRO 4x LED IP PAR 3x8W QCL/3x9W SCL**

|                          |                                                |
|--------------------------|------------------------------------------------|
| Maximum load:            | 50 kg                                          |
| Aluminum profile frames: | 25 mm                                          |
| Case handle:             | 2 pc/pcs                                       |
| Stop hinge:              | 2 pc/pcs                                       |
| Lock:                    | Butterfly lock: 1 pc/pcs                       |
| Use of brands:           | Branded hardware                               |
| Material:                | Birch multiplex, 6.5 mm                        |
| Color:                   | Dark brown, laminated                          |
| Inside dimensions:       | 48 cm x 47 cm x 28 cm                          |
| Device compartment:      | 17 cm x 22.5 cm x 27 cm                        |
| Accessory compartment:   | 11.5 cm x 46.5 cm x 28 cm                      |
| Dimensions:              | Length: 53 cm<br>Width: 52 cm<br>Height: 33 cm |
| Weight:                  | 9.10 kg                                        |

#### **Scope of delivery:**

1 x spotlight  
 1 x power cord  
 1 x remote control  
 1 x battery  
 1 x user manual