



List price: 998.41 €

incl. 19% VAT.

Features:

- Positioning within PAN and TILT
- <p>EUROLITE LED KLS Scan Next FX Compact Light Set
- <p class="featureSatz">Compact bar with derby, spots, scanners, UV effect, QuickDMX port and bag
- Crossbar with integrated DMX control unit and TV spigot for tripod installation
- When fog is used, this effect becomes especially attractive
- Positioning within PAN and TILT
- Color wheel; gobo wheel with static gobos
- 20 integrated show programs
- Control via DMX; IR remote control; Sound to light via Microphone; stand-alone; Master/slave function; Wireless footswitch (optional); QuickDMX via USB (optional); W-DMX by wireless solution via USB (optional); CRMX by LumenRadio via USB (optional)
- OLED display
- For application areas such as: Rental; small rental; Wedding/gala/events; mobile use; mobile djs / entertainer
- Mains input and output for power linking up to 8 units
- Color wheel with 8 dichroic filters plus open
half colors selectable
- Preprogrammed in Light Captain; EASY SHOW 2; EASY SHOW 3
- Application possibility: Suspended; on stand
- **spotlight**
- 3 powerful LEDs 7 W high-power 4in1 QCL RGB/WW (homogenous color mix)
4 spots controlled separately
- With a beam angle of 15°
- **light effect**
- 2 powerful LEDs 3 W R/G/B
- **moving light**

Logistic

EAN / GTIN: 4026397690842
Weight: 14,80 kg
Length: 1.30 m
Width: 0.50 m
Height: 0.30 m
Bulky product

- 1 powerful LED 15 W cold white (CW)
bar
- 4 powerful LEDs 1 W high-power ultra violet (UV)
 LEDs controlled separately
Package contents
- 1 x device, 1 x user manual, 1 x power cord, 1 x declaration of conformity, 2 x mounting bracket, 1 x remote control, 1 x battery, 1 x bag, 2 x knurled screw, 2 x washer, 1 x terminating plug (power)
- <p>EUROLITE Foot Switch KLS Compact Light Set MK2
- <p class="featureSatz">Wireless foot switch for KLS Compact Light Sets
- Powered by a battery/battery pack
- Non-slip pedal housing
Package contents
- 1 x foot control, 1 x declaration of conformity, 1 x battery

Technical specifications:

Weight: 13,64 kg

EUROLITE LED KLS Scan Next FX Compact Light Set

Power supply:	100-240 V AC, 50/60 Hz
Power consumption:	115 W
IP classification:	IP20
Protection class:	Protection class I
Power connection:	Mains input via P-Con (blue), mounting version power supply cord with safety plug (provided)
Power output:	P-Con (gray), mounting version
Fuse:	5 x 20 mm, T 2 A Fuse replaceable
Lamp type:	LED lamp
Equipment:	Color wheel; gobo wheel with static gobos
Color generation:	Cold white (CW)
Color generation:	Color wheel with 8 dichroic filters plus open Half colors selectable
DMX channels:	3; 7; 13; 14; 15; 18; 19; 30; 32; 39
DMX input:	1 x 3-pin XLR (M) mounting version
DMX output:	1 x 3-pin XLR (F) mounting version
Cooling:	Cooling fan
Control:	DMX; IR remote control; Sound to light via Microphone; stand-alone; Master/slave function; Wireless footswitch (optional); QuickDMX via USB (optional); W-DMX by wireless solution via USB (optional); CRMX by LumenRadio via USB (optional)
Preprogrammed in:	Light Captain; EASY SHOW 2; EASY SHOW 3
Illuminance in Lux (lx):	Red (R) 1m: 1022 lx, 3m: 125 lx, 6m: 33 lx Green (G) 1m: 2448 lx, 3m: 285 lx, 6m: 75 lx Blue (B) 1m: 395 lx, 3m: 47 lx, 6m: 13 lx Warm white (WW) 1m: 1892 lx, 3m: 219 lx, 6m: 58 lx All 1m: 4853 lx, 3m: 676 lx, 6m: 175 lx

Housing color:	Black
Attachment system:	TV spigot Ø 28mm 2x Mounting bracket
Display type:	OLED display
Dimensions:	Width: 1,1 m Depth: 15,5 cm Height: 43 cm
Weight:	12,80 kg
Noise classification:	Class 3 (clearly perceptible sounds)
Spotlight	
LED:	3 x 7 W high-power 4in1 QCL RGB/WW (homogenous color mix)
Beam angle:	15°
Beam angle (1/2 peak):	15°
Beam angle (1/10 peak):	28°
Light effect	
LED:	2 x 3 W R/G/B
Moving light	
LED:	1 x 15 W cold white (CW)
Bar	
LED:	4 x 1 W high-power ultra violet (UV)
Remote control	
Battery:	1 x Button cell 3.0 V CR2025 lithium manganese built-in
Legal specifications	
Special product:	Not designed for household room illumination
Intended use:	Show effect lighting

EUROLITE Foot Switch KLS Compact Light Set MK2

IP classification:	IP20
Battery:	1 x 9.0 V E block 6F22 zinc carbon included
Carrier frequency:	433,92 MHz
Housing color:	Black
Housing design:	Non-slip pedal housing
Dimensions:	Width: 42,0 cm Depth: 14,0 cm Height: 4,5 cm
Weight:	840 g