



### Features:

#### EUROLITE AKKU TL-3 QCL RGB+UV Trusslight

Battery-powered trusslight with RGB+UV LEDs and IR remote control

- Ideal for ALUTRUSS DECOLOCK DQ3 3-point system
- Threaded inserts for suspended installation
- Cordless, flexible and versatile
- Battery operation up to 8h depending on program used
- Integrated automatic charging of the battery and status indicator
- 3 LEDs 4 W SMD 9080 4in1 RGB/UV (homogenous color mix)
- Color blend stepless; color change adjustable; color fade adjustable; Dimmer electronic; white balance; Energy-saving mode
- Strobe effect
- Integrated show programs
- Direct color selection for 20 preset colors
- The device is cooled by passive convection cooling
- Control via stand-alone; DMX; IR remote control; sound to light via microphone; master/slave function; QuickDMX via USB (optional); W-DMX by wireless solution via USB (optional); CRMX by LumenRadio via USB (optional)
- Flicker-free
- With a beam angle of 10°
- 4 digit 7-segment LED display
- Rubber feet
- Mains input and output for power linking up to 8 units
- For application areas such as: Stage; clubs/dancing school; decoration; wedding/gala/events; mobile djs / entertainer; rental; advertisement/Shop window
- Silent operation
- Application possibility: Standing; suspended

### Logistic

EAN / GTIN: 4026397690880

Weight: 15,00 kg

Length: 0.70 m

Width: 0.27 m

Height: 0.52 m

## ROADINGER Flightcase 4x AKKU TL-3 TCL Trusslight

Carrying case, PRO version

- With accessory compartment
- With 4 device compartments
- High-quality workmanship with birch multiplex 7 mm, dark brown, laminated
- Interior with foam padding
- Aluminum profile frames 25mm with rounded edges
- Hinged, chromium plated case handle
- 2 chrome tip-over locks
- 1 high-quality butterfly lock
- Branded hardware
- Made in Europe
- For further information about this product, please refer to the Data Sheet under "Downloads"

## Technical specifications:

---

Weight: 9.55 kg

---

## EUROLITE AKKU TL-3 QCL RGB+UV Trusslight

Power supply:	100-240 V AC, 50/60 Hz
Protection class:	Protection class III
Power connection:	Battery/battery pack built-in Mains input via IEC connector (M) mounting version power supply cord with safety plug (provided)
Power output:	IEC connector (F) mounting version
Fuse:	F 1 A fuse replaceable
Battery pack type:	1 x lithium ion 11.1 V, 2200 mAh, 24.42 Wh
Battery pack:	Battery operation up to 8h depending on program used Recharging time 2.5h
Lamp type:	LED lamp
LED type:	3 x 4 W SMD 9080 4in1 RGB/UV (homogenous color mix)
Flash rate:	0 - 20 Hz
DMX channels:	2; 4; 5; 6; 9
DMX input:	3-pin XLR (M) mounting version
DMX output:	3-pin XLR (F) mounting version
Cooling:	Passive convection cooling
Control:	Stand-alone; DMX; IR remote control; sound to light via microphone; master/slave function; QuickDMX via USB (optional); W-DMX by wireless solution via USB (optional); CRMX by LumenRadio via USB (optional)
Fixtures available for:	Light Captain; EASY SHOW 2; EASY SHOW 3; Light J; Colorchief
Projection:	Flicker-free

Beam angle (1/2 peak):	10°
Beam angle (1/10 peak):	33°
Housing color:	Black matte
Display type:	4 digit 7-segment LED display
Transport aid:	Rubber feet
Dimensions:	Width: 12.22 cm Depth: 10.8 cm Height: 14.3 cm
Weight:	1.26 kg
Noise classification:	Class 0 (no noise at all)
Battery:	1 x button cell 3.0 V CR2025 lithium manganese built-in
Special product:	Not designed for household room illumination
Intended use:	Show effect lighting

### **ROADINGER Flightcase 4x AKKU TL-3 TCL Trusslight**

Maximum load:	25 kg
Aluminum profile frames:	25 mm
Case handle:	1 pc/pcs
Stop hinge:	2 pc/pcs
Lock:	Butterfly lock: 1 pc/pcs
Use of brands:	Branded hardware
Material:	Birch multiplex, 7 mm
Color:	Dark brown, laminated
Device compartment:	12 cm x 11.5 cm x 6.5 cm
Inside dimensions:	19 cm x 8 cm
Dimensions:	Width: 47.5 cm Depth: 24.5 cm Height: 21.5 cm
Weight:	4.50 kg

### **Scope of delivery:**

- 1 x spotlight
- 1 x user manual
- 1 x power cord
- 1 x remote control
- 1 x battery