



Features:

EUROLITE LED TL-3 RGB+UV Trusslight

Variable truss light and uplight with bright 3 x 7 W RGB+UV LED

- Compact and bright
- Perfect for ALUTRUS 3 point system DECOLOCK DQ3
- Color change adjustable; Dimmer electronic; color blend stepless
- UV effect; strobe effect
- 2 integrated show programs
- Direct color selection for 17 preset colors
- The device is cooled by passive convection cooling
- Control via IR remote control; stand-alone; DMX; master/slave function; sound to light via microphone; QuickDMX via USB (optional); W-DMX by wireless solution via USB (optional); CRMX by LumenRadio via USB (optional)
- Fixtures available for LED PC-Control 512; LED EASY OPERATOR DELUXE; Light Captain; EASY SHOW 2; EASY SHOW 3; Colorchief
- Flicker-free
- With a beam angle of 16°
- 4 digit 7-segment LED display
- Rubber feet
- Mains input and output for power linking up to 8 units
- For application areas such as: Stage; clubs/dancing school; decoration; wedding/gala/events; mobile djs / entertainer; advertisement/Shop window
- Very quiet working noise
- Application possibility: Standing; suspended

Logistic

EAN / GTIN: 4026397690989

Weight: 10,00 kg

Length: 0.54 m

Width: 0.53 m

Height: 0.45 m

ROADINGER Flightcase 4x TL-3 TCL

Trunk case, PRO version

- With accessory compartment
- High-quality workmanship with birch multiplex 7 mm, black, laminated
- Interior with foam padding
- Rugged carrying handle
- 2 chrome tip-over locks
- Made in Germany
- For further information about this product, please refer to the Data Sheet under "Downloads"

Technical specifications:

Weight: 8.36 kg

EUROLITE LED TL-3 RGB+UV Trusslight

Power supply:	100-240 V AC, 50/60 Hz
Power consumption:	15 W
IP classification:	IP20
Protection class:	Protection class I
Power connection:	Mains input via IEC connector (M) mounting version power supply cord with safety plug (provided)
Power output:	1 x IEC connector (F) mounting version
Fuse:	F 1 A fuse replaceable
Lamp type:	LED lamp
Flash rate:	1 - 20 Hz
DMX channels:	3; 4; 4; 8
DMX input:	1 x 3-pin XLR (M) mounting version
DMX output:	1 x 3-pin XLR (F) mounting version
Cooling:	Passive convection cooling
Control:	IR remote control; stand-alone; DMX; master/slave function; sound to light via microphone; QuickDMX via USB (optional); W-DMX by wireless solution via USB (optional); CRMX by LumenRadio via USB (optional)
Fixtures available for:	LED PC-Control 512; LED EASY OPERATOR DELUXE; Light Captain; EASY SHOW 2; EASY SHOW 3; Colorchief
Projection:	Flicker-free
Beam angle:	16°
Beam angle (1/2 peak):	16°
Beam angle (1/10 peak):	33°
Housing color:	Black
Attachment system:	M10 thread
Display type:	4 digit 7-segment LED display

Transport aid:	Rubber feet
Material:	Metal
Dimensions:	Width: 12.2 cm Depth: 10.8 cm Height: 11.7 cm
Weight:	0.89 kg
Noise classification:	Class 1 (very slight noise, suitable for noise-sensitive environments)
Photobiological safety:	Risk Group 0
Cable construction:	3 x 0.75 mm ² H05VV-F
Cable length:	Approx. 1.1 m
Battery:	1 x button cell 3.0 V CR2025 lithium manganese built-in
Special product:	Not designed for household room illumination
Intended use:	Show effect lighting

ROADINGER Flightcase 4x TL-3 TCL

Maximum load:	25 kg
Carrying handle:	1 pc/pcs
Stop hinge:	2 pc/pcs
Material:	Birch multiplex, 7 mm
Color:	Black, laminated
Compartment dimensions:	12.5 cm x 11.5 cm x 9.5 cm
Accessory compartment:	12.5 cm x 28 cm x 10.5 cm
Inside dimensions:	37.5 cm x 28 cm x 10.5 cm
Dimensions:	Width: 47 cm Depth: 31 cm Height: 18 cm
Weight:	4.80 kg

Scope of delivery:

1 x spotlight
1 x power cord
1 x remote control
1 x battery
1 x user manual