



List price: 1188.81 €

incl. 19% VAT.

Features:

EUROLITE LED 4C-7 Silent Slim Spot

Silent 4in1 LED spotlight with RGBW color mixture

- Flat version requires minimal space when mounting
- 7 powerful LEDs 8 W high-power 4in1 QCL RGBW (homogenous color mix)
- 9 integrated show programs
- Direct color selection for 19 preset colors
- The device is cooled by passive convection cooling
- Control via stand-alone; IR remote control; DMX; QuickDMX via USB (optional); Sound to light via Microphone; Master/slave function
- With a beam angle of 16°
- With double bracket
- 4 digit 7-segment LED display
- Color blend stepless; Dimmer electronic
- Strobe effect
- Silent operation
- Preprogrammed in LED PC-Control 512; EASY SHOW 1; LED EASY OPERATOR 4x4; LED EASY OPERATOR 4x6; Light'J; LED EASY OPERATOR DELUXE; Light Captain; EASY SHOW 2; EASY SHOW 3
- Mains input and output for power linking up to 8 units
- For application areas such as: Clubs/dancing school; Wedding/gala/events; Stage; theater; mobile djs / entertainer
- Application possibility: Standing; suspended; on stand

Package contents

- 1 x spotlight, 1 x user manual, 1 x power cord, 1 x remote control, 1 x battery

Logistic

EAN / GTIN: 4026397690996

Weight: 21,00 kg

Length: 1.20 m

Width: 0.80 m

Height: 0.60 m

Bulky product

EUROLITE QuickDMX USB Wireless Transmitter/Receiver

Wireless miniature DMX transceiver 2.4 GHz, phantom powered

- User-friendly USB plug with swivel antenna
- Wireless DMX eliminates extensive cabling between DMX controller and the DMX-controlled units in lighting installations
- Due to GFSK modulation with 78 channels, interference-free operation also alongside other QuickDMX transceiver and wireless devices in the 2.4 GHz band (e.g. Wi-Fi and Bluetooth)
- LED indication for functions
- Transceiver, to be used as transmitter or receiver
- Requires 5 V phantom power for operation
- Can receive and process up to 512 DMX channels
- Can transmit up to 512 DMX channels
- Control via DMX; QuickDMX; plug and play
- Operating range up to 400m with line-of-sight
- Up to 6 transmitters can be operated in parallel without interference

Package contents

- 1 x device, 1 x user manual, 1 x declaration of conformity

ROADINGER Flightcase 4x SLS Size M

Trunk case, PRO version

- Individually adjustable and removable dividers for universal use
- With 4 Device compartments
- High-quality workmanship with birch multiplex 7 mm, dark brown, laminated
- Interior with foam padding
- Aluminum profile frames 30mm with rounded edges
- Hinged, chromium plated case handle
- 2 chrome tip-over locks
- 1 high-quality butterfly lock
- Branded hardware
- Made in Europe
- For further information about this product, please refer to the Data Sheet under "Downloads"

Technical specifications:

Weight: 18,11 kg

EUROLITE LED 4C-7 Silent Slim Spot

Power supply:	100-240 V AC, 50/60 Hz
Power consumption:	40 W
IP classification:	IP20
Power connection:	Mains input via P-Con (blue), mounting version power supply cord with safety plug (provided)
Power output:	1 x P-Con (gray), mounting version
Lamp type:	LED lamp
LED:	7 x 8 W high-power 4in1 QCL RGBW (homogenous color mix)
Flash rate:	1 - 20 Hz
DMX channels:	3; 4; 5; 6; 9
DMX input:	1 x 3-pin XLR (M) mounting version
DMX output:	1 x 3-pin XLR (F) mounting version

Cooling:	Passive convection cooling
Control:	Stand-alone; IR remote control; DMX; QuickDMX via USB (optional); Sound to light via Microphone; Master/slave function
Preprogrammed in:	LED PC-Control 512; EASY SHOW 1; LED EASY OPERATOR 4x4; LED EASY OPERATOR 4x6; Light J; LED EASY OPERATOR DELUXE; Light Captain; EASY SHOW 2; EASY SHOW 3
Beam angle:	16°
Beam angle (1/2 peak):	16°
Beam angle (1/10 peak):	35°
Housing color:	Black
Attachment system:	Double bracket
Display type:	4 digit 7-segment LED display
Dimensions:	Width: 24,5 cm Depth: 11 cm Height: 25,5 cm
Weight:	2,60 kg
Noise classification:	Class 0 (no noise at all)
Photobiological safety:	Risk Group 0
Remote control	
Battery:	1 x Button cell 3.0 V CR2025 lithium manganese built-in
Legal specifications	
Special product:	Not designed for household room illumination
Intended use:	Show effect lighting

EUROLITE QuickDMX USB Wireless Transmitter/Receiver

Power supply:	5 V DC
IP classification:	IP20
Power connection:	Mains input via USB A (M) connectable version
DMX channels:	Input 512 Output 512
DMX output:	1 x USB, type A
Control:	DMX; QuickDMX; plug and play
Range:	Range up to 400m with line-of-sight
Carrier frequency:	2,4 GHz
Parallel mode:	Max. 6 transmitter
Modulation:	GFSK
Color:	Black
Dimensions:	Width: 8,6 cm Depth: 4 cm Height: 1,1 cm
Weight:	10 g

ROADINGER Flightcase 4x SLS Size M

Maximum load:	25 kg
Aluminum profile frames:	30 mm
Case handle:	1 pc/pcs
Stop hinge:	2 pc/pcs
Lock:	Butterfly lock: 1 pc/pcs
Use of brands:	Branded hardware
Material:	Birch multiplex, 7 mm
Color:	Dark brown, laminated
Compartment dimensions:	12 cm x 25 cm x 35,5 cm
Inside dimensions:	49,5 cm x 25 cm x 35,5 cm
Dimensions:	Width: 52,5 cm Depth: 28,5 cm Height: 44,5 cm
Weight:	7,65 kg