



List price: 1486.31 €

incl. 19% VAT.

Features:

EUROLITE AKKU IP Flat Light 3 bl

Flat IP65 spotlight in black with 3 x 8 W 4in1 QCL RGBW LED, QuickDMX transceiver

- Integrated QuickDMX transceiver for wireless DMX control
- Battery operation up to 16h depending on program used
- 3 powerful LEDs 8 W high-power 4in1 QCL RGBW (homogenous color mix)
- The device is cooled by passive convection cooling
- Control via Master/slave function; IR remote control; QuickDMX; stand-alone; Sound to light via Microphone
- Flicker-free
- With a beam angle of 15°
- With Mounting bracket
- LCD display
- Suitable for outdoor use IP65
- For application areas such as: Small rental; Rental; Wedding/gala/events; mobile djs / entertainer
- Dimmer electronic; Dimmer speed (step response) adjustable; color blend stepless; color change adjustable; colors preset
- Strobe effect
- Preprogrammed in Light´J; Light Captain; EASY SHOW 1; EASY SHOW 2; EASY SHOW 3
- Cordless, flexible and versatile
- Integrated automatic charging of the battery and status indicator
- Silent operation
- Application possibility: Standing

Package contents

- 1 x device, 1 x external mains adapter, 1 x power cord, 1 x remote control, 1 x battery, 1 x declaration of conformity, 1 x user manual

Logistic

EAN / GTIN: 4026397691054

Weight: 12,50 kg

Length: 0.82 m

Width: 0.41 m

Height: 0.52 m

ROADINGER Flightcase 4x AKKU Flat Light Series

Carrying case, PRO version

- High-quality workmanship with birch multiplex 7 mm, dark brown, laminated
- Interior with foam padding
- Aluminum profile frames 25mm with rounded edges
- Rugged carrying handle
- 1 high-quality butterfly lock
- Branded hardware
- Made in Europe
- For further information about this product, please refer to the Data Sheet under "Downloads"

Technical specifications:

Weight: 10,58 kg

EUROLITE AKKU IP Flat Light 3 bl

Power supply: 100-240 V AC, 50/60 Hz
12,6 V DC 2,5 A

IP classification: IP65

Protection class: Protection class III

Power connection: Mains input via Coaxial power connector (M)
mounting version power supply cord with Euro
plug (provided)
Battery/battery pack

Battery pack type: 2 x lithium ion 11,1 V, 2600 mAh, 28,86 Wh

Battery pack: Battery operation up to 16h depending on
program used
Recharging time 4h

Lamp type: LED lamp

LED: 3 x 8 W high-power 4in1 QCL RGBW
(homogenous color mix)

Flash rate: 1 - 23 Hz

DMX channels: 3; 4; 6; 8; 10

Cooling: Passive convection cooling

Control: Master/slave function; IR remote control;
QuickDMX; stand-alone; Sound to light via
Microphone

Preprogrammed in: Light J; Light Captain; EASY SHOW 1; EASY
SHOW 2; EASY SHOW 3

Projection: Flicker-free

Carrier frequency: 2,4 GHz

Beam angle: 15°

Beam angle (1/2 peak): 15°

Beam angle (1/10 peak): 33°

Housing color: Black

Attachment system: Mounting bracket

| | |
|-----------------------|---|
| Display type: | LCD display |
| Dimensions: | Width: 17,2 cm Depth: 13,8 cm Height: 6,2 cm |
| Weight: | 1,61 kg |
| Noise classification: | Class 0 (no noise at all) |
| Remote control | |
| Battery: | 1 x Button cell 3.0 V CR2032 lithium manganese built-in |
| Legal specifications | |
| Special product: | Not designed for household room illumination |
| Intended use: | Show effect lighting |

ROADINGER Flightcase 4x AKKU Flat Light Series

| | |
|--------------------------|---|
| Aluminum profile frames: | 25 mm |
| Carrying handle: | 1 pc/pcs |
| Lock: | Butterfly lock: 1 pc/pcs |
| Use of brands: | Branded hardware |
| Material: | Birch multiplex, 7 mm |
| Color: | Dark brown, laminated |
| Compartment dimensions: | 7 cm x 18,5 cm x 9 cm |
| Accessory compartment: | 38 cm x 6,5 cm x 12 cm |
| Inside dimensions: | 38 cm x 25 cm x 12 cm |
| Dimensions: | Width: 42 cm Depth: 31 cm Height: 20 cm |
| Weight: | 4,15 kg |