



List price: 1902.81 €

incl. 19% VAT.

Features:

- Positioning within
- <p>EUROLITE LED TMH-W63 Moving Head Zoom Wash
- <p class="featureSatz">Washlight with 7 x 9 W LEDs, 4in1 QCL RGBW-Farbmischung and motorized zoom
- 7 powerful LEDs 9 W high-power 4in1 QCL RGBW (homogenous color mix)
- Positioning within 540° PAN, 195° TILT
- Exact positioning (16 bit resolution)
- Zoom motor driven
- Motion macros adjustable; Dimmer electronic; color blend stepless
- Strobe effect
- Integrated show programs
- The device is cooled by cooling fan
- Control via stand-alone; DMX; master/slave function; sound to light via microphone; QuickDMX via USB (optional); W-DMX by wireless solution via USB (optional); CRMX by LumenRadio via USB (optional)
- Preprogrammed in Light´J; EASY SHOW 1; Light Captain; EASY SHOW 2; EASY SHOW 3
- Flicker-free
- With a beam angle of 6° - 29°
- 4 digit 7-segment LED display
- Rubber feet
- For application areas such as: Clubs/dancing school; wedding/gala/events; mobile djs / entertainer; small rental
- Application possibility: Suspended; standing

Package contents

- 1 x moving light, 1 x user manual, 1 x power cord, 1 x omega bracket, 1 x safety eyelet
- <p>EUROLITE LED TMH-S30 Moving Head Spot

Logistic

EAN / GTIN: 4026397693805

Weight: 20,00 kg

Length: 1.20 m

Width: 0.80 m

Height: 0.60 m

Bulky product

- <p class="featureSatz">Compact moving head Spot with 30 W LED, gobos and color wheel
- 1 powerful LED 30 W COB (chip-on-board) cold white (CW)
- Positioning within 540° PAN, 170° TILT
- Exact positioning (16 bit resolution)
- Color wheel; focus manual; gobo wheel with rotating gobos
- Dimmer electronic
- Beam effect; strobe effect
- Color wheel with 7 dichroic filters plus open
half colors selectable, Rainbow effect with adjustable speed in both directions
- Gobo wheel with rotating gobos, 7 gobos and open
shake effect
- Gobos changeable
- Slot-in gobo system for easy gobo replacement
- Integrated show programs
- The device is cooled by cooling fan
- Control via stand-alone; DMX; sound to light via microphone; master/slave function; CRMX by LumenRadio via USB (optional); W-DMX by wireless solution via USB (optional); QuickDMX via USB (optional)
- Preprogrammed in Light'J; LED PC-Control 512; EASY SHOW 1; Light Captain; EASY SHOW 2; EASY SHOW 3
- Flicker-free
- With a beam angle of 8°
- 4 digit 7-segment LED display
- Rubber feet
- For application areas such as: Clubs/dancing school; wedding/gala/events; party room; mobile djs / entertainer
- Application possibility: Standing; suspended

Package contents

- 1 x moving light, 1 x user manual, 1 x power cord, 1 x omega bracket, 1 x safety eyelet
- <p>EUROLITE EASY Show
- <p class="featureSatz">Programmed DMX controller for over 200 spotlights from EUROLITE
- Easy-to-use DMX controller and DMX recorder
- Designed for DMX beginners with 200 programmed fixtures
- DMX recording function for your own projects, ideal for installations or rental companies
- Ideal for colored LED spotlights, KLS systems, moving lights and lighting effects
- No programming required, simply connect your spotlights and get started
- All spotlights can be freely combined to a show
- Data storage on USB flash drives
- A list of all preset devices is available at www.steinigke.de
- Program speed adjustable; color fade adjustable; Dimmer
- Strobe effect
- 24 integrated show programs
- Direct color selection for 12 preset colors
- Preprogrammed 24 scenes/chases and 12 cues
- Control via DMX; sound to light via microphone; QuickDMX via USB (optional)
- Monochrome LCD display
- Desktop console housing
- For application areas such as: Clubs/dancing school; party room; mobile djs / entertainer; restaurants, bars and hotels; installation
- Silent operation

Package contents

- 1 x controller, 1 x user manual, 1 x external mains adapter, 2 x USB cable, 2 x mounting bracket, 4 x screw
- <p>EUROLITE QuickDMX USB Wireless Transmitter/Receiver
- <p class="featureSatz">Wireless miniature DMX transceiver 2.4 GHz, phantom powered
- User-friendly USB plug with swivel antenna
- Wireless DMX eliminates extensive cabling between DMX controller and the DMX-controlled units in lighting installations
- Due to GFSK modulation with 78 channels, interference-free operation also alongside other QuickDMX transceiver and wireless devices in the 2.4 GHz band (e.g. Wi-Fi and Bluetooth)
- LED indication for functions
- Transceiver, to be used as transmitter or receiver
- Requires 5 V phantom power for operation
- Can receive and process up to 512 DMX channels
- Can transmit up to 512 DMX channels
- Control via DMX; QuickDMX; plug and play
- Operating range up to 400m with line-of-sight

- Up to 6 transmitters can be operated in parallel without interference

Package contents

- 1 x device, 1 x user manual, 1 x declaration of conformity

Technical specifications:

Weight: 15,78 kg

EUROLITE LED TMH-W63 Moving Head Zoom Wash

Power supply:	100-240 V AC, 50/60 Hz
Power consumption:	100 W
IP classification:	IP20
Power connection:	Mains input via P-Con (blue), mounting version power supply cord with safety plug (provided)
Fuse:	5 x 20 mm, T 2 A fuse replaceable
Lamp type:	LED lamp
LED type:	7 x 9 W high-power 4in1 QCL RGBW (homogenous color mix)
Max. TILT movement:	195° exact positioning (16 bit resolution)
Max. PAN movement:	540° exact positioning (16 bit resolution)
Flash rate:	2,5 - 18 Hz
Equipment:	Zoom motor driven
DMX channels:	15
DMX input:	3-pin XLR (M) mounting version
DMX output:	3-pin XLR (F) mounting version
Cooling:	Cooling fan
Control:	Stand-alone; DMX; master/slave function; sound to light via microphone; QuickDMX via USB (optional); W-DMX by wireless solution via USB (optional); CRMX by LumenRadio via USB (optional)
Preprogrammed in:	Light`J; EASY SHOW 1; Light Captain; EASY SHOW 2; EASY SHOW 3
Projection:	Flicker-free
PWM frequency:	2900 Hz
Beam angle:	6° - 29°
Beam angle (1/2 peak):	6 - 18°
Beam angle (1/10 peak):	11 - 29°
Illuminance in Lux (lx):	Narrow red (R) 1m: 7863 lx, 3m: 1074 lx, 6m: 269 lx Narrow green (G) 1m: 15691 lx, 3m: 2179 lx, 6m: 549 lx Narrow blue (B) 1m: 2497 lx, 3m: 406 lx, 6m: 103 lx Narrow cold white (CW) 1m: 17115 lx, 3m: 2398 lx, 6m: 605 lx Narrow all 1m: 40258 lx, 3m: 5714 lx, 6m: 1432 lx

Wide red (R) 1m: 1586 lx, 3m: 187 lx, 6m: 49 lx
 Wide green (G) 1m: 3083 lx, 3m: 385 lx, 6m: 101 lx
 Wide blue (B) 1m: 568 lx, 3m: 73 lx, 6m: 20 lx
 Wide cold white (CW) 1m: 3372 lx, 3m: 407 lx, 6m: 106 lx
 Wide all 1m: 8103 lx, 3m: 994 lx, 6m: 257 lx

Housing color:	Black
Display type:	4 digit 7-segment LED display
Transport aid:	Rubber feet
Dimensions:	Width: 21,0 cm Depth: 16,0 cm Height: 29,5 cm
Weight:	4,15 kg
Noise classification:	Class 2 (slight noise)
Legal specifications	
Special product:	Not designed for household room illumination
Intended use:	Show effect lighting

EUROLITE LED TMH-S30 Moving Head Spot

Power supply:	100-240 V AC, 50/60 Hz
Power consumption:	45 W
IP classification:	IP20
Power connection:	Mains input via P-Con (blue), mounting version power supply cord with safety plug (provided)
Fuse:	T 1 A fuse replaceable
Lamp type:	LED lamp
LED type:	1 x 30 W COB (chip-on-board) cold white (CW)
Max. TILT movement:	170° exact positioning (16 bit resolution)
Max. PAN movement:	540° exact positioning (16 bit resolution)
Equipment:	Color wheel; focus manual; gobo wheel with rotating gobos
Color generation:	Color wheel with 7 dichroic filters plus open Half colors selectable, Rainbow effect with adjustable speed in both directions
Gobos:	Gobo wheel with rotating gobos, 7 gobos and open Outside diameter 14mm Image diameter 10mm Shake effect Gobos changeable Slot-in gobo system for easy gobo replacement
DMX channels:	10; 12
DMX input:	3-pin XLR (M) mounting version
DMX output:	3-pin XLR (F) mounting version
Cooling:	Cooling fan

Control:	Stand-alone; DMX; sound to light via microphone; master/slave function; CRMX by LumenRadio via USB (optional); W-DMX by wireless solution via USB (optional); QuickDMX via USB (optional)
Preprogrammed in:	Light´J; LED PC-Control 512; EASY SHOW 1; Light Captain; EASY SHOW 2; EASY SHOW 3
Projection:	Flicker-free
Beam angle:	8°
Beam angle (1/2 peak):	8°
Color temperature:	8000K
Illuminance in Lux (lx):	Cold white (CW) 1m: 14450 lx, 3m: 1574 lx, 6m: 377 lx
Housing color:	Black
Display type:	4 digit 7-segment LED display
Transport aid:	Rubber feet
Dimensions:	Width: 17,0 cm Depth: 15,0 cm Height: 24,0 cm
Weight:	3,03 kg
Noise classification:	Class 3 (clearly perceptible sounds)
Legal specifications	
Special product:	Not designed for household room illumination
Intended use:	Show effect lighting

EUROLITE EASY Show

Power supply:	100-240 V AC, 50/60 Hz 5V DC 250 mA
Power consumption:	1,25 W
IP classification:	IP20
Power connection:	Mains input via USB C (W) mounting version power supply cord with AC adapter
Programs:	Preprogrammed 24 scenes/chases and 12 cues
DMX input:	3-pin XLR (M) mounting version
DMX output:	3-pin XLR (F) mounting version
Control:	DMX; sound to light via microphone; QuickDMX via USB (optional)
Housing color:	Black
Display type:	Monochrome LCD display
Available storage media:	USB devices
Housing design:	Desktop console housing
Dimensions:	Width: 28,0 cm Depth: 14,5 cm Height: 6,0 cm
Weight:	1,35 kg
Noise classification:	Class 0 (no noise at all)

EUROLITE QuickDMX USB Wireless Transmitter/Receiver

Power supply:	5V DC
IP classification:	IP20
Power connection:	Mains input via USB A (M) connectable version
DMX channels:	Input 512 Output 512
DMX output:	1 x USB, type A
Control:	DMX; QuickDMX; plug and play
Range:	Range up to 400m with line-of-sight
Carrier frequency:	2,4 GHz
Parallel mode:	Max. 6 transmitter
RF power output:	19 dBm
Modulation:	GFSK
Color:	Black
Dimensions:	Width: 8,6 cm Depth: 4 cm Height: 1,1 cm
Weight:	0,01 kg