

EUROLITE Set 2x LED KLS Laser Bar PRO + Easy Show + 2x M-4 Speaker System Stand

GTIN: 4026397693812



List price: 1486.31 €

incl. 19% VAT.

Features:

EUROLITE LED KLS Laser Bar PRO FX Light Set

Bar with 2 strong derbies and spots, white/UV strobe LEDs, laser (RG, 2M)

- Enhanced version with very high brightness and additional UV LEDs
- Compact lightweight
- Crossbar with integrated DMX control unit and stand sleeve
- 2 laser diodes project hundreds of red and green laser beams
- 2 rotating derbies for mirror ball effects
- When fog is used, this effect becomes especially attractive
- Laser; multi beam effect; flower effect; UV effect; strobe effect
- 39 integrated show programs
- The device is cooled by cooling fan
- Control via stand-alone; DMX; IR remote control; sound to light via microphone; wireless footswitch; master/slave function
- Preprogrammed in EASY SHOW 1; Light'J; LED PC-Control 512; Light Captain; EASY SHOW 2; EASY SHOW 3; Colorchief
- With mounting bracket
- Mains input and output for power linking up to 8 units
- For application areas such as: Wedding/gala/events; mobile use; clubs/dancing school; mobile djs / entertainer; rental
- Application possibility: On stand

lase

 Laser class 2M
 does not require additional protective measures or appointment of a laser safety officer

spotlight

 6 powerful LEDs 6 W SMD 8072 3in1 TCL RGB (homogenous color mix)
 spots controlled separately

Logistic

EAN / GTIN: 4026397693812

Weight: 36,00 kg Length: 1.20 m Width: 0.80 m Heigth: 1.50 m Bulky product - With a beam angle of 13°

light effect

- 6 powerful LEDs 2 W SMD 8072 R/G/B
 spots controlled separately

har

 4 powerful LEDs 2 W SMD 8072 2in1 BCL CW/UV (homogenous color mix)
 LEDs controlled separately

Package contents

1 x device, 1 x power cord, 1 x user manual, 1 x declaration of conformity, 1 x remote control, 1 x foot control, 2 x knurled screw, 2 x washer, 2 x mounting bracket, 2 x battery, 1 x bag

EUROLITE EASY Show

Programmed DMX controller for over 200 spotlights from EUROLITE

- Easy-to-use DMX controller and DMX recorder
- Designed for DMX beginners with 200 programmed fixtures
- DMX recording function for your own projects, ideal for installations or rental companies
- Ideal for colored LED spotlights, KLS systems, moving lights and lighting effects
- No programming required, simply connect your spotlights and get started
- All spotlights can be freely combined to a show
- Data storage on USB flash drives
- A list of all preset devices is available at www.steinigke.de
- Program speed adjustable; color fade adjustable; Dimmer
- Strobe effect
- 24 integrated show programs
- Direct color selection for 12 preset colors
- Preprogrammed 24 scenes/chases and 12 cues
- Control via DMX; sound to light via microphone; QuickDMX via USB (optional)
- Monochrome LCD display
- Desktop console housing
- For application areas such as: Clubs/dancing school; party room; mobile djs / entertainer; restaurants, bars and hotels; installation
- Silent operation

Package contents

 1 x controller, 1 x user manual, 1 x external mains adapter, 2 x USB cable, 2 x mounting bracket, 4 x screw

OMNITRONIC M-4 Speaker-System Stand

Aluminum speaker stand, height adjustable 140-345 cm, maximum load 18 kg

- Durable aluminum version
- Tube diameter: Ø 35 mm
- Adjustable height

Package contents

- 1 x user manual

| Technical specifications: | | |
|---------------------------|----------|--|
| | | |
| Weight: | 27,95 kg | |

EUROLITE LED KLS Laser Bar PRO FX Light Set

| Power supply: | 100-240 V AC, 50/60 Hz |
|--------------------|------------------------|
| Power consumption: | 150 W |
| IP classification: | IP20 |
| Protection class: | Protection class I |

| Power output: | Power connection: | Mains input via IEC connector (M) mounting version power supply cord with safety plug (provided) |
|-----------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------|-------------------------|--------------------------------------------------------------------------------------------------|
| LED lamp LED lamp | Power output: | 1 x IEC connector (F) mounting version |
| DMX channels: 3; 5; 10; 28 DMX input: 1 x 3-pin XLR (M) mounting version DMX output: 1 x 3-pin XLR (F) mounting version Cooling: Cooling fan Control: Stand-alone; DMX; IR remote control; sound to light via microphone; wireless footswitch; master/size function Preprogrammed in: EASY SHOW 1; Light U; LED PC-Control 512; Light Capitain; EASY SHOW 2; EASY SHOW 3; Colorchief Housing color: Black Attachment system: 2x mounting bracket Dimensions: Width: 1,030 cm Depth: 6,1 cm Height: 38,7 cm Weight: 10,00 kg Noise classification: Class 2 (slight noise) Power cord Cable length: 3 m Remote control Battery: 1 x button cell 3.0 V CR2025 lithium manganese built-in Foot control Battery: 1 x 9.0 V E block 6F22 zinc carbon included Laser Laser class: 2M Laser module: Red (R) 100 mW 650nm Green (G) 30 mW 532nm Light effect LED type: 6 x 2 W SMD 8072 R/G/B LED type: 6 x 6 W SMD 8072 3in1 TCL RGB (homogenous color mix) Beam angle: <td>Fuse:</td> <td>5 x 20 mm, T 3,15 A</td> | Fuse: | 5 x 20 mm, T 3,15 A |
| DMX input: 1 x 3-pin XLR (M) mounting version DMX output: 1 x 3-pin XLR (F) mounting version Cooling: Cooling fan Control: Stand-alone; DMX; IR remote control; sound to light via microphone; wireless footswitch; master/slave function Preprogrammed in: EASY SHOW 1; Light 'J; LED PC-Control 512; Light Captain; EASY SHOW 2; EASY SHOW 3; Colorchief Housing color: Black Attachment system: 2x mounting bracket Dimensions: Width: 1,030 cm Depth: 6,1 cm Height: 38,7 cm Weight: 10,00 kg Noise classification: Class 2 (slight noise) Power cord Cable length: Cable length: 3 m Remote control Battery: Battery: 1 x button cell 3.0 V CR2025 lithium manganese built-in Foot control Battery: 1 x 9.0 V E block 6F22 zinc carbon included Laser Laser class: 2 M Laser color: Laser module: Red (R) 100 mW 650mm Green (G) 30 mW 532nm Light effect LED type: 6 x 2 W SMD 8072 R/G/B LED type: 6 x 6 W SMD 8072 3in1 TCL RGB (homogenous color mix) | Lamp type: | LED lamp |
| DMX output: 1 x 3-pin XLR (F) mounting version Cooling: Cooling fan Control: Stand-alone; DMX; IR remote control; sound to light via microphone; wireless footswitch; master/stave function Preprogrammed in: EASY SHOW 1; Light 'J; LED PC-Control 512; Light Captain; EASY SHOW 2; EASY SHOW 3; Colorchief Housing color: Black Attachment system: 2x mounting bracket Dimensions: Width: 1,030 cm Depth: 6.1 cm Height: 38,7 cm Weight: 10,00 kg Noise classification: Class 2 (slight noise) Power cord Class 2 (slight noise) Cable length: 3 m Remote control Battery: 1 x button cell 3.0 V CR2025 lithium manganese built-in Foot control Battery: 1 x 9.0 V E block 6F22 zinc carbon included Laser Laser Laser color: R/G Laser module: Red (R) 100 mW 650nm Green (G) 30 mW 532nm Light effect LED type: 6 x 2 W SMD 8072 R/G/B Flash rate: 0 - 30 Hz Spotlight LED type: 6 x 6 W SMD 8072 3in1 TCL RGB (homogenous color mix) Beam angle (1/10 peak): 2 | DMX channels: | 3; 5; 10; 28 |
| Cooling: Cooling fan Control: Stand-alone; DMX; IR remote control; sound to light via microphone; wireless footswitch; master/slave function Preprogrammed in: EASY SHOW 1; Light 'J; LED PC-Control 512; Light Captain; EASY SHOW 2; EASY SHOW 3; Colorchief Housing color: Black Attachment system: 2x mounting bracket Dimensions: Width: 1,030 cm | DMX input: | 1 x 3-pin XLR (M) mounting version |
| Control: Stand-alone; DMX; IR remote control; sound to light via microphone; wireless footswitch; master/slave function Preprogrammed in: EASY SHOW 1; Light' J; LED PC-Control 512; Light Captain; EASY SHOW 2; EASY SHOW 3; Colorchief Housing color: Black Attachment system: 2x mounting bracket Dimensions: Width: 1,030 cm | DMX output: | 1 x 3-pin XLR (F) mounting version |
| light via microphone; wireless footswitch; master/slave function Preprogrammed in: EASY SHOW 1; Light 'J; LED PC-Control 512; Light Captain; EASY SHOW 2; EASY SHOW 3; Colorchief Housing color: Black Attachment system: 2x mounting bracket Dimensions: Width: 1,030 cm | Cooling: | Cooling fan |
| Light Captain; EASY SHOW 2; EASY SHOW 3; Colorchief | Control: | light via microphone; wireless footswitch; |
| Attachment system: 2x mounting bracket Dimensions: Width: 1,030 cm Depth: 6,1 cm Height: 38,7 cm Weight: 10,00 kg Noise classification: Class 2 (slight noise) Power cord Cable length: 3 m Remote control Battery: 1 x button cell 3.0 V CR2025 lithium manganese built-in Foot control Battery: 1 x 9.0 V E block 6F22 zinc carbon included Laser Laser class: 2M Laser color: R/G Laser module: Red (R) 100 mW 650nm Green (G) 30 mW 532nm Light effect LED type: 6 x 2 W SMD 8072 R/G/B Flash rate: 0 - 30 Hz Spotlight LED type: 6 x 6 W SMD 8072 3in1 TCL RGB (homogenous color mix) Beam angle (1/12 peak): 13° Beam angle (1/10 peak): 20° Bar LED type: 4 x 2 W SMD 8072 2in1 BCL CW/UV (homogenous color mix) | Preprogrammed in: | Light Captain; EASY SHOW 2; EASY SHOW 3; |
| Dimensions: Width: 1,030 cm Depth: 6,1 cm Height: 38,7 cm Weight: 10,00 kg Noise classification: Class 2 (slight noise) Power cord Cable length: Cable length: 3 m Remote control Battery: 1 x button cell 3.0 V CR2025 lithium manganese built-in Foot control Battery: Laser 1 x 9.0 V E block 6F22 zinc carbon included Laser Laser class: Laser color: R/G Laser module: Red (R) 100 mW 650nm Green (G) 30 mW 532nm Light effect LED type: LED type: 6 x 2 W SMD 8072 R/G/B Flash rate: 0 - 30 Hz Spotlight LED type: 6 x 6 W SMD 8072 3in1 TCL RGB (homogenous color mix) Beam angle: 13° Beam angle (1/2 peak): 13° Beam angle (1/10 peak): 20° Bar LED type: 4 x 2 W SMD 8072 2in1 BCL CW/UV (homogenous color mix) | Housing color: | Black |
| Depth: 6,1 cm | Attachment system: | 2x mounting bracket |
| Height: 38,7 cm | Dimensions: | Width: 1,030 cm |
| Weight: 10,00 kg Noise classification: Class 2 (slight noise) Power cord Cable length: 3 m Remote control Battery: 1 x button cell 3.0 V CR2025 lithium manganese built-in Foot control Battery: 1 x 9.0 V E block 6F22 zinc carbon included Laser Laser class: 2M Laser color: R/G Laser module: Red (R) 100 mW 650nm Green (G) 30 mW 532nm Light effect LED type: 6 x 2 W SMD 8072 R/G/B Flash rate: 0 - 30 Hz Spotlight LED type: 6 x 6 W SMD 8072 3in1 TCL RGB (homogenous color mix) Beam angle (1/2 peak): 13° Beam angle (1/10 peak): 20° Bar 4 x 2 W SMD 8072 2in1 BCL CW/UV (homogenous color mix) | | |
| Noise classification: Class 2 (slight noise) Power cord 3 m Remote control 1 x button cell 3.0 V CR2025 lithium manganese built-in Foot control 1 x 9.0 V E block 6F22 zinc carbon included Battery: 1 x 9.0 V E block 6F22 zinc carbon included Laser Laser class: Laser color: R/G Laser module: Red (R) 100 mW 650nm Green (G) 30 mW 532nm Light effect LED type: LED type: 6 x 2 W SMD 8072 R/G/B Flash rate: 0 - 30 Hz Spotlight LED type: LED type: 6 x 6 W SMD 8072 3in1 TCL RGB (homogenous color mix) Beam angle (1/2 peak): 13° Beam angle (1/10 peak): 20° Bar LED type: 4 x 2 W SMD 8072 2in1 BCL CW/UV (homogenous color mix) | | - |
| Power cord Cable length: 3 m Remote control Battery: 1 x button cell 3.0 V CR2025 lithium manganese built-in Foot control Battery: 1 x 9.0 V E block 6F22 zinc carbon included Laser Laser class: 2M Laser color: R/G Laser module: Red (R) 100 mW 650nm Green (G) 30 mW 532nm Light effect LED type: 6 x 2 W SMD 8072 R/G/B Flash rate: 0 - 30 Hz Spotlight LED type: 6 x 6 W SMD 8072 3in1 TCL RGB (homogenous color mix) Beam angle: 13° Beam angle (1/10 peak): 13° Beam angle (1/10 peak): 20° Bar LED type: 4 x 2 W SMD 8072 2in1 BCL CW/UV (homogenous color mix) | | |
| Cable length: 3 m Remote control Battery: 1 x button cell 3.0 V CR2025 lithium manganese built-in Foot control Battery: 1 x 9.0 V E block 6F22 zinc carbon included Laser 2M Laser color: R/G Laser module: Red (R) 100 mW 650nm Green (G) 30 mW 532nm Light effect LED type: LED type: 6 x 2 W SMD 8072 R/G/B Flash rate: 0 - 30 Hz Spotlight LED type: LED type: 6 x 6 W SMD 8072 3in1 TCL RGB (homogenous color mix) Beam angle: 13° Beam angle (1/2 peak): 13° Beam angle (1/10 peak): 20° Bar 4 x 2 W SMD 8072 2in1 BCL CW/UV (homogenous color mix) | | Class 2 (slight noise) |
| Remote control 1 x button cell 3.0 V CR2025 lithium manganese built-in Foot control 1 x 9.0 V E block 6F22 zinc carbon included Battery: 1 x 9.0 V E block 6F22 zinc carbon included Laser 2M Laser color: R/G Laser module: Red (R) 100 mW 650nm Green (G) 30 mW 532nm Light effect LED type: 6 x 2 W SMD 8072 R/G/B Flash rate: 0 - 30 Hz Spotlight LED type: 6 x 6 W SMD 8072 3in1 TCL RGB (homogenous color mix) Beam angle: 13° Beam angle (1/12 peak): 13° Beam angle (1/10 peak): 20° Bar LED type: 4 x 2 W SMD 8072 2in1 BCL CW/UV (homogenous color mix) | | |
| Battery: | | 3 m |
| Battery: | | |
| Battery: 1 x 9.0 V E block 6F22 zinc carbon included Laser 2M Laser color: R/G Laser module: Red (R) 100 mW 650nm Green (G) 30 mW 532nm Light effect ED type: LED type: 6 x 2 W SMD 8072 R/G/B Flash rate: 0 - 30 Hz Spotlight ED type: LED type: 6 x 6 W SMD 8072 3in1 TCL RGB (homogenous color mix) Beam angle: 13° Beam angle (1/2 peak): 13° Beam angle (1/10 peak): 20° Bar 4 x 2 W SMD 8072 2in1 BCL CW/UV (homogenous color mix) | Battery: | |
| Laser Laser class: 2M Laser color: R/G Laser module: Red (R) 100 mW 650nm Green (G) 30 mW 532nm Light effect ED type: LED type: 6 x 2 W SMD 8072 R/G/B Flash rate: 0 - 30 Hz Spotlight EED type: LED type: 6 x 6 W SMD 8072 3in1 TCL RGB (homogenous color mix) Beam angle: 13° Beam angle (1/2 peak): 13° Beam angle (1/10 peak): 20° Bar 4 x 2 W SMD 8072 2in1 BCL CW/UV (homogenous color mix) | Foot control | |
| Laser class: 2M Laser color: R/G Laser module: Red (R) 100 mW 650nm Green (G) 30 mW 532nm Light effect ED type: 6 x 2 W SMD 8072 R/G/B Flash rate: 0 - 30 Hz Spotlight LED type: 6 x 6 W SMD 8072 3in1 TCL RGB (homogenous color mix) Beam angle: 13° Beam angle (1/2 peak): 13° Beam angle (1/10 peak): 20° Bar 4 x 2 W SMD 8072 2in1 BCL CW/UV (homogenous color mix) | Battery: | 1 x 9.0 V E block 6F22 zinc carbon included |
| Laser color: R/G Laser module: Red (R) 100 mW 650nm Green (G) 30 mW 532nm Light effect LED type: 6 x 2 W SMD 8072 R/G/B Flash rate: 0 - 30 Hz Spotlight LED type: 6 x 6 W SMD 8072 3in1 TCL RGB (homogenous color mix) Beam angle: 13° Beam angle (1/2 peak): 13° Beam angle (1/10 peak): 20° Bar 4 x 2 W SMD 8072 2in1 BCL CW/UV (homogenous color mix) | Laser | |
| Laser module: Red (R) 100 mW 650nm Green (G) 30 mW 532nm Light effect LED type: 6 x 2 W SMD 8072 R/G/B Flash rate: 0 - 30 Hz Spotlight LED type: 6 x 6 W SMD 8072 3in1 TCL RGB (homogenous color mix) Beam angle: 13° Beam angle (1/2 peak): 13° Beam angle (1/10 peak): 20° Bar 4 x 2 W SMD 8072 2in1 BCL CW/UV (homogenous color mix) | Laser class: | 2M |
| Green (G) 30 mW 532nm Light effect LED type: 6 x 2 W SMD 8072 R/G/B Flash rate: 0 - 30 Hz Spotlight LED type: 6 x 6 W SMD 8072 3in1 TCL RGB (homogenous color mix) Beam angle: 13° Beam angle (1/2 peak): 13° Beam angle (1/10 peak): 20° Bar 4 x 2 W SMD 8072 2in1 BCL CW/UV (homogenous color mix) | Laser color: | R/G |
| LED type: 6 x 2 W SMD 8072 R/G/B Flash rate: 0 - 30 Hz Spotlight 6 x 6 W SMD 8072 3in1 TCL RGB (homogenous color mix) Beam angle: 13° Beam angle (1/2 peak): 13° Beam angle (1/10 peak): 20° Bar 4 x 2 W SMD 8072 2in1 BCL CW/UV (homogenous color mix) | Laser module: | |
| Flash rate: 0 - 30 Hz Spotlight LED type: 6 x 6 W SMD 8072 3in1 TCL RGB (homogenous color mix) Beam angle: 13° Beam angle (1/2 peak): 13° Beam angle (1/10 peak): 20° Bar LED type: 4 x 2 W SMD 8072 2in1 BCL CW/UV (homogenous color mix) | Light effect | |
| Spotlight LED type: 6 x 6 W SMD 8072 3in1 TCL RGB (homogenous color mix) Beam angle: 13° Beam angle (1/2 peak): 13° Beam angle (1/10 peak): 20° Bar LED type: 4 x 2 W SMD 8072 2in1 BCL CW/UV (homogenous color mix) | LED type: | 6 x 2 W SMD 8072 R/G/B |
| LED type: 6 x 6 W SMD 8072 3in1 TCL RGB (homogenous color mix) Beam angle: 13° Beam angle (1/2 peak): 13° Beam angle (1/10 peak): 20° Bar 4 x 2 W SMD 8072 2in1 BCL CW/UV (homogenous color mix) | Flash rate: | 0 - 30 Hz |
| color mix) Beam angle: 13° Beam angle (1/2 peak): 13° Beam angle (1/10 peak): 20° Bar 4 x 2 W SMD 8072 2in1 BCL CW/UV (homogenous color mix) | Spotlight | |
| Beam angle (1/2 peak): 13° Beam angle (1/10 peak): 20° Bar LED type: 4 x 2 W SMD 8072 2in1 BCL CW/UV (homogenous color mix) | LED type: | , · · · |
| Beam angle (1/10 peak): 20° Bar LED type: 4 x 2 W SMD 8072 2in1 BCL CW/UV (homogenous color mix) | Beam angle: | 13° |
| Bar LED type: 4 x 2 W SMD 8072 2in1 BCL CW/UV (homogenous color mix) | Beam angle (1/2 peak): | 13° |
| LED type: 4 x 2 W SMD 8072 2in1 BCL CW/UV (homogenous color mix) | Beam angle (1/10 peak): | 20° |
| (homogenous color mix) | Bar | |
| Flash rate: 0 - 30 Hz | LED type: | |
| | Flash rate: | 0 - 30 Hz |

EUROLITE EASY Show

| Power supply: | 100-240 V AC, 50/60 Hz |
|--------------------------|------------------------------------------------------------------------------|
| | 5V DC 250 mA |
| Power consumption: | 1,25 W |
| IP classification: | IP20 |
| Power connection: | Mains input via USB C (W) mounting version power supply cord with AC adapter |
| Programs: | Preprogrammed 24 scenes/chases and 12 cues |
| DMX input: | 3-pin XLR (M) mounting version |
| DMX output: | 3-pin XLR (F) mounting version |
| Control: | DMX; sound to light via microphone; QuickDMX via USB (optional) |
| Housing color: | Black |
| Display type: | Monochrome LCD display |
| Available storage media: | USB devices |
| Housing design: | Desktop console housing |
| Dimensions: | Width: 28,0 cm |
| | Depth: 14,5 cm |
| | Height: 6,0 cm |
| Weight: | 1,35 kg |
| Noise classification: | Class 0 (no noise at all) |

OMNITRONIC M-4 Speaker-System Stand

| Maximum carrying capacity: | 18 kg |
|----------------------------|-------------------------------------------------------------------------|
| Tube diameter sector: | 38 - 35 mm |
| Height: | Maximum: 345 cm Minimum: 140 cm Adjustable in 10 steps with locking pin |
| Attachment system: | Ø 35mm |
| Type (general stands): | Speaker stand/manual |
| Material: | Aluminum |
| Color: | Black |
| Transport dimensions: | 140 cm x 13,5 cm |
| Weight: | 3,30 kg |