



List price: 1093.61 €

incl. 19% VAT.

Features:

EUROLITE LED THA-20PC TRC Theater-Spot bk

Fanless PC spot with 17 W white light LED, color rendering index (CRI) >90

- New LED technology that simulates the color temperature curve of a halogen lamp when dimming
- Two additional frost filters provide a soft, homogeneous light
- 1 powerful LED 17 W COB (chip-on-board) Dim to warm (homogenous color mix)
- The device is cooled by passive convection cooling
- Control via stand-alone
- Flicker-free
- With a beam angle of 17°
- Very high color rendering index (CRI)
- With Mounting bracket
- Silent operation
- For application areas such as: Trade fair and shop fitting; Wedding/gala/events; video and photography; mobile use
- Dimmer electronic
- Rubber feet
- Application possibility: Suspended; on stand

Package contents

- 1 x spotlight, 1 x barndoor, 1 x filter frame, 2 x diffusor cover, 1 x ring, 2 x lamp clamping ring, 1 x user manual

Logistic

EAN / GTIN: 4026397694116

Weight: 20,20 kg

Length: 1.20 m

Width: 0.80 m

Height: 0.35 m

Bulky product

ROADINGER Flightcase 4x THA-20PC

- 6,5 mm,
- Branded hardware
- Made in Europe
- For further information about this product, please refer to the Data Sheet under "Downloads"

Technical specifications:

Weight: 17,02 kg

EUROLITE LED THA-20PC TRC Theater-Spot bk

Power supply:	100-240 V AC, 50/60 Hz
Power consumption:	22 W
IP classification:	IP20
Protection class:	Protection class I
Power connection:	Fixed power supply cord with safety plug
Fuse:	5 x 20 mm, T 1 A Fuse replaceable
LED:	1 x 17 W COB (chip-on-board) Dim to warm (homogenous color mix)
Color temperature:	3000K
Cooling:	Passive convection cooling
Control:	Stand-alone
Projection:	Flicker-free
Beam angle:	17°
Beam angle (1/2 peak):	17° Frost filter 19° Frost filter 26°
Beam angle (1/10 peak):	36° Frost filter 40° Frost filter 53°
Color rendering index (CRI):	92 Ra
Illuminance in Lux (lx):	Warm white (WW) 3m: 727 lx, 6m: 188 lx
Housing color:	Black
Attachment system:	Mounting bracket
Transport aid:	Rubber feet
Material:	Aluminum casting
Slot for spot length:	10 cm x 10 cm
Dimensions:	Length: 21,5 cm Width: 14,5 cm Depth: 21 cm
Weight:	2,23 kg
Noise classification:	Class 0 (no noise at all)
Power cord	
Cable construction:	3 x 0,75 mm ² H05VV-F
Cable length:	Approx. 1 m

Mounting bracket

Diameter mounting holes: 1 x Ø10mm

Material: Metal, 3 mm

Diffusor cover

Material: Plastic

Color: Frost

Dimensions: Width: 2 mm
Diameter: Ø 8 cm

Ring

Material: Aluminum, 1 mm

Color: Gold

Dimensions: Depth: 1,3 cm
Diameter: Ø 8,2 cm

Barndoor

Material: Aluminum, 1 mm; metal

Ring diameter: Outside: 99 mm
Inside: 80 mm

Filter frame

Diameter mounting holes: 1 x Ø4mm

Material: Aluminum, 0,8 mm

Color: Black

Dimensions: Width: 9,9 cm
Height: 9,9 cm
Diameter: Ø 8 cm

Lamp clamping ring

Material: Metal, 2 mm

Color: Black

Legal specifications

Special product: Not designed for household room illumination

Intended use: Show effect lighting

ROADINGER Flightcase 4x THA-20PC

Maximum load: 50 kg

Use of brands: Branded hardware

Device compartment: 16 cm x 19 cm x 13,5 cm

Inside dimensions: 42,5 cm x 43 cm x 18 cm

Accessory compartment: 10,5 cm x 43 cm x 18 cm

Material thickness: 6,5 mm

Dimensions: Width: 51 cm
Depth: 46 cm
Height: 27 cm

Weight: 8,10 kg
