



Features:

EUROLITE LED THA-20PC TRC Theater Spot bk

Fanless PC spot with 17 W white light LED, color rendering index (CRI) >90

- New LED technology that simulates the color temperature curve of a halogen lamp when dimming
- Two additional frost filters provide a soft, homogeneous light
- 1 LED 17 W COB (chip-on-board) Dim to warm (homogenous color mix)
- Dimmer electronic
- The device is cooled by passive convection cooling
- Control via stand-alone
- Flicker-free
- With a beam angle of 17°
- Very high color rendering index (CRI)
- With mounting bracket
- Rubber feet
- For application areas such as: Decoration; Trade fair and shop fitting; wedding/gala/events; video and photography; advertisement/Shop window; restaurants, bars and hotels
- Silent operation
- Application possibility: Suspended; on stand

Logistic

EAN / GTIN: 4026397694116

Weight: 20,20 kg

Length: 1.20 m

Width: 0.80 m

Height: 0.35 m

Bulky product

ROADINGER Flightcase 4x THA-20PC

- 6.5 mm,
- Branded hardware
- Made in Europe

- For further information about this product, please refer to the Data Sheet under "Downloads"

Technical specifications:

Weight: 17.02 kg

EUROLITE LED THA-20PC TRC Theater Spot bk

Power supply:	100-240 V AC, 50/60 Hz
Power consumption:	22 W
IP classification:	IP20
Protection class:	Protection class I
Power connection:	Fixed power supply cord with safety plug
Fuse:	5 x 20 mm, T 1 A fuse replaceable
Lamp type:	LED lamp
LED type:	1 x 17 W COB (chip-on-board) Dim to warm (homogenous color mix)
Cooling:	Passive convection cooling
Control:	Stand-alone
Projection:	Flicker-free
Beam angle:	17°
Beam angle (1/2 peak):	17° Frost filter 19° Frost filter 26°
Beam angle (1/10 peak):	36° Frost filter 40° Frost filter 53°
Color temperature:	3000K
Color rendering index (CRI):	92 Ra
Illuminance in Lux (lx):	Warm white (WW) 3m: 727 lx, 6m: 188 lx
Housing color:	Black
Attachment system:	Mounting bracket
Transport aid:	Rubber feet
Material:	Aluminum casting
Slot for spot length:	10 cm x 10 cm
Dimensions:	Length: 21.5 cm Width: 14.5 cm Depth: 21 cm
Weight:	2.23 kg
Noise classification:	Class 0 (no noise at all)
Diameter mounting holes:	1 x Ø10mm
Material:	Metal, 3 mm
Cable construction:	3 x 0.75 mm ² H05VV-F
Cable length:	Approx. 1 m

Material:	Aluminum, 1 mm; metal
Ring diameter:	Outside: 99 mm Inside: 80 mm
Diameter mounting holes:	1 x Ø4mm
Material:	Aluminum, 0.8 mm
Color:	Black
Dimensions:	Width: 9.9 cm Height: 9.9 cm Diameter: Ø 8 cm
Material:	Plastic
Color:	Semi-transparent
Dimensions:	Width: 0.2 cm Diameter: Ø 8 cm
Material:	Aluminum, 1 mm
Color:	Gold
Dimensions:	Depth: 1.3 cm Diameter: Ø 8.2 cm
Material:	Metal, 2 mm
Color:	Black
Special product:	Not designed for household room illumination
Intended use:	Show effect lighting

ROADINGER Flightcase 4x THA-20PC

Maximum load:	50 kg
Use of brands:	Branded hardware
Device compartment:	16 cm x 19 cm x 13.5 cm
Inside dimensions:	42.5 cm x 43 cm x 18 cm
Accessory compartment:	10.5 cm x 43 cm x 18 cm
Material thickness:	6.5 mm
Dimensions:	Width: 51 cm Depth: 46 cm Height: 27 cm
Weight:	8.10 kg

Scope of delivery:

1 x spotlight
 1 x barndoor
 1 x filter frame
 2 x frost filter
 1 x ring
 2 x lamp clamping ring
 1 x user manual