

EUROLITE Set 8x LED IP PAR 7x9W SCL Spot + Case with wheels

Art. No.: 20000883

GTIN: 4026397694895







List price: 3152.31 €

incl. 19% VAT.

Features:

EUROLITE LED IP PAR 7x9W SCL Spot

Weather-proof (IP65) spotlight with 7 x 9 W LED and 7in1 SCL RGB/CW/WW/A/UV color mixing

- 7 powerful LEDs 9 W high-power 7in1 SCL RGB/CW/WW/A/UV (homogenous color mix)
- Color blend stepless; color change adjustable; color fade adjustable; Dimmer electronic
- Strobe effect
- Direct color selection for 28 preset colors
- The device is cooled by passive convection cooling
- Control via DMX; stand-alone; IR remote control
- Preprogrammed in LED PC-Control 512; EASY SHOW 1; Light Captain; EASY SHOW 2; EASY SHOW 3
- Flicker-free
- With a beam angle of 15°
- With double bracket
- LCD display
- Mains input and output for power linking up to 8 units
- Suitable for outdoor use IP65
- For application areas such as: Installation; stage; rental; architecture
- Silent operation
- Application possibility: Standing; suspended; on stand

Package contents

1 x spotlight, 1 x power cord, 1 x remote control, 1 x battery, 1 x user manual

ROADINGER Flightcase 8x LED IP PAR 7x8W QCL/7x9W SCL with wheels

Trunk case with castors, PRO version

Logistic

EAN / GTIN: 4026397694895

Weight: 65,00 kg Length: 1.20 m Width: 0.80 m Heigth: 0.75 m Bulky product

- With 8 device compartments
- With 1 accessory compartment
- High-quality workmanship with birch multiplex 6,50 mm, black, laminated
- Interior with foam padding
- Aluminum profile frames 25mm with rounded edges
- 4 hinged, chromium plated case handles
- 3 chrome tip-over locks
- 2 high-quality butterfly locks
- 4 x castors with 2 locking brakes
- 4 x built-in stacking trays in the cover
- Branded hardware
- Made in Europe
- For further information about this product, please refer to the Data Sheet under "Downloads"

Technical specifications:

Weight: 58,96 kg

EUROLITE LED IP PAR 7x9W SCL Spot

Power supply:	100-240 V AC, 50/60 Hz
Power consumption:	55 W
IP classification:	IP65
Power connection:	Mains input via IP T-Con (M) mounting version power supply cord with safety plug
Power output:	IP T-Con (F) mounting version
Lamp type:	LED lamp
LED type:	7 x 9 W high-power 7in1 SCL RGB/CW/WW/A/UV (homogenous color mix)
Flash rate:	0 - 20 Hz
DMX channels:	3; 5; 7; 9; 13
DMX input:	1 x 3-pin XLR (M) mounting version IP
DMX output:	1 x 3-pin XLR (F) mounting version IP
Cooling:	Passive convection cooling
Control:	DMX; stand-alone; IR remote control
Preprogrammed in:	LED PC-Control 512; EASY SHOW 1; Light Captain; EASY SHOW 2; EASY SHOW 3
Projection:	Flicker-free
Beam angle:	15°
Beam angle (1/2 peak):	15°
Housing color:	Black matte
Attachment system:	Double bracket
Display type:	LCD display
Material:	Aluminum casting
Dimensions:	Width: 25,5 cm Depth: 15,3 cm Height: 28,1 cm
Weight:	4,07 kg

Noise classification:	Class 0 (no noise at all)
Photobiological safety:	Risk Group 0
Mounting bracket	
Diameter mounting holes:	3 x Ø11mm
Material:	Metal, 2,5 mm
Power cord	
Cable construction:	3 x 1,0 mm ² H05RN-F
Cable length:	Approx. 1,2 m
Remote control	
Battery:	1 x button cell 3.0 V CR2025 lithium manganese built-in
Legal specifications	
Special product:	Not designed for household room illumination
Intended use:	Show effect lighting

ROADINGER Flightcase 8x LED IP PAR 7x8W QCL/7x9W SCL with wheels

Maximum load:	100 kg
Aluminum profile frames:	25 mm
Case handle:	4 pc/pcs
Stop hinge:	3 pc/pcs
Lock:	Butterfly lock: 2 pc/pcs
Transport aid:	4 x castors with 2 locking brakes 4 x built-in stacking trays in the cover
Use of brands:	Branded hardware
Material:	Birch multiplex, 6,50 mm, laminated
Color:	Black, laminated
Device compartment:	22,5 cm x 24 cm x 30 cm
Accessory compartment:	101 cm x 10,5 cm x 28 cm
Dimensions:	Length: 105 cm
	Depth: 63 cm
	Height: 51 cm
Weight:	26,40 kg