



The article is no longer in our assortment.

Features:

OMNITRONIC PAS-181A MK3 Subwoofer, active, DSP

Active 18" PA bassreflex subwoofer, 850 W RMS

- Active PA subwoofer for touring applications and permanent installations
- 46 cm (18") bass speaker with 100 mm voice coil
- DSP-controlled class D amplifier with 850 watts power
- XLR outputs with switchable high-pass filter, 120 Hz
- Digital signal processor
- 2 Rugged carrying handles
- Wheels optional
- Black metal grille with acoustic foam
- DSP presets: FLAT; DJ; LIVE
- For application areas such as: Clubs/dancing school; Installation; mobile use; mobile djs / entertainer; restaurants, bars and hotels; Rental

Package contents

- 1 x user manual, 1 x power cord, 1 x bass

Logistic

EAN / GTIN: 4026397699845

Weight: 180,00 kg

Length: 0.00 m

Width: 0.00 m

Height: 0.00 m

Bulky product

OMNITRONIC PAS-212A MK3 2-Way Top, active, DSP

Active 12" PA speaker with DSP presets, 2 input channels, 450 W RMS

- Active PA speaker system for touring applications and permanent installations
- 2-way bass-reflex enclosure with 30 cm woofer and 2.5 cm compression driver
- DSP-controlled class D amplifier with 450 watts power
- Switchable low cut (120 Hz, 90 Hz)
- 1 adjustable line input via XLR/6.3mm combo jack and RCA
- 1 adjustable mic/line input via XLR/6.3mm combo jack

- XLR output for linking further active speaker systems, switchable CH 1/CH 2
- Optimized for combination with PAS subwoofers
- Digital signal processor
- 2 Rugged carrying handles
- With rigging points
- Black metal grille with acoustic foam
- Application possibility: Standing; suspended; monitoring; on stand
- DSP presets: FLAT; DJ; MONITOR
- Dual flange

Package contents

- 1 x compact cabinet speaker, 1 x user manual, 1 x power cord

OMNITRONIC Distance Tube Subwoofer/Satellite with Crank

Variable distance tube, M20 thread, height adjustable 80-110 cm, max. load 35 kg

- Connecting tube for satellite systems
- Powder-coated steel version
- Adjustable height
- M20 thread

Package contents

- 1 x distance tube, 1 x user manual

PSSO XLR cable 3pin 10m bk Neutrik

Reliable microphone cable

- High quality connection for microphones etc.
- High conductivity
- Slim and short construction
- Built with NEUTRIK connector
- Made in Germany

Package contents

- 1 x xLR cable

PSSO XLR cable 3pin 3m bk Neutrik

Reliable microphone cable

- High quality connection for microphones etc.
- High conductivity
- Slim and short construction
- Made in Germany

Plug (male)

- Built with NEUTRIK connector

Package contents

- 1 x xLR cable

Technical specifications:

Weight: 143,72 kg

OMNITRONIC PAS-181A MK3 Subwoofer, active, DSP

Power supply: 230 V AC, 50 Hz

Power consumption: 1000 W

Power connection: Mains input via IEC connector (M) mounting version power supply cord with safety plug (provided)

Power: Rated: 850W RMS

| | |
|-----------------------|--|
| Frequency range: | 38 - 200 Hz |
| Max. SPL: | 127 dB |
| DSP: | Digital signal processor |
| DSP presets: | FLAT; DJ; LIVE |
| Attachment system: | Flange: M20 thread |
| Circuitry: | Class D |
| Control elements: | Phase reversal switch |
| Controls: | Power on/off transient; limiter |
| Status LED: | Limit, power, signal, DSP presets |
| Connections: | Input: 2 x 3-pin XLR Output: 2 x 3-pin XLR |
| Input channels: | Stereo via XLR, channel control via Rotary dial |
| Speaker: | 1 x woofer 18" with ferrit magnet Basket material: aluminum Voice coil lows 4" |
| Type of speaker: | Subwoofer |
| Type of construction: | Vented |
| Carrying handle: | 2 pc/pcs |
| Transport aid: | Wheels optional |
| Material: | Birch multiplex |
| Color: | Black, textured coating, painted |
| Dimensions: | Width: 54 cm Depth: 68 cm Height: 63 cm |
| Weight: | 46,00 kg |

OMNITRONIC PAS-212A MK3 2-Way Top, active, DSP

| | |
|--------------------|--|
| Power supply: | 230 V AC, 50 Hz |
| Power consumption: | 500 W |
| Output power: | 450 W RMS |
| Power connection: | Mains input via IEC connector (M) mounting version power supply cord with safety plug (provided) |
| Frequency range: | 60 - 20000 Hz |
| Max. SPL: | 125 dB |
| DSP: | Digital signal processor |
| DSP presets: | FLAT; DJ; MONITOR |
| Dispersion angle: | 90° x 60° |
| Attachment system: | Dual flange: Ø 35mm (0°/5°) |
| Flying points: | 4 x M10 thread; 6 x M8 thread |
| Circuitry: | Class D |
| Controls: | Power on/off transient; limiter |
| Status LED: | Limit, power, signal, DSP presets |
| Connections: | Input: 2 x 3-pin XLR/6.35mm jack (F) combination socket (mounting version) |

| | |
|------------------|---|
| | Input: 1 x stereo RCA Link: 3-pin XLR |
| Input channels: | 1 x mono via XLR or RCA, channel control via Rotary dial 1 x mono with Mic-line switch via XLR, channel control via Rotary dial |
| Speaker: | 1 x compression tweeter highs 1" with ferrit magnet Basket material: aluminum Voice coil compression tweeter highs 1,5" Horn vent 1" 1 x woofer 12" Voice coil lows 3" |
| Type of speaker: | Compact cabinet speaker |
| Carrying handle: | 2 pc/pcs |
| Material: | Birch multiplex |
| Color: | Black, textured coating, painted |
| Dimensions: | Width: 39 cm Depth: 61,5 cm Height: 38 cm |
| Weight: | 22,30 kg |

OMNITRONIC Distance Tube Subwoofer/Satellite with Crank

| | |
|----------------------------|-----------------------------------|
| Maximum carrying capacity: | 35 kg |
| Height: | Maximum: 110 cm Minimum: 80 cm |
| Attachment system: | Ø 35mm |
| Type (general stands): | Distance tube |
| Color: | Black |
| Thread: | M20 thread |
| Weight: | 2,80 kg |

PSSO XLR cable 3pin 10m bk Neutrik

| | |
|---------------------|--------------------------------------|
| Pin configuration: | Pin 1 (GND) / Pin 2 (+) / Pin 3 (-) |
| Cable construction: | 3 x 0,22 mm ² Audio cable |
| Cable length: | 10 m |
| Plug A: | 1 x 3-pin XLR (M) |
| Plug B: | 1 x 3-pin XLR (F) |
| Use of brands: | Built with NEUTRIK connector |
| Color: | Black |
| Weight: | 540 g |

PSSO XLR cable 3pin 3m bk Neutrik

| | |
|---------------------|--------------------------------------|
| Cable construction: | 2 x 0,22 mm ² Audio cable |
|---------------------|--------------------------------------|

| | |
|----------------|------------------------------|
| Cable length: | 3 m |
| Plug A: | 1 x 3-pin XLR (M) |
| Plug B: | 1 x 3-pin XLR (F) |
| Color: | Black |
| Weight: | 230 g |
| Plug (male) | |
| Use of brands: | Built with NEUTRIK connector |
| Material: | Metal |