



**List price: 1605.31 €**

incl. 19% VAT.

### Features:

- Positioning within PAN and TILT
- <p>EUROLITE LED TSL-1000 Scan MK2
- <p class="featureSatz">Scanner with 100 W LED, rotating gobos, 3-facet prism, color wheel and motorized focus
- Note: The macro programs of the predecessor model (no. 51786122) are not identical, therefore no synchronous master/slave operation is possible between these devices.
- 1 powerful LED 100 W COB (chip-on-board) cold white (CW)
- Positioning within 160° PAN and 50° TILT
- Exact positioning (16 bit resolution)
- Focus motor-driven; color wheel; gobo wheel with rotating gobos; Prism 3-fold
- Gobo effect; Strobe effect
- Color wheel with 8 dichroic filters plus open<BR>half colors selectable, Rainbow effect with adjustable speed in both directions
- Gobo wheel with rotating gobos, 7 gobos and open<BR>shake effect
- Gobos changeable
- Slot-in gobo system for easy gobo replacement
- Integrated show programs
- The device is cooled by cooling fan
- Control via stand-alone; DMX; Master/slave function; Sound to light via Microphone
- Flicker-free
- With a beam angle of 20°
- OLED display
- Dimmer electronic
- Preprogrammed in Light´J; Light Captain; EASY SHOW 2; EASY SHOW 3
- Rubber feet
- Mains input and output for power linking up to 8 units

### Logistic

EAN / GTIN: 4026397705683

Weight: 25,00 kg

Length: 0.00 m

Width: 0.00 m

Height: 0.00 m

- For application areas such as: Clubs/dancing school; Wedding/gala/events; mobile djs / entertainer; Rental
  - Application possibility: Standing; suspended; on stand
- Package contents**
- 1 x light effect, 1 x user manual, 1 x power cord, 1 x safety eyelet
  - <p>ROADINGER Flightcase 2x LED TSL-1000 with trolley function
  - <p class="featureSatz">Trolley case, PRO version
  - High-quality workmanship with birch multiplex 6,5 mm,
  - Interior with foam padding
  - Aluminum profile frames 25mm with rounded edges
  - 3 hinged, chromium plated case handles
  - 2 chrome tip-over locks
  - 2 high-quality butterfly locks
  - Trolley
  - Branded hardware
  - Made in Europe
  - For further information about this product, please refer to the Data Sheet under "Downloads"

## Technical specifications:

---

Weight: 21,60 kg

---

### EUROLITE LED TSL-1000 Scan MK2

Power supply:	100-240 V AC, 50/60 Hz
Power consumption:	110 W
IP classification:	IP20
Protection class:	Protection class I
Power connection:	Mains input via P-Con (blue), mounting version power supply cord with safety plug (provided)
Power output:	P-Con (gray), mounting version
Fuse:	5 x 20 mm, T 4 A Fuse replaceable
Lamp type:	LED lamp
LED:	1 x 100 W COB (chip-on-board) cold white (CW)
Color temperature:	8000K
Max. TILT movement:	50° Exact positioning (16 bit resolution)
Max. PAN movement:	160° Exact positioning (16 bit resolution)
Flash rate:	1 - 25 Hz
Equipment:	Focus motor-driven; color wheel; gobo wheel with rotating gobos; Prism 3-fold
Color generation:	Color wheel with 8 dichroic filters plus open Half colors selectable, Rainbow effect with adjustable speed in both directions
Gobos:	Gobo wheel with rotating gobos, 7 gobos and open Shake effect Gobos changeable Slot-in gobo system for easy gobo replacement
DMX channels:	10; 15
DMX input:	3-pin XLR (M) mounting version

DMX output:	3-pin XLR (F) mounting version
Cooling:	Cooling fan
Control:	Stand-alone; DMX; Master/slave function; Sound to light via Microphone
Preprogrammed in:	Light J; Light Captain; EASY SHOW 2; EASY SHOW 3
Projection:	Flicker-free
Beam angle:	20°
Beam angle (1/2 peak):	20°
Illuminance in Lux (lx):	Cold white (CW) 1m: 35679 lx, 3m: 4265 lx, 6m: 1055 lx
Housing color:	Black
Display type:	OLED display
Transport aid:	Rubber feet
Dimensions:	Width: 25,1 cm Depth: 14,1 cm Height: 37,7 cm
Weight:	5,75 kg
Noise classification:	Class 2 (slight noise)
Legal specifications	
Special product:	Not designed for household room illumination
Intended use:	Show effect lighting

#### **ROADINGER Flightcase 2x LED TSL-1000 with trolley function**

Maximum load:	25 kg
Aluminum profile frames:	25 mm
Case handle:	3 pc/pcs
Stop hinge:	2 pc/pcs
Lock:	Butterfly lock: 2 pc/pcs
Transport aid:	Trolley
Use of brands:	Branded hardware
Material:	Birch multiplex, 6,5 mm
Accessory compartment:	44 cm x 7 cm x 13 cm
Device compartment:	36 cm x 25,5 cm x 13 cm
Inside dimensions:	86,5 cm x 32,5 cm x 13 cm
Weight:	10,10 kg