



**List price: 1248.31 €**

incl. 19% VAT.

### Features:

#### EUROLITE AKKU UP-4 Entry QCL Spot

Battery-powered upright with 4 x 8 watt 4in1 LED and IR remote control

- Sturdy housing with handle and folding foot for angled placement
- Battery operation up to 14h depending on program used
- 4 powerful LEDs 8 W high-power 4in1 QCL RGBW (homogenous color mix)
- Color blend stepless; color change adjustable; color fade adjustable; Dimmer electronic; Energy-saving mode
- Strobe effect
- Integrated show programs
- Direct color selection for 17 preset colors
- The device is cooled by passive convection cooling
- Control via stand-alone; IR remote control; DMX; Master/slave function; Sound to light via Microphone; QuickDMX via USB (optional); W-DMX by wireless solution via USB (optional); CRMX by LumenRadio via USB (optional)
- Flicker-free
- With a beam angle of 17°
- 4 digit 7-segment LED display
- Preprogrammed in Light Captain; EASY SHOW 1; EASY SHOW 2; EASY SHOW 3; Light J
- Mains input and output for power linking up to 8 units
- Application possibility: Standing
- Cordless, flexible and versatile
- Integrated automatic charging of the battery and status indicator
- For application areas such as: Wedding/gala/events; mobile use; mobile djs / entertainer; small rental
- Silent operation

#### Package contents

### Logistic

EAN / GTIN: 4026397710885

Weight: 22,00 kg

Length: 0.00 m

Width: 0.00 m

Height: 0.00 m

- 1 x spotlight, 1 x user manual, 1 x power cord, 1 x remote control, 1 x battery

### ROADINGER Flightcase 4x AKKU UP-4 Entry/IP UP-4 Entry

Trunk case, PRO version

- High-quality workmanship with birch multiplex 6 mm, dark brown
- Interior with foam padding<BR>cover with foam padding
- Aluminum profile frames 22mm with rounded edges
- 2 hinged, chromium plated case handles
- 2 chrome tip-over locks
- 1 high-quality butterfly lock
- Branded hardware
- Made in Europe
- For further information about this product, please refer to the Data Sheet under "Downloads"

#### Package contents

- 1 x case

### Technical specifications:

---

|         |          |
|---------|----------|
| Weight: | 19,15 kg |
|---------|----------|

---

### EUROLITE AKKU UP-4 Entry QCL Spot

|                    |  |
|--------------------|--|
| Power supply:      | 100-240 V AC, 50/60 Hz   |
| IP classification: | IP20   |
| Protection class:  | Protection class I   |
| Power connection:  | Mains input via IEC connector (M) mounting version power supply cord with safety plug (provided)   |
| Power output:      | IEC connector (F) mounting version   |
| Fuse:              | T 1 A Fuse replaceable   |
| Battery pack type: | 1 x lithium ion 11,1 V, 4400 mAh, 48,84 Wh   |
| Battery pack:      | Battery operation up to 14h depending on program used<br>Recharging time 4h  |
| Lamp type:         | LED lamp   |
| LED:               | 4 x 8 W high-power 4in1 QCL RGBW (homogenous color mix)  |
| Flash rate:        | 0 - 20 Hz  |
| DMX channels:      | 3; 4-1; 4; 6; 8  |
| DMX input:         | 3-pin XLR (M) mounting version   |
| DMX output:        | 3-pin XLR (F) mounting version   |
| Cooling:           | Passive convection cooling   |
| Control:           | Stand-alone; IR remote control; DMX; Master/slave function; Sound to light via Microphone; QuickDMX via USB (optional); W-DMX by wireless solution via USB (optional); CRMX by LumenRadio via USB (optional) |
| Preprogrammed in:  | Light Captain; EASY SHOW 1; EASY SHOW 2; EASY SHOW 3; Light J  |
| Projection:        | Flicker-free   |

|                         |   |
|-------------------------|---|
| Beam angle:             | 17°   |
| Beam angle (1/2 peak):  | 17°   |
| Beam angle (1/10 peak): | 34°   |
| Housing color:          | Black   |
| Attachment system:      | M10 thread  |
| Display type:           | 4 digit 7-segment LED display                           |
| Dimensions:             | Width: 14,4 cm<br>Depth: 14,4 cm<br>Height: 19,1 cm     |
| Weight:                 | 2,35 kg   |
| Noise classification:   | Class 0 (no noise at all)                               |
| Remote control          |   |
| Battery:                | 1 x Button cell 3.0 V CR2025 lithium manganese built-in |
| Legal specifications    |   |
| Special product:        | Not designed for household room illumination            |
| Intended use:           | Show effect lighting                                    |

#### **ROADINGER Flightcase 4x AKKU UP-4 Entry/IP UP-4 Entry**

|                          |   |
|--------------------------|---|
| Maximum load:            | 50 kg   |
| Aluminum profile frames: | 22 mm   |
| Case handle:             | 2 pc/pcs                                      |
| Stop hinge:              | 2 pc/pcs                                      |
| Lock:                    | Butterfly lock: 1 pc/pcs                      |
| Use of brands:           | Branded hardware                              |
| Material:                | Birch multiplex, 6 mm, laminated              |
| Color:                   | Dark brown                                    |
| Device compartment:      | 18 cm x 18,5 cm x 23 cm                       |
| Accessory compartment:   | 10 cm x 40 cm x 24 cm                         |
| Dimensions:              | Width: 52 cm<br>Depth: 43 cm<br>Height: 30 cm |
| Weight:                  | 9,75 kg                                       |