

EUROLITE Set 4x AKKU UP-4 Entry QCL Spot + Case

Art. No.: 20000934

GTIN: 4026397710885



Features:

EUROLITE AKKU UP-4 Entry QCL Spot

Battery-powered uplight with 4 x 8 W 4in1 LED and IR remote control

- Sturdy housing with handle and folding foot for angled placement
- Cordless, flexible and versatile
- Battery operation up to 14h depending on program used
- Integrated automatic charging of the battery and status indicator
- 4 LEDs 8 W SMD 9080 4in1 QCL RGBW (homogenous color mix)
- Color blend stepless; color change adjustable; color fade adjustable; Dimmer electronic; Energy-saving mode
- Strobe effect
- Integrated show programs
- Direct color selection for 17 preset colors
- The device is cooled by passive convection cooling
- Control via stand-alone; IR remote control; DMX; master/slave function; sound to light via microphone; QuickDMX via USB (optional); W-DMX by wireless solution via USB (optional); CRMX by LumenRadio via USB (optional)
- Fixtures available for Light Captain; EASY SHOW 1; EASY SHOW 2; EASY SHOW 3; Light´J; Colorchief
- Flicker-free
- With a beam angle of 17°
- 4 digit 7-segment LED display
- Mains input and output for power linking up to 8 units
- For application areas such as: Decoration; wedding/gala/events; mobile djs / entertainer; restaurants, bars and hotels; rental; advertisement/Shop window
- Silent operation
- Application possibility: Standing

Logistic

EAN / GTIN: 4026397710885

Weight: 22,00 kg

Length: 0.00 m

Width: 0.00 m

Height: 0.00 m

ROADINGER Flightcase 4x AKKU UP-4 Entry/IP UP-4 Entry

Trunk case, PRO version

- High-quality workmanship with birch multiplex 6 mm, dark brown
- Interior with foam padding
cover with foam padding
- Aluminum profile frames 22mm with rounded edges
- 2 hinged, chromium plated case handles
- 2 chrome tip-over locks
- 1 high-quality butterfly lock
- Branded hardware
- Made in Europe
- For further information about this product, please refer to the Data Sheet under "Downloads"

Technical specifications:

Weight:	18.10 kg
---------	----------

EUROLITE AKKU UP-4 Entry QCL Spot

Power supply:	100-240 V AC, 50/60 Hz
IP classification:	IP20
Protection class:	Protection class I
Power connection:	Mains input via IEC connector (M) mounting version power supply cord with safety plug (provided)
Power output:	IEC connector (F) mounting version
Fuse:	T 1 A fuse replaceable
Battery pack type:	1 x lithium ion 11.1 V, 4400 mAh, 48.84 Wh
Battery pack:	Battery operation up to 14h depending on program used Recharging time 4h
Lamp type:	LED lamp
LED type:	4 x 8 W SMD 9080 4in1 QCL RGBW (homogenous color mix)
Flash rate:	0.5 - 24 Hz
DMX channels:	3; 4-1; 4; 6; 8
DMX input:	3-pin XLR (M) mounting version
DMX output:	3-pin XLR (F) mounting version
Cooling:	Passive convection cooling
Control:	Stand-alone; IR remote control; DMX; master/slave function; sound to light via microphone; QuickDMX via USB (optional); W-DMX by wireless solution via USB (optional); CRMX by LumenRadio via USB (optional)
Fixtures available for:	Light Captain; EASY SHOW 1; EASY SHOW 2; EASY SHOW 3; Light J; Colorchief
Projection:	Flicker-free
PWM frequency:	2900 Hz
Beam angle:	17°

Beam angle (1/2 peak):	17°
Beam angle (1/10 peak):	34°
Housing color:	Black
Attachment system:	M10 thread
Display type:	4 digit 7-segment LED display
Dimensions:	Width: 14.4 cm Depth: 14.4 cm Height: 19.1 cm
Weight:	2.35 kg
Noise classification:	Class 0 (no noise at all)
Battery:	1 x button cell 3.0 V CR2025 lithium manganese built-in
Special product:	Not designed for household room illumination
Intended use:	Show effect lighting

ROADINGER Flightcase 4x AKKU UP-4 Entry/IP UP-4 Entry

Maximum load:	50 kg
Aluminum profile frames:	22 mm
Case handle:	2 pc/pcs
Stop hinge:	2 pc/pcs
Lock:	Butterfly lock: 1 pc/pcs
Use of brands:	Branded hardware
Material:	Birch multiplex, 6 mm, laminated
Color:	Dark brown
Device compartment:	18 cm x 18.5 cm x 23 cm
Accessory compartment:	10 cm x 40 cm x 24 cm
Dimensions:	Width: 52 cm Depth: 43 cm Height: 30 cm
Weight:	8.70 kg

Scope of delivery:

4 x EUROLITE AKKU UP-4 Entry QCL Spot

1 x spotlight
1 x user manual
1 x power cord
1 x remote control
1 x battery

1 x ROADINGER Flightcase 4x AKKU UP-4 Entry/IP UP-4 Entry

1 x case