



List price: 1783.81 €

incl. 19% VAT.

Features:

EUROLITE AKKU IP UP-4 Entry QCL Spot QuickDMX

IP65 battery-powered uplight with RGBW LEDs, QuickDMX and IR remote control

- Integrated QuickDMX transceiver for wireless DMX control
- Sturdy metal housing with handle and folding foot for angled placement
- Cordless, flexible and versatile
- Battery operation up to 12h depending on program used
- 4 powerful LEDs 8 W COB (chip-on-board) 4in1 QCL RGBW (homogenous color mix)
- Color blend stepless; color change adjustable; color fade adjustable; Dimmer electronic
- Strobe effect
- Integrated show programs
- Direct color selection for 19 preset colors
- The device is cooled by passive convection cooling
- Control via stand-alone; IR remote control; DMX; master/slave function; QuickDMX
- Preprogrammed in Light Captain; EASY SHOW 1; EASY SHOW 2; EASY SHOW 3; Light J; Colorchief
- Flicker-free
- With a beam angle of 16°
- OLED display
- Rubber feet
- Suitable for outdoor use IP65
- For application areas such as: Wedding/gala/events; mobile use; mobile djs / entertainer; small rental
- Silent operation
- Application possibility: Standing

Package contents

- 1 x spotlight, 1 x user manual, 1 x power cord, 1 x remote control, 2 x battery

Logistic

EAN / GTIN: 4026397710908

Weight: 32,00 kg

Length: 0.00 m

Width: 0.00 m

Height: 0.00 m

Bulky product

ROADINGER Flightcase 4x AKKU UP-4 Entry/IP UP-4 Entry

Trunk case, PRO version

- High-quality workmanship with birch multiplex 6 mm, dark brown
- Interior with foam padding
cover with foam padding
- Aluminum profile frames 22mm with rounded edges
- 2 hinged, chromium plated case handles
- 2 chrome tip-over locks
- 1 high-quality butterfly lock
- Branded hardware
- Made in Europe
- For further information about this product, please refer to the Data Sheet under "Downloads"

Package contents

- 1 x case

Technical specifications:

Weight:	26,70 kg
---------	----------

EUROLITE AKKU IP UP-4 Entry QCL Spot QuickDMX

Power supply:	100-240 V AC, 50/60 Hz
IP classification:	IP65
Protection class:	Protection class I
Power connection:	Battery/battery pack built-in Mains input via IP T-Con (M) mounting version power supply cord with safety plug (provided)
Battery pack type:	1 x lithium ion 11,1 V, 4400 mAh, 48,84 Wh
Battery pack:	Battery operation up to 12h depending on program used Recharging time 3h
Lamp type:	LED lamp
LED type:	4 x 8 W COB (chip-on-board) 4in1 QCL RGBW (homogenous color mix)
DMX channels:	3; 4; 5; 6; 9
DMX input:	3-pin XLR (M) mounting version IP
DMX output:	3-pin XLR (F) mounting version IP
Cooling:	Passive convection cooling
Control:	Stand-alone; IR remote control; DMX; master/slave function; QuickDMX
Preprogrammed in:	Light Captain; EASY SHOW 1; EASY SHOW 2; EASY SHOW 3; Light´J; Colorchief
Projection:	Flicker-free
Carrier frequency:	2,4 GHz
Beam angle:	16°
Beam angle (1/2 peak):	16°
Beam angle (1/10 peak):	32
Housing color:	Black

Display type:	OLED display
Transport aid:	Rubber feet
Dimensions:	Width: 19,00 cm Depth: 15,50 cm Height: 23,25 cm
Weight:	4,50 kg
Noise classification:	Class 0 (no noise at all)
Remote control	
Battery:	1 x button cell 3.0 V CR2025 lithium manganese built-in
Legal specifications	
Special product:	Not designed for household room illumination
Intended use:	Show effect lighting

ROADINGER Flightcase 4x AKKU UP-4 Entry/IP UP-4 Entry

Maximum load:	50 kg
Aluminum profile frames:	22 mm
Case handle:	2 pc/pcs
Stop hinge:	2 pc/pcs
Lock:	Butterfly lock: 1 pc/pcs
Use of brands:	Branded hardware
Material:	Birch multiplex, 6 mm, laminated
Color:	Dark brown
Device compartment:	18 cm x 18,5 cm x 23 cm
Accessory compartment:	10 cm x 40 cm x 24 cm
Dimensions:	Width: 52 cm Depth: 43 cm Height: 30 cm
Weight:	8,70 kg