



List price: 950.81 €

incl. 19% VAT.

Features:

EUROLITE LED TSL-350 Scan COB wh

Handy scanner with 60 W COB LED, gobo and color wheel

- Compact design
- 1 powerful LED 60 W COB (chip-on-board) cold white (CW)
- Positioning within
- Color wheel; gobo wheel with rotating gobos; focus manual
- Dimmer electronic
- Color wheel with 7 dichroic filters plus open
half colors selectable, Rainbow effect with adjustable speed
- Gobo wheel with rotating gobos, 7 gobos and open
slot-in gobo system for easy gobo replacement
- Shake effect
- Integrated show programs
- The device is cooled by cooling fan
- Control via stand-alone; DMX; QuickDMX via USB (optional); master/slave function; sound to light via microphone; W-DMX by wireless solution via USB (optional); CRMX by LumenRadio via USB (optional)
- Preprogrammed in Light´J; Light Captain; EASY SHOW 2; EASY SHOW 3
- Flicker-free
- With a beam angle of 11°
- LCD display
- Rubber feet
- For application areas such as: Clubs/dancing school; wedding/gala/events; party room; mobile djs / entertainer
- Application possibility: Standing; suspended; on stand

Package contents

Logistic

EAN / GTIN: 4026397704426

Weight: 17,00 kg

Length: 0.00 m

Width: 0.00 m

Height: 0.00 m

- 1 x moving light, 1 x user manual, 1 x power cord, 1 x mounting bracket, 3 x gobos

ROADINGER Flightcase 2x TSL-150/250/350

Trunk case

- High-quality workmanship with plywood multi-layer glued 7 mm, black, laminated
- Interior with foam padding
cover with foam padding
- Aluminum profile frames 30mm with rounded edges
- 2 hinged, chromium plated case handles
- 2 chrome tip-over locks
- 2 high-quality butterfly locks with shut-off function
- 4 x rubber feet
- For further information about this product, please refer to the Data Sheet under "Downloads"

Technical specifications:

Weight:	13,42 kg
---------	----------

EUROLITE LED TSL-350 Scan COB wh

Power supply:	100-240 V AC, 50/60 Hz
Power consumption:	70 W
IP classification:	IP20
Protection class:	Protection class I
Power connection:	Mains input via IEC connector (M) mounting version power supply cord with safety plug (provided)
Fuse:	5 x 20 mm, T 1,5 A fuse replaceable
Lamp type:	LED lamp
LED type:	1 x 60 W COB (chip-on-board) cold white (CW)
Equipment:	Color wheel; gobo wheel with rotating gobos; focus manual
Color generation:	Color wheel with 7 dichroic filters plus open Half colors selectable, Rainbow effect with adjustable speed
Gobos:	Gobo wheel with rotating gobos, 7 gobos and open Outside diameter 10mm Image diameter 14mm Slot-in gobo system for easy gobo replacement Shake effect
DMX channels:	10
DMX input:	3-pin XLR (M) mounting version
DMX output:	3-pin XLR (F) mounting version
Cooling:	Cooling fan
Control:	Stand-alone; DMX; QuickDMX via USB (optional); master/slave function; sound to light via microphone; W-DMX by wireless solution via USB (optional); CRMX by LumenRadio via USB (optional)

Preprogrammed in:	Light`J; Light Captain; EASY SHOW 2; EASY SHOW 3
Projection:	Flicker-free
Beam angle:	11°
Beam angle (1/2 peak):	11°
Illuminance in Lux (lx):	Cold white (CW) 1m: 12034 lx, 3m: 1489 lx, 6m: 388 lx
Housing color:	White
Display type:	LCD display
Transport aid:	Rubber feet
Dimensions:	Width: 16,0 cm Depth: 15,0 cm Height: 33,0 cm
Weight:	3,26 kg

ROADINGER Flightcase 2x TSL-150/250/350

Maximum load:	50 kg
Aluminum profile frames:	30 mm
Case handle:	2 pc/pcs
Stop hinge:	2 pc/pcs
Lock:	Butterfly lock: 2 pc/pcs with shut-off function
Transport aid:	4 x rubber feet
Material:	Plywood multi-layer glued, 7 mm
Color:	Black, laminated
Device compartment:	19 cm x 33,5 cm x 12,5 cm
Accessory compartment:	8 cm x 33 cm x 12,5 cm
Inside dimensions:	49 cm x 33,5 cm x 12,5 cm
Dimensions:	Width: 54 cm Depth: 38 cm Height: 24 cm
Weight:	6,90 kg