



### Features:

#### EUROLITE AKKU MBT-3 Spot MK2

Light fan for special uplight and beam effects with rechargeable battery

- Cordless, flexible and versatile
- Battery operation up to 16h depending on program used
- Integrated automatic charging of the battery and status indicator
- 3 LEDs 8 W SMD 9080 4in1 QCL RGBW (homogenous color mix) <BR> LEDs controlled separately
- Color blend stepless; color change adjustable; color fade adjustable; Dimmer electronic; Dimmer speed (step response) with adjustable response
- Strobe effect; fan effect; uplight effect
- 9 integrated show programs
- Direct color selection for 15 preset colors
- The device is cooled by passive convection cooling
- Control via stand-alone; master/slave function; sound to light via microphone; IR remote control; DMX; QuickDMX via USB (optional); W-DMX by wireless solution via USB (optional); CRMX by LumenRadio via USB (optional)
- Fixtures available for Light´J; Light Captain; EASY SHOW 1; EASY SHOW 3; EASY SHOW 2; Colorchief
- Flicker-free
- Space-saving construction
- With a beam angle of 13°
- 4 digit 7-segment LED display
- Mains input and output for power linking up to 8 units
- For application areas such as: Clubs/dancing school; decoration; wedding/gala/events; mobile djs / entertainer; party room; restaurants, bars and hotels; rental
- Silent operation

### Logistic

EAN / GTIN: 4026397684087

- Application possibility: Standing; suspended

### EUROLITE SB-15 Soft Bag

Universal softbag

- High-quality workmanship with nylon , black
- Interior with foam padding
- 2 carrying straps

### Technical specifications:

---

Weight:	8.57 kg
---------	---------

---

### EUROLITE AKKU MBT-3 Spot MK2

Power supply:	100-240 V AC, 50/60 Hz
IP classification:	IP20
Protection class:	Protection class I
Power connection:	Mains input via IEC connector (M) mounting version power supply cord with safety plug (provided)
Cable length:	1.5 m
Power output:	IEC connector (F) mounting version
Fuse:	5 x 20 mm, T 1.6 A fuse replaceable
Battery pack type:	1 x lithium ion 14.8 V, 6600 mAh, 97.68 Wh
Battery pack:	Battery operation up to 16h depending on program used Recharging time 4h
Battery:	1 x button cell 3.0 V CR2025 lithium manganese built-in
Lamp type:	LED lamp
LED type:	3 x 8 W SMD 9080 4in1 QCL RGBW (homogenous color mix)
Inclination angle:	180 °
Flash rate:	0 - 25 Hz
DMX channels:	3; 4; 8; 12; 16
DMX input:	3-pin XLR (M) mounting version
DMX output:	3-pin XLR (F) mounting version
Cooling:	Passive convection cooling
Control:	Stand-alone; master/slave function; sound to light via microphone; IR remote control; DMX; QuickDMX via USB (optional); W-DMX by wireless solution via USB (optional); CRMX by LumenRadio via USB (optional)
Fixtures available for:	Light´J; Light Captain; EASY SHOW 1; EASY SHOW 3; EASY SHOW 2; Colorchief
Projection:	Flicker-free
Setup:	Space-saving construction

Beam angle:	13°
Beam angle (1/2 peak):	13°
Housing color:	Black
Display type:	4 digit 7-segment LED display
Dimensions:	Length: 30.5 cm Width: 9.5 cm Height: 22 cm
Weight:	4.15 kg
Noise classification:	Class 0 (no noise at all)
Special product:	Not designed for household room illumination
Intended use:	Show effect lighting

#### **EUROLITE SB-15 Soft Bag**

Carrying strap:	2 pc/pcs
Material:	Nylon
Color:	Black
Dimensions:	Width: 34.5 cm Depth: 21.5 cm Height: 22 cm
Weight:	0.27 kg

#### **Scope of delivery:**

##### **2 x EUROLITE AKKU MBT-3 Spot MK2**

- 1 x device
- 1 x power cord
- 1 x user manual
- 1 x remote control
- 1 x battery

##### **1 x EUROLITE SB-15 Soft Bag**

- 1 x bag
- 1 x segment