



List price: 950.81 €

incl. 19% VAT.

Features:

EUROLITE AKKU Mini IP UP-4 QCL Spot MK2

Mini battery uplight IP65 with RGBW LEDs and IR remote control

- Cordless, flexible and versatile
- Battery operation up to 9h depending on program used
- Integrated automatic charging of the battery and status indicator
- 4 powerful LEDs 4 W 4in1 QCL RGBW (homogenous color mix)
- Color blend stepless; color change adjustable; color fade adjustable
- Strobe effect; uplight effect
- Direct color selection for 10 preset colors
- The device is cooled by passive convection cooling
- Control via sound to light via microphone; stand-alone; IR remote control
- Flicker-free
- With a beam angle of 15°
- 4 digit 7-segment LED display
- Suitable for outdoor use IP65
- For application areas such as: Wedding/gala/events; mobile use; mobile djs / entertainer; small rental
- Application possibility: Standing
- Silent operation

Package contents

- 1 x device, 1 x user manual, 1 x remote control, 1 x USB cable

Logistic

EAN / GTIN: 4026397711837

Weight: 9,00 kg

Length: 0.00 m

Width: 0.00 m

Height: 0.00 m

EUROLITE Soft Bag for 6x AKKU Mini IP UP-4 QCL Spot MK2

Nylon transport bag

- With 6 device compartments
 - With accessory compartment
 - High-quality workmanship with nylon , black
 - Interior with foam padding
 - 2 carrying straps
- Package contents**
- 1 x bag

Technical specifications:

Weight:	7,53 kg
---------	---------

EUROLITE AKKU Mini IP UP-4 QCL Spot MK2

Power supply:	100-240 V AC, 50/60 Hz 5V 1600 mA
IP classification:	IP65
Protection class:	Protection class III
Power connection:	Battery/battery pack Mains input via USB C (W) mounting version
Battery pack type:	1 x 11,1 V, 3200 mAh, 35,52 Wh
Battery pack:	Battery operation up to 9h depending on program used Recharging time 5h
Lamp type:	LED lamp
LED type:	4 x 4 W 4in1 QCL RGBW (homogenous color mix)
Flash rate:	1 - 20 Hz
Cooling:	Passive convection cooling
Control:	Sound to light via microphone; stand-alone; IR remote control
Projection:	Flicker-free
Beam angle:	15°
Beam angle (1/2 peak):	15°
Beam angle (1/10 peak):	30°
Housing color:	Black
Display type:	4 digit 7-segment LED display
Dimensions:	Length: 10 cm Width: 11 cm Height: 12 cm
Weight:	1,17 kg
Noise classification:	Class 0 (no noise at all)
Remote control	
Battery:	1 x button cell CR2025
Legal specifications	
Special product:	Not designed for household room illumination
Intended use:	Show effect lighting

EUROLITE Soft Bag for 6x AKKU Mini IP UP-4 QCL Spot MK2

Carrying strap:	2 pc/pcs
Material:	Nylon, water repellent
Color:	Black
Device compartment:	9,5 cm x 11 cm x 13 cm
Accessory compartment:	5 cm x 23 cm x 13 cm
Dimensions:	Length: 43,5 cm
	Depth: 29 cm
	Height: 16 cm
Weight:	0,51 kg