



### Features:

#### EUROLITE AKKU IP PAR 7 QCL CRMX MK2

IP65 battery-powered spotlight with RGBW LEDs, CRMX, frost filters and IR remote control

- Integrated wireless receiver for CRMX operation
- Two additional frost filters provide a soft, homogeneous light
- Battery operation up to 9h depending on program used
- 7 LEDs 8 W SMD 9080 4in1 QCL RGBW (homogenous color mix)
- Emergency lighting function in case of power failure; color blend stepless; color change adjustable; color fade adjustable; Dimmer electronic; Dimmer speed (step response) with adjustable response; white balance; Energy-saving mode
- Strobe effect
- 36 integrated show programs
- Direct color selection for 15 preset colors
- The device is cooled by passive convection cooling
- Control via stand-alone; master/slave function; IR remote control; DMX; W-DMX by wireless solution; CRMX by LumenRadio; RDM
- Fixtures available for Light' J; Light Captain; Colorchief
- Flicker-free
- With a beam angle of 6°
- With double bracket
- OLED display
- Display of the remaining battery life for the current setting
- Charge status indicator
- Mains input and output for power linking up to 8 units
- Suitable for outdoor use IP65
- With pressure compensation membrane
- With a KENSINGTON LOCK theft protection

### Logistic

EAN / GTIN: 4026397697483

Weight: 33,00 kg

Length: 0.00 m

Width: 0.00 m

Height: 0.00 m

Bulky product

- For application areas such as: Architecture; stage; wedding/gala/events; rental; video and photography
- Silent operation
- Application possibility: Standing; suspended; on stand
- 3 buttons on the remote control for saving your own settings

#### **ROADINGER Flightcase 8x AKKU IP PAR 7 QCL WDMX with charging function**

Trunk case with castors

- With 8 device compartments
- With accessory compartment
- High-quality workmanship with plywood multi-layer glued 9 mm, black, laminated
- Interior with foam padding<BR>cover with foam padding
- Aluminum profile frames 30mm with rounded edges
- 4 hinged, chromium plated case handles
- 2 chrome tip-over locks
- 2 high-quality butterfly locks with shut-off function
- 4 x castors with 2 locking brakes Ø 100 mm
- 4 x built-in stacking trays in the cover

#### **Technical specifications:**

|         |          |
|---------|----------|
| Weight: | 32.33 kg |
|---------|----------|

#### **EUROLITE AKKU IP PAR 7 QCL CRMX MK2**

|                         |                                                                                                                        |
|-------------------------|------------------------------------------------------------------------------------------------------------------------|
| Power supply:           | 100-240 V AC, 50/60 Hz                                                                                                 |
| IP classification:      | IP65                                                                                                                   |
| Protection class:       | Protection class I                                                                                                     |
| Power connection:       | Battery/battery pack<br>Mains input via IP T-Con (M) mounting version<br>power supply cord with safety plug (provided) |
| Cable length:           | Approx. 1.2 m                                                                                                          |
| Power output:           | 1 x IP T-Con (F) mounting version                                                                                      |
| Battery pack:           | Battery operation up to 9h depending on program used<br>Recharging time 4h                                             |
| Lamp type:              | LED lamp                                                                                                               |
| LED type:               | 7 x 8 W SMD 9080 4in1 QCL RGBW<br>(homogenous color mix)                                                               |
| Flash rate:             | 1 - 23 Hz                                                                                                              |
| DMX channels:           | 3; 4; 6; 8; 11                                                                                                         |
| DMX input:              | 1 x 3-pin XLR (M) mounting version IP                                                                                  |
| DMX output:             | 1 x 3-pin XLR (F) mounting version IP                                                                                  |
| Cooling:                | Passive convection cooling                                                                                             |
| Control:                | Stand-alone; master/slave function; IR remote control; DMX; W-DMX by wireless solution; CRMX by LumenRadio; RDM        |
| Fixtures available for: | Light´J; Light Captain; Colorchief                                                                                     |
| Projection:             | Flicker-free                                                                                                           |

|                         |                                                          |
|-------------------------|----------------------------------------------------------|
| Carrier frequency:      | 2.4 GHz                                                  |
| Beam angle:             | 6°                                                       |
| Beam angle (1/2 peak):  | 6°<br>Frost filter 13°<br>Frost filter 20°               |
| Beam angle (1/10 peak): | 16°<br>Frost filter 32°<br>Frost filter 44°              |
| Housing color:          | Black                                                    |
| Attachment system:      | Double bracket                                           |
| Display type:           | OLED display                                             |
| Display:                | Battery runtime calculation , charge status indicator    |
| Color:                  | Black                                                    |
| Theft protection:       | KENSINGTON LOCK                                          |
| Dimensions:             | Width: 23.4 cm<br>Height: 28.0 cm<br>Diameter: Ø 17.0 cm |
| Weight:                 | 5.30 kg                                                  |
| Noise classification:   | Class 0 (no noise at all); Class 0 (no noise at all)     |
| Battery:                | 1 x button cell 3.0 V CR2032 lithium manganese built-in  |
| Special product:        | Not designed for household room illumination             |
| Intended use:           | Show effect lighting                                     |

#### **ROADINGER Flightcase 8x AKKU IP PAR 7 QCL WDMX with charging function**

|                          |                                                                                                |
|--------------------------|------------------------------------------------------------------------------------------------|
| Power supply:            | 100-240 V AC, 50/60 Hz                                                                         |
| Power connection:        | Mains input via IP T-Con (M) mounting version<br>power supply cord with safety plug (provided) |
| Device fuse:             | 5 x 20 mm, F 5 A fuse replaceable                                                              |
| Aluminum profile frames: | 30 mm                                                                                          |
| Case handle:             | 4 pc/pcs                                                                                       |
| Stop hinge:              | 2 pc/pcs                                                                                       |
| Lock:                    | Butterfly lock: 2 pc/pcs with shut-off function                                                |
| Transport aid:           | 4 x castors with 2 locking brakes Ø 100 mm<br>4 x built-in stacking trays in the cover         |
| Material:                | Plywood multi-layer glued, 9 mm                                                                |
| Color:                   | Black, laminated                                                                               |
| Device compartment:      | 18 cm x 25 cm x 28 cm                                                                          |
| Accessory compartment:   | 9.5 cm x 51.5 cm x 26 cm                                                                       |
| Dimensions:              | Width: 115 cm<br>Depth: 56 cm<br>Height: 49 cm                                                 |
| Weight:                  | 27.65 kg                                                                                       |
| Cable construction:      | 3 x 1.5 mm² H07RN-F                                                                            |
| Cable length:            | 1.2 m                                                                                          |

## Scope of delivery:

---

### **8 x EUROLITE AKKU IP PAR 7 QCL CRMX MK2**

- 1 x device
- 1 x user manual
- 1 x power cord
- 1 x remote control
- 1 x battery
- 2 x frost filter
- 2 x knurled screw
- 1 x declaration of conformity
- 2 x mounting bracket

### **1 x ROADINGER Flightcase 8x AKKU IP PAR 7 QCL WDMX with charging function**

- 1 x case
- 1 x power cord
- 4 x castors
- 16 x screw
- 1 x key
- 1 x user manual