

# EUROLITE Set 4x LED CLS-18 QCL RGB/WW 18x7W + Flightcase with wheels No.: 20001036

GTIN: 4026397733082







List price: 1783.81 €

incl. 19% VAT.

### Features:

### **EUROLITE LED CLS-18 QCL RGB/WW 18x7W**

LED floodlight with RGB/WW color mixing, barn doors, IR remote control and frost filter

- Additional frost filter provides a wide, soft and homogeneous light
- 18 powerful LEDs 7 W 4in1 QCL RGB/WW (homogenous color mix)
- Color blend stepless; color change adjustable; color fade adjustable; Dimmer electronic;
  Dimmer speed (step response) adjustable; white balance
- Strobe effect
- The device is cooled by temperature-controlled fan
- Control via stand-alone; DMX; QuickDMX (optional); W-DMX by wireless solution (optional); CRMX by LumenRadio (optional); master/slave function; sound to light via microphone; IR remote control
- Preprogrammed in Light'J; EASY SHOW 2; EASY SHOW 3; Colorchief
- Flicker-free
- With a beam angle of 11°
- Direct color temperature selection for 3100 preset values
- With mounting bracket
- OLED display
- Rubber feet
- For application areas such as: Wedding/gala/events; stage; theater; mobile djs / entertainer; restaurants, bars and hotels
- Very quiet working noise
- Application possibility: Standing; suspended; on stand
- 3 buttons on the remote control for saving your own settings

#### knurled screw

- M4 thread

Package contents

### Logistic

EAN / GTIN: 4026397733082

Weight: 40,50 kg Length: 0.00 m Width: 0.00 m Heigth: 0.00 m Bulky product - 1 x device, 1 x power cord, 1 x frost filter, 1 x remote control, 4 x knurled screw, 1 x user manual

### ROADINGER Flightcase 4x LED CLS-18 QCL RGB/WW with wheels

Trunk case with castors

- High-quality workmanship with plywood multi-layer glued 9 mm, black, laminated
- Interior with foam padding<BR>cover with foam padding
- Aluminum profile frames 30mm with rounded edges
- 2 hinged, chromium plated case handles
- 2 chrome tip-over locks
- 2 high-quality butterfly locks
- 4 x castors with 2 locking brakes
- For further information about this product, please refer to the Data Sheet under "Downloads"

### **Technical specifications:**

Weight: 39,81 kg

### **EUROLITE LED CLS-18 QCL RGB/WW 18x7W**

| Power supply:           | 100-240 V AC, 50/60 Hz   |
|-------------------------|--|
| Power consumption:      | 104 W  |
| IP classification:      | IP20   |
| Protection class:       | Protection class I   |
| Power connection:       | Mains input via P-Con (blue), mounting version power supply cord with safety plug included   |
| Power output:           | 1 x PowerCON (gray)  |
| Fuse:                   | T 6,3 A fuse fix on board  |
| Lamp type:              | LED lamp   |
| LED type:               | 18 x 7 W 4in1 QCL RGB/WW (homogenous color mix)  |
| Flash rate:             | 1 - 23 Hz  |
| DMX channels:           | 3; 4; 6; 8; 11   |
| DMX input:              | 1 x 3-pin XLR (M) mounting version   |
|                         | 1 x 5-pin XLR (M) mounting version   |
| DMX output:             | 1 x 3-pin XLR (F) mounting version   |
|                         | 1 x 5-pin XLR (F) mounting version   |
| Cooling:                | Temperature-controlled fan   |
| Control:                | Stand-alone; DMX; QuickDMX (optional); W-DMX by wireless solution (optional); CRMX by LumenRadio (optional); master/slave function; sound to light via microphone; IR remote control |
| Preprogrammed in:       | Light'J; EASY SHOW 2; EASY SHOW 3;<br>Colorchief   |
| Projection:             | Flicker-free   |
| Beam angle:             | 11°  |
| Beam angle (1/2 peak):  | 11°  |
|                         | Frost filter 15°   |
| Beam angle (1/10 peak): | 26°  |

|                          | Frost filter 37°   |
|--------------------------|--|
| Housing color:           | Black matte  |
| Attachment system:       | Mounting bracket   |
| Display type:            | OLED display   |
| Transport aid:           | Rubber feet  |
| Dimensions:              | Length: 39,6 cm<br>Width: 14,3 cm<br>Height: 21,3 cm                       |
| Weight:                  | 4,75 kg  |
| Noise classification:    | Class 1 (very slight noise, suitable for noise-<br>sensitive environments) |
| Mounting bracket         |  |
| Diameter mounting holes: | 3 x Ø11mm; 2 x Ø8mm; 8 x Ø15mm   |
| Material:                | Metal, 2 mm  |
| Power cord               |  |
| Cable construction:      | 3 x 1,0 mm² H05VV-F  |
| Cable length:            | Approx. 1,2 m  |
| Frost filter             |  |
| Diameter mounting holes: | 4 x Ø4,5mm   |
| Material:                | Plastic, 2 mm  |
| Dimensions:              | Width: 28,3 cm<br>Height: 11,6 cm  |
| Remote control           |  |
| Battery:                 | 1 x button cell 3.0 V CR2032 lithium manganese built-in                    |
| Barndoor                 |  |
| Material:                | Metal, 0,8 mm  |
| Dimensions:              | Width: 46,5 cm<br>Height: 28,5 cm  |
| Knurled screw            |  |
| Thread:                  | M4 thread x 8 mm   |
| Legal specifications     |  |
| Special product:         | Not designed for household room illumination                               |
| Intended use:            | Show effect lighting   |
|                          |  |

## ROADINGER Flightcase 4x LED CLS-18 QCL RGB/WW with wheels

| 30 mm                             |
|-----------------------------------|
| 2 pc/pcs                          |
| 2 pc/pcs                          |
| Butterfly lock: 2 pc/pcs          |
| 4 x castors with 2 locking brakes |
| Plywood multi-layer glued, 9 mm   |
| Black, laminated                  |
| 12 cm x 40 cm x 28 cm             |
| 11 cm x 46,5 cm x 28 cm           |
|                                   |

Dimensions: Width: 87,5 cm Depth: 52,5 cm

Height: 44 cm

Weight: 19,10 kg