

# EUROLITE Set 2x LED TMH-B120 Hypno Moving-Head Beam + Flightcase withwwheels45

GTIN: 4026397748345







List price: 1902.81 €

incl. 19% VAT.

## Features:

### **EUROLITE LED TMH-B120 Hypno Moving Head Beam**

LED moving head beam with hypno ring, color wheel, static gobo wheel, prism and focus

- 1 powerful LED 120 W COB (chip-on-board) cold white (CW)
- 30 powerful LEDs 0,2 W SMD 5050 3in1 TCL RGB (homogenous color mix)
- Positioning within 540° PAN, 240° TILT
- Auto position correction (feedback)
- Exact positioning (16 bit resolution)
- Color wheel; gobo wheel with static gobos; focus motor-driven; frost filter; prism 8-fold rotating
- Dimmer
- Beam effect
- Color wheel with 7 dichroic filters plus open<BR>half colors selectable, Rainbow effect with adjustable speed in both directions
- Gobo wheel with static gobos, 13 gobos und open<BR>shake effect
- 4 integrated show programs
- The device is cooled by cooling fan at the base; cooling fan at the Head
- Control via stand-alone; sound to light via microphone; DMX; QuickDMX via USB (optional);
   CRMX by LumenRadio via USB (optional); W-DMX by wireless solution via USB (optional);
   master/slave function
- Preprogrammed in Light Captain
- Flicker-free
- DMX fail mode (hold; zero values)
- With a beam angle of 2°
- With omega bracket
- Multicolor LCD display
- 2 Rugged carrying handles
- 4 x rubber feet

### Logistic

EAN / GTIN: 4026397748345

Weight: 32,00 kg Length: 0.00 m Width: 0.00 m Heigth: 0.00 m Bulky product

- Mains input and output for power linking up to 8 units
- For application areas such as: Clubs/dancing school; stage; mobile djs / entertainer; rental
- Application possibility: Standing; suspended

#### Package contents

- 1 x moving light, 1 x power cord, 1 x omega bracket, 1 x safety eyelet, 1 x user manual

#### **ROADINGER Flightcase 2x TMH-B120 with wheels**

Trunk case with castors

- With 2 device compartment
- With 1 accessory compartment
- High-quality workmanship with plywood multi-layer glued 9 mm, black, laminated
- Interior with foam padding<BR>cover with foam padding
- Aluminum profile frames 30mm with rounded edges
- 2 hinged, chromium plated case handles
- 2 chrome tip-over locks
- 2 high-quality butterfly locks
- 4 x castors with 2 locking brakes

# **Technical specifications:**

Weight: 27,90 kg

### **EUROLITE LED TMH-B120 Hypno Moving Head Beam**

| Power supply:       | 100-240 V AC, 50/60 Hz  |
|---------------------|---|
| Power consumption:  | 170 W   |
| IP classification:  | IP20  |
| Protection class:   | Protection class I  |
| Power connection:   | Mains input via P-Con (blue), mounting version power supply cord with safety plug (provided)                                  |
| Cable construction: | 3 x 1,0 mm² H05VV-F   |
| Cable length:       | 1,1 m   |
| Power output:       | P-Con (gray), mounting version  |
| Fuse:               | 5 x 20 mm, T 2 A fuse replaceable   |
| Lamp type:          | LED lamp  |
| LED type:           | 1 x 120 W COB (chip-on-board) cold white (CW)<br>30 x 0,2 W SMD 5050 3in1 TCL RGB<br>(homogenous color mix)                   |
| Max. TILT movement: | 240° exact positioning (16 bit resolution) auto position correction (feedback)  |
| Max. PAN movement:  | 540° exact positioning (16 bit resolution) auto position correction (feedback)  |
| Flash rate:         | 1 - 20 Hz   |
| Equipment:          | Color wheel; gobo wheel with static gobos; focus motor-driven; frost filter; prism 8-fold rotating                            |
| Color generation:   | Color wheel with 7 dichroic filters plus open Half colors selectable, Rainbow effect with adjustable speed in both directions |
| Gobos:              | Gobo wheel with static gobos, 13 gobos und open<br>Shake effect   |

| DMX input:  3-pin XLR (M) mounting version  DMX output:  3-pin XLR (F) mounting version  Cooling:  1 x cooling fan at the base 1 x cooling fan at the Head  Control:  Stand-alone; sound to light via microphone; DMX; QuickDMX via USB (optional); CRMX by LumenRadio via USB (optional); CRMX by wireless solution via USB (optional); master/slave function  Preprogrammed in:  Light Captain  Projection:  Flicker-free  DMX fail mode:  Hold; zero values  Beam angle:  2°  Beam angle (1/2 peak):  Beam 2°  Ring 120°  Beam angle (1/10 peak):  Beam 2°  Ring 120°  Color temperature:  8500K  Housing color:  Black  Attachment system:  Omega bracket  Display type:  Multicolor LCD display  Status LED:  DMX, fault  USB port:  Type A  Carrying handle:  2 pc/pcs  Transport aid:  4 x rubber feet  Material:  Plastic  Dimensions:  Width: 26,0 cm Depth: 23,5 cm Height: 37,5 cm  Weight:  6,95 kg  Legal specifications  Special product:  Not designed for household room illumination  Intended use:  Show effect lighting   | DMX channels:           | 21  |
|--|-------------------------|---|
| Cooling:  1 x cooling fan at the base 1 x cooling fan at the Head  Control:  Stand-alone; sound to light via microphone; DMX; QuickDMX via USB (optional); CRMX by LumenRadio via USB (optional); W-DMX by wireless solution via USB (optional); master/slave function  Preprogrammed in:  Light Captain  Projection:  Flicker-free  DMX fail mode:  Hold; zero values  Beam angle:  2°  Beam angle (1/2 peak):  Beam angle (1/2 peak):  Beam angle (1/10 peak):  Beam angle (1/2 | DMX input:              | 3-pin XLR (M) mounting version  |
| 1 x cooling fan at the Head  Control:  Stand-alone; sound to light via microphone; DMX; QuickDMX via USB (optional); CRMX by LumenRadio via USB (optional); W-DMX by wireless solution via USB (optional); master/slave function  Preprogrammed in:  Light Captain  Projection:  Flicker-free  DMX fail mode:  Hold; zero values  Beam angle:  2°  Beam angle (1/2 peak):  Beam 2°  Ring 120°  Beam angle (1/10 peak):  Beam 2°  Ring 120°  Color temperature:  8500K  Housing color:  Black  Attachment system:  Omega bracket  Display type:  Multicolor LCD display  Status LED:  DMX, fault  USB port:  Type A  Carrying handle:  2 pc/pcs  Transport aid:  4 x rubber feet  Material:  Plastic  Dimensions:  Width: 26,0 cm  Depth: 23,5 cm  Height: 37,5 cm  Weight:  6,95 kg  Legal specifications  Special product:  Not designed for household room illumination  | DMX output:             | 3-pin XLR (F) mounting version  |
| QuickDMX via USB (optional); CRMX by LumenRadio via USB (optional); w-DMX by wireless solution via USB (optional); master/slave function  Preprogrammed in:  Light Captain  Projection:  Flicker-free  DMX fail mode:  Beam angle:  2°  Beam angle (1/2 peak):  Beam 2°  Ring 120°  Beam angle (1/10 peak):  Beam 2°  Ring 120°  Color temperature:  8500K  Housing color:  Black  Attachment system:  Omega bracket  Display type:  Multicolor LCD display  Status LED:  DMX, fault  USB port:  Type A  Carrying handle:  2 pc/pcs  Transport aid:  4 x rubber feet  Material:  Plastic  Dimensions:  Width: 26,0 cm Depth: 23,5 cm Height: 37,5 cm  Weight:  6,95 kg  Legal specifications  Special product:  Not designed for household room illumination   | Cooling:                | -   |
| Projection:  DMX fail mode:  Hold; zero values  Beam angle:  2°  Beam angle (1/2 peak):  Beam angle (1/10 peak):  Beam 2°  Ring 120°  Beam angle (1/10 peak):  Beam 2°  Ring 120°  Color temperature:  8500K  Housing color:  Black  Attachment system:  Omega bracket  Display type:  Multicolor LCD display  Status LED:  DMX, fault  USB port:  Type A  Carrying handle:  2 pc/pcs  Transport aid:  4 x rubber feet  Material:  Plastic  Dimensions:  Width: 26,0 cm  Depth: 23,5 cm  Height: 37,5 cm  Weight:  6,95 kg  Legal specifications  Special product:  Not designed for household room illumination   | Control:                | QuickDMX via USB (optional); CRMX by LumenRadio via USB (optional); W-DMX by wireless solution via USB (optional); master/slave |
| DMX fail mode:  Beam angle:  Beam angle (1/2 peak):  Beam 2° Ring 120°  Beam angle (1/10 peak):  Beam 2° Ring 120°  Color temperature:  8500K  Housing color:  Black  Attachment system:  Omega bracket  Display type:  Multicolor LCD display  Status LED:  DMX, fault  USB port:  Type A  Carrying handle:  2 pc/pcs  Transport aid:  4 x rubber feet  Material:  Plastic  Dimensions:  Width: 26,0 cm Depth: 23,5 cm Height: 37,5 cm  Weight:  6,95 kg  Legal specifications  Special product:  Not designed for household room illumination  | Preprogrammed in:       | Light Captain   |
| Beam angle:  Beam angle (1/2 peak):  Beam 2° Ring 120°  Beam 2° Ring 120°  Color temperature:  8500K  Housing color:  Black  Attachment system:  Omega bracket  Display type:  Multicolor LCD display  Status LED:  DMX, fault  USB port:  Type A  Carrying handle:  2 pc/pcs  Transport aid:  4 x rubber feet  Material:  Dimensions:  Width: 26,0 cm Depth: 23,5 cm Height: 37,5 cm  Weight:  6,95 kg  Legal specifications  Special product:  Not designed for household room illumination  | Projection:             | Flicker-free  |
| Beam angle (1/2 peak):  Ring 120°  Beam angle (1/10 peak):  Beam 2° Ring 120°  Color temperature:  8500K  Housing color:  Black  Attachment system:  Omega bracket  Display type:  Multicolor LCD display  Status LED:  DMX, fault  USB port:  Type A  Carrying handle:  2 pc/pcs  Transport aid:  4 x rubber feet  Material:  Plastic  Dimensions:  Width: 26,0 cm Depth: 23,5 cm Height: 37,5 cm  Weight:  6,95 kg  Legal specifications  Special product:  Not designed for household room illumination   | DMX fail mode:          | Hold; zero values   |
| Ring 120°  Beam angle (1/10 peak):  Beam 2° Ring 120°  Color temperature:  8500K  Housing color:  Black  Attachment system:  Omega bracket  Display type:  Multicolor LCD display  Status LED:  DMX, fault  USB port:  Type A  Carrying handle:  2 pc/pcs  Transport aid:  4 x rubber feet  Material:  Plastic  Dimensions:  Width: 26,0 cm Depth: 23,5 cm Height: 37,5 cm  Weight:  6,95 kg  Legal specifications  Special product:  Not designed for household room illumination   | Beam angle:             | 2°  |
| Ring 120°  Color temperature: 8500K  Housing color: Black  Attachment system: Omega bracket  Display type: Multicolor LCD display  Status LED: DMX, fault  USB port: Type A  Carrying handle: 2 pc/pcs  Transport aid: 4 x rubber feet  Material: Plastic  Dimensions: Width: 26,0 cm Depth: 23,5 cm Height: 37,5 cm  Weight: 6,95 kg  Legal specifications  Special product: Not designed for household room illumination   | Beam angle (1/2 peak):  |   |
| Housing color:  Attachment system:  Omega bracket  Display type:  Multicolor LCD display  Status LED:  DMX, fault  USB port:  Type A  Carrying handle:  2 pc/pcs  Transport aid:  4 x rubber feet  Material:  Plastic  Dimensions:  Width: 26,0 cm Depth: 23,5 cm Height: 37,5 cm  Weight:  6,95 kg  Legal specifications  Special product:  Not designed for household room illumination  | Beam angle (1/10 peak): |   |
| Attachment system:  Display type:  Multicolor LCD display  Status LED:  DMX, fault  USB port:  Type A  Carrying handle:  2 pc/pcs  Transport aid:  4 x rubber feet  Material:  Plastic  Dimensions:  Width: 26,0 cm Depth: 23,5 cm Height: 37,5 cm  Weight:  6,95 kg  Legal specifications  Special product:  Not designed for household room illumination   | Color temperature:      | 8500K   |
| Display type:  Status LED:  DMX, fault  USB port:  Type A  Carrying handle:  2 pc/pcs  Transport aid:  4 x rubber feet  Material:  Plastic  Dimensions:  Width: 26,0 cm Depth: 23,5 cm Height: 37,5 cm  Weight:  6,95 kg  Legal specifications  Special product:  Not designed for household room illumination   | Housing color:          | Black   |
| Status LED:  USB port:  Type A  Carrying handle:  2 pc/pcs  Transport aid:  4 x rubber feet  Material:  Plastic  Dimensions:  Width: 26,0 cm Depth: 23,5 cm Height: 37,5 cm  Weight:  6,95 kg  Legal specifications  Special product:  Not designed for household room illumination  | Attachment system:      | Omega bracket   |
| USB port:  Carrying handle:  2 pc/pcs  Transport aid:  4 x rubber feet  Material:  Plastic  Dimensions:  Width: 26,0 cm Depth: 23,5 cm Height: 37,5 cm  Weight:  6,95 kg  Legal specifications  Special product:  Not designed for household room illumination   | Display type:           | Multicolor LCD display  |
| Carrying handle:  2 pc/pcs  Transport aid:  4 x rubber feet  Material:  Plastic  Dimensions:  Width: 26,0 cm Depth: 23,5 cm Height: 37,5 cm  Weight:  6,95 kg  Legal specifications  Special product:  Not designed for household room illumination  | Status LED:             | DMX, fault  |
| Transport aid:  4 x rubber feet  Material:  Plastic  Dimensions:  Width: 26,0 cm  Depth: 23,5 cm  Height: 37,5 cm  Weight:  6,95 kg  Legal specifications  Special product:  Not designed for household room illumination  | USB port:               | Туре А  |
| Material:  Plastic  Width: 26,0 cm  Depth: 23,5 cm  Height: 37,5 cm  Weight:  6,95 kg  Legal specifications  Special product:  Not designed for household room illumination  | Carrying handle:        | 2 pc/pcs  |
| Dimensions:  Width: 26,0 cm Depth: 23,5 cm Height: 37,5 cm  Weight: 6,95 kg  Legal specifications  Special product:  Not designed for household room illumination  | Transport aid:          | 4 x rubber feet   |
| Depth: 23,5 cm Height: 37,5 cm  Weight: 6,95 kg  Legal specifications  Special product: Not designed for household room illumination   | Material:               | Plastic   |
| Legal specifications  Special product:  Not designed for household room illumination   | Dimensions:             | Depth: 23,5 cm  |
| Special product: Not designed for household room illumination  | Weight:                 | 6,95 kg   |
|  | Legal specifications    |   |
| Intended use: Show effect lighting   | Special product:        | Not designed for household room illumination  |
|  | Intended use:           | Show effect lighting  |

# ROADINGER Flightcase 2x TMH-B120 with wheels

| Maximum load:            | 50 kg                                      |
|--------------------------|--|
| Aluminum profile frames: | 30 mm                                      |
| Case handle:             | 2 pc/pcs                                   |
| Stop hinge:              | 2 pc/pcs                                   |
| Lock:                    | Butterfly lock: 2 pc/pcs                   |
| Transport aid:           | 4 x castors with 2 locking brakes          |
| Material:                | Plywood multi-layer glued, 9 mm, laminated |
| Color:                   | Black, laminated                           |
| Device compartment:      | 20,5 cm x 26 cm x 36 cm                    |
| Accessory compartment:   | 8 cm x 26 cm x 19 cm                       |
| ·                        |  |

Dimensions: Width: 57 cm
Depth: 31,5 cm

Height: 59 cm

Weight: 14,00 kg