

## EUROLITE Set 4x AKKU IP UP-4 QCL Spot QuickDMX MK2 + Flightcase with wheels and charging station

GTIN: 4026397625813



**List price: 2278.85 €**

incl. 19% VAT.

### Features:

#### EUROLITE AKKU IP UP-4 QCL Spot QuickDMX MK2

Weather-proof (IP65) battery powered LED uplight with 10W 4in1 LEDs and QuickDMX

- Integrated QuickDMX transceiver for wireless DMX control
- Cordless, flexible and versatile
- Battery operation up to 5.5h depending on program used
- Integrated automatic charging of the battery and status indicator
- 4 LEDs 10 W SMD 5050 4in1 QCL RGBW (homogenous color mix)
- Frost filter
- Dimmer electronic; Dimmer speed (step response) adjustable; color blend stepless; color fade adjustable speed; color change adjustable speed; colors preset; white balance adjustable; program selection manual; pulse-width modulation; Energy-saving mode; Emergency lighting function in case of power failure
- Wash effect; strobe effect
- 36 integrated show programs
- Direct color selection for 15 preset colors
- The device is cooled by passive convection cooling
- Control via stand-alone; IR remote control; DMX; QuickDMX; RDM; master/slave function; wireless Master/slave function
- Flicker-free
- DMX fail mode (blackout; hold; static; full on)
- With a beam angle of 8°
- With mounting bracket; with bracket for floor use; with omega bracket
- OLED display
- Charge status indicator
- Display of the remaining battery life for the current setting
- Built with SEETRONIC connector

### Logistic

EAN / GTIN: 4026397625813

Weight: 40,00 kg

Length: 0.00 m

Width: 0.00 m

Height: 0.00 m

Bulky product

- Suitable for outdoor use IP65
- With pressure compensation membrane
- With a KENSINGTON LOCK theft protection
- For application areas such as: Architecture; decoration; wedding/gala/events; mobile djs / entertainer; restaurants, bars and hotels; rental; advertisement/Shop window
- Silent operation
- Application possibility: Standing; suspended
- 3 buttons on the remote control for saving your own settings

**ROADINGER Flightcase 4x AKKU IP UP-4 QuickDMX with charging function**

Trunk case with castors

- With accessory compartment
- With 4 device compartments
- High-quality workmanship with plywood multi-layer glued 9 mm, black, laminated
- Interior with foam padding
- Aluminum profile frames 25mm with rounded edges
- 4 hinged, chromium plated case handles
- 2 chrome tip-over locks
- 2 high-quality butterfly locks with shut-off function
- 4 x castors with 2 locking brakes
- 4 x built-in stacking trays in the cover

**Technical specifications:**

|         |          |
|---------|----------|
| Weight: | 33.53 kg |
|---------|----------|

**EUROLITE AKKU IP UP-4 QCL Spot QuickDMX MK2**

|                     |                                                                                                           |
|---------------------|-----------------------------------------------------------------------------------------------------------|
| Power supply:       | 100-240 V AC, 50/60 Hz                                                                                    |
| IP classification:  | IP65                                                                                                      |
| Protection class:   | Protection class I                                                                                        |
| Power connection:   | Mains input via IP T-Con (M) mounting version power supply cord with safety plug                          |
| Cable construction: | 3 x 1.5 mm² H07RN-F                                                                                       |
| Battery pack type:  | 1 x lithium ion 14.8 V, 6600 mAh, 97.68 Wh                                                                |
| Battery pack:       | Battery operation up to 5.5h depending on program used<br>Recharging time 3h                              |
| Lamp type:          | LED lamp                                                                                                  |
| LED type:           | 4 x 10 W SMD 5050 4in1 QCL RGBW (homogenous color mix)                                                    |
| Equipment:          | Frost filter                                                                                              |
| DMX channels:       | 3; 4; 6; 8; 11                                                                                            |
| DMX input:          | 3-pin XLR (M) mounting version IP                                                                         |
| DMX output:         | 3-pin XLR (F) mounting version IP                                                                         |
| Cooling:            | Passive convection cooling                                                                                |
| Control:            | Stand-alone; IR remote control; DMX; QuickDMX; RDM; master/slave function; wireless Master/slave function |
| Projection:         | Flicker-free                                                                                              |

|                          |                                                            |
|--------------------------|------------------------------------------------------------|
| PWM frequency:           | 3000 Hz                                                    |
| Carrier frequency:       | 2.4 GHz                                                    |
| DMX fail mode:           | Blackout; hold; static; full on                            |
| Beam angle:              | 8°                                                         |
| Beam angle (1/2 peak):   | 8°                                                         |
| Beam angle (1/10 peak):  | 17°                                                        |
| Housing color:           | Black                                                      |
| Attachment system:       | Mounting bracket<br>Bracket for floor use<br>Omega bracket |
| Display type:            | OLED display                                               |
| Display:                 | Charge status indicator , battery runtime calculation      |
| Diameter mounting holes: | 1 x Ø10mm                                                  |
| Use of brands:           | Built with SEETRONIC connector                             |
| Material:                | Aluminum                                                   |
| Theft protection:        | KENSINGTON LOCK                                            |
| Dimensions:              | Width: 17.9 cm<br>Depth: 15.0 cm<br>Height: 19.8 cm        |
| Weight:                  | 4.57 kg                                                    |
| Noise classification:    | Class 0 (no noise at all)                                  |
| Battery:                 | 1 x button cell 3.0 V CR2032 lithium manganese built-in    |
| Special product:         | Not designed for household room illumination               |
| Intended use:            | Show effect lighting                                       |

#### **ROADINGER Flightcase 4x AKKU IP UP-4 QuickDMX with charging function**

|                          |                                                                                                |
|--------------------------|------------------------------------------------------------------------------------------------|
| Power supply:            | 100-240 V AC, 50/60 Hz                                                                         |
| Power consumption:       | Max. 1150 W                                                                                    |
| Power connection:        | Mains input via IP T-Con (M) mounting version<br>power supply cord with safety plug (provided) |
| Device fuse:             | 5 x 20 mm, F 5 A fuse replaceable                                                              |
| Aluminum profile frames: | 25 mm                                                                                          |
| Case handle:             | 4 pc/pcs                                                                                       |
| Stop hinge:              | 2 pc/pcs                                                                                       |
| Lock:                    | Butterfly lock: 2 pc/pcs with shut-off function                                                |
| Transport aid:           | 4 x castors with 2 locking brakes<br>4 x built-in stacking trays in the cover                  |
| Material:                | Plywood multi-layer glued, 9 mm                                                                |
| Color:                   | Black, laminated                                                                               |
| Device compartment:      | 18 cm x 15.5 cm x 14 cm                                                                        |
| Accessory compartment:   | 7 cm x 43 cm x 14 cm                                                                           |
| Inside dimensions:       | 56 cm x 43 cm x 20 cm                                                                          |
| Dimensions:              | Width: 60 cm                                                                                   |

|                     |                                 |
|---------------------|---------------------------------|
|                     | Depth: 47.5 cm                  |
|                     | Height: 41 cm                   |
| Weight:             | 15.25 kg                        |
| Cable construction: | 3 x 1.5 mm <sup>2</sup> H07RN-F |
| Cable length:       | 1.2 m detachable                |

### Scope of delivery:

#### **4 x EUROLITE AKKU IP UP-4 QCL Spot QuickDMX MK2**

1 x spotlight  
 1 x user manual  
 1 x power cord  
 1 x frost filter  
 1 x remote control  
 1 x battery  
 2 x knurled screw  
 1 x mounting bracket  
 2 x screw  
 4 x washer  
 1 x omega bracket

#### **1 x ROADINGER Flightcase 4x AKKU IP UP-4 QuickDMX with charging function**

1 x case  
 1 x power cord  
 4 x castors  
 16 x screw  
 1 x key  
 1 x user manual