

EUROLITE LED PFE-60 WW Profile Spot 20-50°

Profile spotlight, 60 W WW LED, manual zoom, shutter blades, CRI>90

Art. No.: 40001712

GTIN: 4026397715576



Features:

- 1 LED 60 W COB (chip-on-board) warm white (WW)
- Zoom manual; focus manual
- Dimmer electronic; pulse-width modulation variable
- Strobe effect
- The device is cooled by temperature-controlled fan
- Control via stand-alone; master/slave function; DMX; RDM
- Fixtures available for Light Captain
- Flicker-free
- With a beam angle of 20° - 50°
- Very high color rendering index (CRI)
- With mounting bracket
- Multicolor OLED display
- For application areas such as: Stage; wedding/gala/events; Trade fair and shop fitting; restaurants, bars and hotels; theater; rental; video and photography
- Very quiet working noise
- Application possibility: Suspended; on stand

Logistic

EAN / GTIN: 4026397715576

Weight: 3,77 kg

Length: 0.42 m

Width: 0.20 m

Height: 0.22 m

Technical specifications:

Power supply:	100-240 V AC, 50/60 Hz
---------------	------------------------

Power consumption:	60 W
--------------------	------

IP classification:	IP20
--------------------	------

Protection class:	Protection class I
-------------------	--------------------

Power connection:	Fixed power supply cord with safety plug
Fuse:	T 1 A fuse replaceable
Lamp type:	LED lamp
LED type:	1 x 60 W COB (chip-on-board) warm white (WW)
Equipment:	Zoom manual; focus manual
DMX channels:	1; 2
DMX input:	3-pin XLR (M) mounting version
DMX output:	3-pin XLR (F) mounting version
Cooling:	Temperature-controlled fan
Control:	Stand-alone; master/slave function; DMX; RDM
Fixtures available for:	Light Captain
Projection:	Flicker-free
Beam angle:	20° - 50°
Beam angle (1/2 peak):	20 - 50°
Beam angle (1/10 peak):	20 - 50°
Color temperature:	3200K
Color rendering index (CRI):	94 Ra
Lamp life:	50000 h
Luminous flux:	4500 lm
Housing color:	Black matte
Attachment system:	Mounting bracket
Display type:	Multicolor OLED display
Material:	Aluminum casting; metal
Dimensions:	Length: 35.0 cm Width: 16.0 cm Height: 25.5 cm
Weight:	3.20 kg
Noise classification:	Class 1 (very slight noise, suitable for noise-sensitive environments)
Energy efficiency class (A - G):	F
EPREL-Nr:	1597557
Diameter mounting holes:	1 x Ø12mm
Material:	Metal, 3 mm
Gobos:	Outside diameter 37mm Image diameter 25mm
Material:	Aluminum, 0.5 mm; plastic
Dimensions:	Diameter: Ø 3 cm

Scope of delivery:

1 x spotlight
1 x gobo holder
1 x user manual