

EUROLITE LED PFE-60 RGBW Profile Spot 9-25°

Profile spotlight, 80 W 4in1 LED (RGBW), manual Zoom, shutter blades

Art. No.: 40001731 GTIN: 4026397715545











List price: 546.21 €

incl. 19% VAT.

Features:

- 1 powerful LED 80 W COB (chip-on-board) 4in1 QCL RGBW (homogenous color mix)
- Zoom manual; focus manual
- Color blend stepless; color change adjustable; color fade adjustable; Dimmer electronic; pulsewidth modulation variable
- Strobe effect
- The device is cooled by temperature-controlled fan
- Control via stand-alone; DMX; RDM; master/slave function
- Preprogrammed in Light Captain
- Flicker-free
- With a beam angle of 9° 25°
- Variable color temperature 1800 K 10000 K
- With mounting bracket
- Multicolor OLED display
- For application areas such as: Theater; stage; installation; rental
- Very quiet working noise
- Application possibility: Suspended; on stand

Package contents

- 1 x spotlight, 1 x gobo holder, 1 x user manual

Technical specifications:

Power supply:	100-240 V AC, 50/60 Hz
Power consumption:	60 W
IP classification:	IP20

Logistic

EAN / GTIN: 4026397715545

Weight: 3,95 kg Length: 0.48 m Width: 0.20 m Heigth: 0.21 m

Protection class:	Protection class I
Power connection:	Fixed power supply cord with safety plug
Fuse:	5 x 20 mm, T 1 A fuse replaceable
Lamp type:	LED lamp
LED type:	1 x 80 W COB (chip-on-board) 4in1 QCL RGBW (homogenous color mix)
Flash rate:	1 - 19 Hz
Equipment:	Zoom manual; focus manual
DMX channels:	5; 6; 9
DMX input:	1 x 3-pin XLR (M) mounting version
DMX output:	1 x 3-pin XLR (F) mounting version
Cooling:	Temperature-controlled fan
Control:	Stand-alone; DMX; RDM; master/slave function
Preprogrammed in:	Light Captain
Projection:	Flicker-free
Beam angle:	9° - 25°
Beam angle (1/2 peak):	9 - 25°
Beam angle (1/10 peak):	9 - 25°
Color temperature:	1800K - 10000K adjustable
Lamp life:	50000 h
Luminous flux:	5000 lm
Housing color:	Black
Attachment system:	Mounting bracket
Display type:	Multicolor OLED display
Dimensions:	Length: 42,5 cm Width: 16,0 cm Depth: 25,5 cm
Weight:	3,40 kg
Noise classification:	Class 1 (very slight noise, suitable for noise- sensitive environments)
Energy efficiency class (A - G):	F
EPREL-Nr:	1597536
Gobo holder	
Gobos:	Outside diameter 37mm Image diameter 25mm