

EUROLITE AKKU PLL-168 WW/CW Panel

Battery-powered surface light with 168 dual white LEDs, QuickDMX port and barn doors

Art. No.: 40001845

GTIN: 4026397703016



List price: 391.51 €

incl. 19% VAT.

Features:

- 84 powerful LEDs 0,5 W SMD 2835 cold white (CW)
- 84 powerful LEDs 0,5 W SMD 2835 warm white (WW)
- Variable color temperature 2800 K - 6500 K
- 4 barn doors to avoid blinding the audience and for protection during transport
- Dimmer electronic; pulse-width modulation variable; Energy-saving mode
- Battery operation up to 8h depending on program used
- Integrated show programs
- Direct color selection for 38 preset colors
- The device is cooled by passive convection cooling
- Control via stand-alone; Sound to light via Microphone; Master/slave function; DMX; Quick select potentiometer for brightness and color temperature; QuickDMX via USB (optional); W-DMX by wireless solution via USB (optional); CRMX by LumenRadio via USB (optional)
- Flicker-free
- With a beam angle of 120°
- Very high color rendering index (CRI)
- With Mounting bracket
- Slim, rugged metal housing
- 4 digit 7-segment LED display
- Preprogrammed in Light Captain
- Cordless, flexible and versatile
- Mains input and output for power linking up to 8 units
- For application areas such as: Video and photography; Stage; mobile use; small rental
- Silent operation
- Application possibility: Suspended; on stand

Package contents

- 1 x spotlight, 1 x user manual, 1 x power cord

Logistic

EAN / GTIN: 4026397703016

Weight: 3,90 kg

Length: 0.40 m

Width: 0.25 m

Height: 0.15 m

Technical specifications:

| | |
|------------------------------|---|
| Power supply: | 100-240 V AC, 50/60 Hz |
| IP classification: | IP20 |
| Protection class: | Protection class I |
| Power connection: | Mains input via P-Con (blue), mounting version power supply cord with safety plug (provided) |
| Power output: | P-Con (gray), mounting version |
| Fuse: | 5 x 20 mm, T 1 A Fuse replaceable |
| Battery pack type: | 1 x lithium ion 22,2 V, 4400 mAh, 97,68 Wh |
| Battery pack: | Battery operation up to 8h depending on program used Recharging time 4h |
| Lamp type: | LED lamp |
| LED: | 84 x 0,5 W SMD 2835 cold white (CW) 84 x 0,5 W SMD 2835 warm white (WW) |
| Color temperature: | 2800K - 6500K adjustable |
| Flash rate: | 0 - 20 Hz |
| DMX channels: | 2; 4; 6 |
| DMX input: | 3-pin XLR (M) mounting version |
| DMX output: | 3-pin XLR (F) mounting version |
| Cooling: | Passive convection cooling |
| Control: | Stand-alone; Sound to light via Microphone; Master/slave function; DMX; Quick select potentiometer for brightness and color temperature; QuickDMX via USB (optional); W-DMX by wireless solution via USB (optional); CRMX by LumenRadio via USB (optional) |
| Preprogrammed in: | Light Captain |
| Projection: | Flicker-free |
| Beam angle: | 120° |
| Beam angle (1/2 peak): | 120° |
| Color rendering index (CRI): | 92 Ra |
| Housing color: | Black |
| Attachment system: | Mounting bracket |
| Display type: | 4 digit 7-segment LED display |
| Dimensions: | Width: 35,7 cm Depth: 11,7 cm Height: 22,0 cm |
| Weight: | 3,60 kg |
| Noise classification: | Class 0 (no noise at all) |
| Photobiological safety: | Risk Group 0 |
| Legal specifications | |
| Special product: | Not designed for household room illumination |
| Intended use: | Show effect lighting |